

Routan Perfect Delivery Inspection (PDI) - Technician and Detailer Inspections

Stock No.:	Dealer Number:	R.O. No.:	
VIN:	Dealer Nottiber	R.O. No	·
VIII			
Technician Inspection			
Initial Inspection (A workshop maintainer/charg	er must be used):	☐ Remove contents of Trailer Tow Package from	m factory had displaying MOPAR®
 □ Check hood latch and safety catch □ Install ignition off-draw fuse □ Test and auto charge battery with INC-940 using the "4 use "Other" test mode to select CCA rating per TB 2018 Record and document test code □ Install front license plate bracket if required □ Check engine coolant level (engine off/cold). Do not exonly OAT specified coolant MY 2013-2014) □ Check brake and power steering fluid levels. Do not exo □ Top-off windshield washer solvent □ Check engine oil level □ Adjust tire pressure to specification on vehicle sticker at until day before delivery) □ Torque wheels to specification. (Refer to ElsaWeb) □ Retrieve radio code from ElsaWeb and check for any op RVUs. Perform if applicable 	694. ceed max fill line (Use eed max fill line "B" Pillar. (Do not set	logo, discard factory bag, place contents intidepartment. (Routan with Trailer Tow Packag. Check third row operation of folding seat policine Check doors / exterior locks. Install Warranty and Maintenance Booklet. Install California Emissions Warranty Booklet. Install Applicable Tire Warranty Brochure. Verify child safety lock is set to unlocked pos. Check proper fuel door operation. Check proper tailgate operation using the real place tow hook and wheel lock adapter in totapplicable. Install rear tow hook cover (if applicable). Raise vehicle and perform a visual inspection damage. Remove suspension blocks located in the suspension.	o new bag received from parts ge only) ower / manual t ition emote and the exterior button bol kit. Discard 2nd tow hook (if
□ Verify vehicle is equipped with spare tire	atialliid.	applicable)	spensions coil springs (if
Make sure hands and clothing are clean before ∈ □ Disable vehicle transport mode	entering the vehicle	Road Test:	
□ Check all instrument cluster warning lights by cycling the □ Check that all keys and remotes lock, unlock, and start solution □ Check operation of all exterior lights using a mirror or a □ Check front windshield wiper/washer functions □ Check function of tilt and telescopic features of steering □ Set clock, date, and year (if applicable) □ Reset inspection/oil service interval □ Verify language and units of measurement (F°) in multi-f Navigation system (if applicable) □ Verify radio operates in AM, FM, CD, MP3 and Satellite applicable radio buttons and steering wheel controls □ Set memory preset stations to AM and FM stations with good by using the scan feature □ Check function of all power windows (including sunroof One-Touch feature, and check function of pinch protect □ Check seat belts, seat adjusters, heated seats (if applica □ Install Start/Stop button (found in the By-Pack in the third ignition switch. (Routan SEL only)	vehicle nother technician wheel unction display and Radio modes using good reception quality if equipped), program ion feature ble)	□ Odometer reading before road test: □ Check engine performance and acceleration □ Store current tire pressure values for TPMS b glove box for a minimum of 2 seconds or se □ Check all menu settings in cluster for correct calibration (if applicable) □ Check automatic transmission operation, inc Tiptronic® □ Check brake system function (including ABS) operation – engage and disengage □ Check steering for pulling, vibration and stee □ Check climate control for mode functions (D operation and heater operation After Road Test: □ Verify no warning lights are illuminated □ Retrieve fault memory, correct any DTC's, see Save and attach printout to Repair Order	y pressing the SET button in the ting in MFI if applicable compass zone and unit - cluding automatic shift lock and //Electronic parking brake ering wheel alignment tefrost/Vent/Floor), air conditioning

I certify that all operations have been completed and that this vehicle has been prepared in accordance with Volkswagen procedures and quality standards.

☐ Dealer 30-day maintenance process has been initiated

☐ All product updates have been checked

Dealership Authorized Signature:

Detailer Process

LAIGHOL.	
□ Remove RAPGARD protective covering (best removed 60°-80F°)	Interior:
☐ Wash/dry vehicle exterior (convertibles: do not use high pressure washer above	☐ Clean all glass, mirrors, and sunroof (if applicable)
door sills or above rear window seals)	☐ Remove all trim protection, coverings, stickers, and decals - Do not remove
□ Check for water leaks	airbag warning triangle/warning labels
□ Clean alloy wheels/tires, remove any adhesive on wheels	☐ Check upholstery and clean as required
□ Inspect paint surfaces, moldings and glass. Remove any adhesive, tar, or	☐ Check for excessive grease on seat tracks and clean as required
residue. If any defects (scratches/dings/dents/body damage) are found,	☐ Check all interior surfaces and compartments (including sun visors and
contact Service Manager to schedule immediate repair.	headliner) and clean as required
□ Wax vehicle using 3M Perfect-It™ Paste Wax or equivalent	□ Vacuum carpet
□ Clean all glass and mirrors using 3M Gloss enhancer, cleaner clay or equivalent	☐ Check luggage compartment and vacuum
□ Wipe door jambs	☐ Install front/rear floor mats (including locking clip / tabs), check color match. If monster mats are installed, please put factory mats in trunk.
l Index Head.	

I certify that all operations have been completed and that this vehicle has been □ All product updates have been checked	n prepared in accordance with Volkswagen procedures and quality standards. □ Dealer 30-day maintenance process has been initiated
Dealership Authorized Signature:	Date:

Original – Retain with Repair Order in Service File

 $\hfill\square$ Wipe down engine compartment (no high pressure wash). Stay clear of HV components on Hybrids.

VW.ROUTAN.PDITECHCHECK. 09.10.2013