



NUMBER: 05-003-13

GROUP: Brakes

DATE: February 28, 2013

This bulletin is supplied as technical information only and is not an authorization for repair. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, or otherwise, without written permission of Chrysler Group LLC.

THIS SERVICE BULLETIN IS ALSO BEING RELEASED AS RAPID RESPONSE TRANSMITTAL (RRT) 13-015. ALL APPLICABLE SOLD AND UN-SOLD RRT VIN'S HAVE BEEN LOADED. TO VERIFY THAT THIS RRT SERVICE ACTION IS APPLICABLE TO THE VEHICLE, USE VIP OR PERFORM A VIN SEARCH IN TECHCONNECT. ALL REPAIRS ARE REIMBURSABLE WITHIN THE PROVISIONS OF WARRANTY.

SUBJECT:

Front And/Or Rear Brake Noise (Squeal)

OVERVIEW:

This bulletin involves changing front and rear brake pads to correct a brake squeal noise.

MODELS:

2013 (LD) Charger

NOTE: This bulletin applies to vehicles in police fleet usage only (sales code AHB) built before November 29, 2012 (MDH 1129XX).

SYMPTOM/CONDITION:

The customer may experience a squealing noise during braking coming from the front and/or rear of the vehicle.

DIAGNOSIS:

If a customer's VIN is listed in VIP or your RRT VIN list, perform the repair. For all other customers that describe the symptom/condition, perform the Repair Procedure.

PARTS REQUIRED:

Qty.	Part No.	Description
1	68147681AA	PAD KIT, Front Disc Brake (Contains Pads and Slippers)
1	68001440AB	PAD KIT, Rear Disc Brake

REPAIR PROCEDURE:

NOTE: Be sure to review all warnings and cautions before proceeding, refer to the detailed information available in DealerCONNECT> TechCONNECT under: Service Info> 05- Brakes - Warning and 05- Brakes - Caution.

1. Raise the vehicle on a suitable hoist. Refer to the detailed service procedures available in DealerCONNECT> TechCONNECT under: Service Info> 04- Vehicle Quick Reference> Hoisting> Standard Procedure> Hoisting.
2. Remove and replace front brake pads (p/n 68147681AA). Refer to the detailed removal procedures available in DealerCONNECT> TechCONNECT under: Service Info> 05- Brakes> Brakes, Base> Hydraulic/Mechanical> Pads, Brake, Front> Removal/Installation.
3. Remove and replace rear brake pads (p/n 68001440AB). Refer to the detailed removal procedures available in DealerCONNECT> TechCONNECT under: Service Info> 05- Brakes> Brakes, Base> Hydraulic/Mechanical> Pads, Brake, Rear> Removal/Installation.

POLICY:

Reimbursable within the provisions of the warranty.

TIME ALLOWANCE:

Labor Operation No:	Description	Amount
05-70-22-9D	Pads, Disc Brake - Replace Front and Rear (2 - Skilled)	0.8 Hrs.

FAILURE CODE:

ZZ	Service Action
----	----------------