

 Connection offline

## Technical product information

<b>Topic</b>	Accessory Tyre Valve Caps - difficult to remove
<b>Market area</b>	Worldwide Bentley (1WBE)
<b>Brand</b>	Bentley
<b>Transaction No.</b>	2033864/1
<b>Level</b>	EH
<b>Status</b>	Approval
<b>Release date</b>	

### New customer code

Object of complaint	Complaint type	Position
Running gear -> Wheels, tyres, tyre pressure monitoring -> Tyre valve	component / consumables -> damaged	> not specified <

### New workshop code

Object of complaint	Complaint type	Position
Running gear -> Wheels, tyres, tyre pressure monitoring -> Tyre valve	component / consumables -> damaged	> not specified <

## Vehicle data

### Continental Series

#### Sales types

Type	MY	Brand	Designation	Engine code	Gearbox code	Final drive code
39**	2012	E		*	*	*
39**	2013	E		*	*	*
39**	2014	E		*	*	*
39**	2015	E		*	*	*
39**	2016	E		*	*	*
39**	2017	E		*	*	*
39**	2018	E		*	*	*
3W**	2004	E		*	*	*
3W**	2005	E		*	*	*
3W**	2006	E		*	*	*
3W**	2007	E		*	*	*
3W**	2008	E		*	*	*
3W**	2009	E		*	*	*
3W**	2010	E		*	*	*
3W**	2011	E		*	*	*


3W**	2012	E		*	*	*
3W**	2013	E		*	*	*
3W**	2014	E		*	*	*
3W**	2015	E		*	*	*
3W**	2016	E		*	*	*
3W**	2017	E		*	*	*
3W**	2018	E		*	*	*

**Chassis numbers**

Manufacturer	Filler	Type	Filler	MY	Factory	From	To	Prod from	Prod to
SCB	**	**	*	*	*	000001	999999		

**Documents**

Document name
master.xml
master.doc



Technical product information

Transaction No.: 2033864/1

Accessory Tyre Valve Caps - difficult to remove

---

### **Customer statement / workshop findings**

Unable to remove Accessory tyre valve cap (part number 3W0 601 367)

### **Technical background**

We have observed instances where these have been difficult to remove once fitted caused by corrosion.

The valve stem itself is made from aluminium and the accessory tyre valve caps are chromium plated brass, it is possible under certain environmental conditions, particularly winter road salt, for corrosion to take place between these dissimilar metals.

### **Production change**

N/A.

### **Measure**

The solution is for you to apply a thin smear of silicon-based grease, such as Dow Corning high vacuum grease, to the external threads of the valve stem prior to fitting the accessory valve cap. Grease should be applied any time the cap is removed and grease is not evident