

Subject

# Oil Viscosity Applicability and Change Interval Guide

Market

**USA**

Service Category

**General**

Section

**Maintenance**

Applicability

**2010 -2014 All Models**

## APPLICABLE VEHICLES

2010 – 2014 Model Year Vehicles

## CONDITION

Starting with the 2010 Model Year, Toyota began a gradual transition to the use of synthetic 0w-20 viscosity engine oil. There are multiple benefits of this oil, including:

- Reduced friction and wear on engine surfaces
- Improved fuel economy
- Reduction in waste oil stream (in vehicles approved for 10,000 mile oil change intervals)
- Reduced maintenance cost (in vehicles approved for 10,000 mile oil change intervals)

Due to the improved performance and durability of 0w-20 synthetic oil, Toyota has extended the oil change intervals to 10,000 miles for most vehicles that require this oil. With this change, the following should be noted:

- The 2TR-FE (4Runner / Tacoma) and the 3UR-FBE (Flex Fuel Tundra / Sequoia) are the exceptions to this new change interval program; these engines have not been approved for the 10,000 mile interval at this time. A 5,000 mile oil change interval is still required for these vehicles. Also, the Flex Fuel 3UR-FBE requires a 2,500 mile interval when operated on E85.
- Only Toyota vehicles in which 0w-20 oil is mandatory (except for the 2TR-FE & 3UR-FBE Engines) have been approved for extended oil change intervals.
- Vehicles in which 0w-20 is an option to 5w-20 (or 5w-30) will continue to require 5,000 mile change intervals, even if 0w-20 oil is used.
- In the case of vehicles with 10,000 mile oil change intervals, the 5,000 mile service interval has not been eliminated. The traditional 5,000 mile maintenance procedures (such as tire rotation) will continue to be required, and the fluid levels (including engine oil) will need to be checked and adjusted at this time.
- If the vehicle operation meets the standard criteria for "Special Operating Conditions" such as: driving off-road, on dirt roads, towing a trailer, making repeated short trips under 32° F, or extensive idling; the engine oil must be replaced at 5,000 mile intervals, regardless of oil used.

## RECOMMENDATIONS

Please follow the charts on pages 2 & 3 to determine the proper oil viscosity, fill quantity, and proper change interval for 2010-2014 Model Year Toyota vehicles under non-severe usage.

Subject

Market

# Oil Viscosity Applicability and Change Interval Guide

USA

Applicability

2010 -2014 All Models

	Vehicle	Engine	Model Year	Oil	Capacity w/Filter Change	Change Interval
<b>TRUCK</b>	<b>4Runner</b>	1GR-FE	2010-2014	0w-20	6.6	10,000 Miles
		2TR-FE	2010	0w-20	6.1	<b>5,000 Miles</b>
	<b>FJ Cruiser</b>	1GR-FE	2010-2014	0w-20	6.4	10,000 Miles
	<b>Highlander</b>	1AR-FE	2010-2014	5w-20 or 0w-20	4.7	5,000 Miles
			2010	<b>NOTE 1</b>	6.4	5,000 Miles
		2GR-FE	2011-2014	0w-20	6.4	10,000 Miles
	<b>Highlander HV</b>	3MZ-FE	2010	5w-20 or 0w-20	5.0	5,000 Miles
		2GR-FXE	2011-2014	0w-20	6.4	10,000 Miles
	<b>Land Cruiser</b>	3UR-FE	2010	5w-20 or 0w-20	<b>NOTE 2</b>	5,000 Miles
			2011		7.9	5,000 Miles
			2013-2014	0w-20	7.9	10,000 Miles
	<b>RAV4</b>	2AR-FE	2010-2012	5w-20 or 0w-20	4.7	5,000 Miles
		2GR-FE	2010-2012	5w-30	6.4	5,000 Miles
		2AR-FE	2013-2014	0w-20	4.6	10,000 Miles
	<b>Sequoia</b>	1UR-FE	2010-2013	0w-20	7.9	10,000 Miles
		3UR-FE	2010-2011	5w-20 or 0w-20	7.9	5,000 Miles
			2012-2014	0w-20	7.9	10,000 Miles
		3UR-FBE	2010-2011	5w-20 or 0w-20	7.9	<b>5,000 Miles / Note 3</b>
			2012-2014	0w-20	7.9	
	<b>Sienna</b>	1AR-FE	2011-2013	0w-20	4.7	10,000 Miles
2GR-FE		2010	5w-30	6.4	5,000 Miles	
		2011-2014	0w-20	6.4	10,000 Miles	
<b>Tacoma</b>	1GR-FE	2010-2014	5w-30	<b>NOTE 4</b>	5,000 Miles	
	2TR-FE	2010	5w-20 or 0w-20	6.1	5,000 Miles	
		2011-2014	0w-20	6.1	<b>5,000 Miles</b>	
<b>Tundra</b>	1GR-FE	2010	5w-30	<b>NOTE 5</b>	5,000 Miles	
		2011-2014	0w-20	6.4	10,000 Miles	
	1UR-FE	2010-2014	0w-20	7.9	10,000 Miles	
		3UR-FE	2010-2011	5w-20 or 0w-20	7.9	5,000 Miles
	2012-2014		0w-20	7.9	10,000 Miles	
	3UR-FBE	2010-2011	5w-20 or 0w-20	7.9	<b>5,000 Miles / Note 3</b>	
2012-2014	0w-20	7.9				

**NOTE 1.** With Towing Package - 5w-30 / Without Towing Package - 5w-20

**NOTE 2.** If dip stick color is BLUE, fill quantity is 7.4 quarts. If dip stick is GREEN, fill quantity is 7.9 quarts

**NOTE 3.** Flex fuel vehicles that have been operated with E85 must have engine oil changed every 2,500 miles

**NOTE 4.** 4.8 quarts for 2WD (except Pre-Runner), 5.5 quarts for 4X4 and Pre-Runner

**NOTE 5.** Vehicles built through Oct 2009 receive 4.8 quarts and vehicles built from Nov 2009 receive 5.5 quarts

Subject

Market

**Oil Viscosity Applicability and Change Interval Guide**
**USA**

Applicability

**2010 -2014 All Models**

	Vehicle	Engine	Model Year	Oil	Capacity w/ Filter Change	Change Interval	
<b>CAR</b>	<b>Avalon</b>	2GR-FE	2010-2012	5w-30	6.4	5,000 Miles	
			2013-2014	0w-20	6.4	10,000 Miles	
	<b>Avalon HV</b>	2AR-FXE	2013-2014	0W-20	4.6	10,000 Miles	
	<b>Camry</b>	2AR-FE	2010-2014	0w-20	4.7	10,000 Miles	
			2GR-FE	2010-2011	5w-30	6.4	5,000 Miles
				2012-2014	0w-20	6.4	10,000 Miles
	<b>Camry HV</b>	2AZ-FXE	2010-2011	5w-20 or 0w-20	4.5	5,000 Miles	
			2012-2014	0w-20	4.5	10,000 Miles	
	<b>Corolla</b>	2ZR-FE	2010	5w-20 or 0w-20	4.4	5,000 Miles	
			2011-2014	0w-20	4.4	10,000 Miles	
		2AZ-FE	2010	5w-20 or 0w-20	4.0	5,000 Miles	
	<b>Matrix</b>	2ZR-FE	2010	5w-20 or 0w-20	4.4	5,000 Miles	
			2011-2013	0w-20	4.4	10,000 Miles	
		2AZ-FE	2010-2013	5w-20 or 0w-20	4.0	5,000 Miles	
	<b>Prius</b>	2ZR-FXE	2010-2014	0w-20	4.4	10,000 Miles	
	<b>Prius C</b>	1NZ-FXE	2012-2014	0w-20	3.9	10,000 Miles	
	<b>Prius PHV</b>	2ZR-FXE	2012-2014	0w-20	4.4	10,000 Miles	
	<b>Prius V</b>	2ZR-FXE	2012-2014	0w-20	4.4	10,000 Miles	
<b>Venza</b>	1AR-FE	2010-2012	5w-20 or 0w-20	4.7	5,000 Miles		
		2013-2014	0w-20	4.7	10,000 Miles		
	2GR-FE	2010-2011	5w-30	6.4	5,000 Miles		
		2012-2014	0w-20	6.4	10,000 Miles		
<b>Yaris</b>	1NZ-FE	2010-2014	5w-30	3.9	5,000 Miles		