15B-0130-14

# TOYOTA CAMRY/CAMRY HV

## 2015 PRE-DELIVERY SERVICE CHECK SHEET September 2014

BEFORE INSPI	ECTION	OK Adjust/	Repair	UNDER VEH	ICLE (ON HOIST)	OK Adjust Repair	
01 Install Short Pin* (Hawaii, Puerto Rico, Saipan, Guam, American Samoa)				wheel film*	orake anti-rust covers/anti-corrosion	80	
FUNCTIONAL OPERATION				02 Inspect tires for defects/damage 03 Initialize or verify Tire Pressure Warning System (TPWS) operation (see page 2) 04 Install wheel covers/caps/spare tire wheel covers* 05 Check hybrid transmission fluid level*. 06 Inspect for fuel, oil, coolant, and other fluid leaks 07 Inspect under the vehicle for damage, rust, etc. 08 Visually check bolts and nuts on chassis and powertrain for looseness. 09 Install rubber body plugs (stored in glove box or center console)*. 10 Install front wheel opening extension pads (see page 2)			
Apply parking brake and cycle ignition "IG-ON"; place gear selector in revitum on lights and rear defogger. Unlock doors, release fuel door.							
01 Check dome, courtesy, map, and sun visor lights* 02 Check warning/indicator lights, gauges, and horn 03 Check windshield wipers and washers. 04 Check headlights, instrument lights, turn signals, emergency flashers, and brake lights. 05 Check inside/outside rear view mirror operation/adjustment*. 06 Check cigarette lighter* and power outlets. 07 Check audio/navigation*/backup camera* systems and							
		00	J	ROAD TEST			
set clock	set clock.  8 Verify Entune/Navigation software version (Display Audio, Non-HDD Type only)*			A complete road test I	nelps assure customer satisfaction  Drive vehicle over an and driving conditions  Check for unusual noise an dings		
WALKAROUND INSPECTION				Reading Before Test: Reading After Test:			
Start at left front door Check window and door lock operation (from master switch, if equipped). Continue around vehicle in a counterclockwise of checking each door and window operation, child door locks, seat belts, condition, all lights, luggage compartment contents. Finish by checking he aim and continue into UNDER HOOD checks.			or ht	01 Check cold engine operation			
01 Check Smart Key System  02 Check door and door lock operation, including each wireless remote control/theft deterrent system*.  03 Check window operation.  04 Check that engine starts with all keys  05 Check that child safety door locks are in normal (unlocked) position  06 Check seats and seat belt operation				07 Inspect for abnormal noise and vibration 08 Inspect for squeaks and rattles 09 Check Blind Spot Monitor System* 10 Check front and rear* heater and A/C operation 11 Check cruise control operation* 12 Check front seat heater/ventilation operation* 13 Set/calibrate compass* (see page 2)		0000000	
07 Check rear defogger/rear view mirror defogger*		88		FINAL INSPECTION AND CLEANING			
O8 Check side marker, tail, backup, and license plate lights O9 Check luggage compartment light* and trim appearance O Adjust spare tire pressure, inspect for damage, and check jack and tool installation				01 Remove interior protective covers, unnecessary labels, tags, etc. (Remove just before delivery to customer) 02 Visually inspect all interior parts for installation, damage, fit, dirt, etc			
UNDER HOOD				retaining clips	s*		
01 Check engine oil level 02 Check brake fluid level 03 Check engine coolant level 04 Check inverter coolant level* 05 Check windshield washer fluid level 06 Check battery state-of-charge using Digital Battery System Analyzer (SOC Reading:%) 07 Inspect for fuel, oil, coolant, and other fluid leaks		00000		<ul> <li>04 Verify green light is illuminated on SOS (Safety Conn button*</li></ul>	ard™ and clear protective bumper film* in vehicle		
BATTERY MAINTENANCE*			left corner				
01 Perform HV battery check and maintenance			10 Place Owner's Guide & first aid kit portfolio* in glove to the portfolio to the portfoli			8-1	
* Inspect or install when equipped/required.			12 Install front license plate & mounting bracket* (see page 2)				
Completion and retention of this form is required to comply with Toyota's Warranty Portion and retention of this form is required to comply with Toyota's Warranty Portion and retention of this form is required to comply with Toyota's Warranty Portion and retention of this form is required to comply with Toyota's Warranty Portion and retention of this form is required to comply with Toyota's Warranty Portion and retention of this form is required to comply with Toyota's Warranty Portion and retention of this form is required to comply with Toyota's Warranty Portion and retention of this form is required to comply with Toyota's Warranty Portion and Retention and Reten				We hereby certify that all items on this form have been checked and corrected for proper operation as required.			
Date Dealer Name				Dealer Code	Vehicle Identification Number (Sticker)		
Date	Douisi Mairie			Dealer Code	vernore racinimization realitizer (Sticker)		

### TPWS INITIALIZATION (FOR MODELS EQUIPPED WITH A RESET SWITCH)

Refer to the Repair Manual for the initialization procedure (Camry/Camry HV). Please note the spare tire does not have a TPWS sensor.

#### NOTE

To adjust the tire pressure correctly when the outside temperature is significantly colder than shop temperature, perform a Health Check using Techstream and select the Compensation Tire Pressure" checkbox. Compensation pressures will be displayed on the Health Check results screen. Adjust the tire pressure when the tires are cold.

## TPWS OPERATION VERIFICATION

- Connect Techstream to DLC3.
- 2. Adjust all tires (except the spare tire) to the standard tire inflation pressure, as indicated on the tire and loading information label on the vehicle.

#### NOTE

To adjust the tire pressure correctly when the outside temperature is significantly colder than shop temperature, perform a Health Check using Techstream and select the Compensation Tire Pressure" checkbox. Compensation pressures will be displayed on the Health Check results screen. Adjust the tire pressure when the tires are cold.

- 3. Cycle the ignition switch to the "IG-ON" mode.
- 4. Check the tire pressure of all tires using Techstream. If the tire pressure values cannot be displayed, the system is NOT operating properly. Refer to the Repair Manual.

### FRONT WHEEL OPENING EXTENSION PAD INSTALLATION

The front wheel opening extension pad set (right and left front wheel opening extension pads and 2 Tapping Screws) is loaded in the luggage compartment at the assembly plant to avoid damage in transit.

- Remove the 2 Tapping Screws from the engine under cover (the screws will be reused for installation).
- 2. Place the left front wheel opening extension pad on the installation position as shown and tighten the 3 Tapping Screws.

#### NOTE


- There is a distinguishable mark on each pad.
- Do not interchange the tapping screws A and B.
- 3. Repeat steps 1 and 2 for the right side.


Tapping Screws A: Nominal Length: 23.0 mm (0.91 in.)

Diameter: 6.0 mm (0.24 in.)

Tapping Screws B: Nominal Length: 16.0 mm (0.63 in.) Diameter: 6.0 mm (0.24 in.)

Washer Outside Diameter: 18.0 mm (0.71 in.) Washer Outside Diameter: 20.0 mm (0.79 in.)





## COMPASS CALIBRATION

Refer to the Repair Manual for the Calibration procedure (Camry / Camry HV) for vehicles equipped with a compass in the rear view mirror.

#### NOTE

- Do NOT perform calibration of the compass in a place where the Earth's magnetic field is subject to interference (underground parking, under a steel tower, between buildings, roof parking, near a railroad crossing, near a large vehicle, etc.).
- During calibration, do NOT operate electric systems (moon roof, power windows, etc.) as they may interfere with the calibration.

## FRONT LICENSE PLATE & MOUNTING BRACKET\* INSTALLATION


#### Installation Procedure

- 1. Position the front license plate mounting bracket over the lower grille.
- Align the installation holes on the mounting bracket with the dimples on the front of the lower grille.
- Screw in the 4 Long Self-tapping Screws through the slotted and round holes of the mounting bracket, directly into the dimples on the lower grille.
- 4. Insert license plate into tabs on the bracket.
- Align the top holes of the license plate with the rounded holes of the mounting bracket.
- Screw in 2 Short Self-tapping Screws through the license plate holes into the mounting bracket.

Short Self-tapping Screw: 20 mm (0.787 in.) Long Self-tapping Screw: 37 mm (1.456 in.)

#### NOTICE

- Do NOT pre-drill holes into the <u>bumper</u> or <u>mounting bracket</u>.
- Do NOT overtighten the Self-tapping Screws.



- 1 Long Self-tapping Screws
- 2 Front License Plate
- Mounting Bracket
- 3 Dimples
- 4 Short Self-tapping Screws
- 5 License Plate

