

2015 PRE-DELIVERY SERVICE CHECK SHEET

August 2012

	TOTAL DELIVE	1 12	-			August 2014
BEFORE INSP	ECTION	OK	Repai	UNDER VEHICLE (ON HOIST)	OK Adjust/ Repair
01 Install antenna				01 Remove disc brake anti-rust covers/anti-corrosion		
FUNCTIONAL OPERATION				wheel film*		
Apply parking brake and cycle ignition "IG-ON"; place gear selector in reve turn on lights and rear defogger. Unlock doors; release fuel door.			03 Verify Tire Pressure Warning System (TPWS) (se page 2)			80
01 Check dome, courtesy, map, and sun visor lights*			<u>ן</u>	O5 Inspect for fuel, oil, coolant, and other fluid leaks O6 Inspect under the vehicle for damage, rust, etc		00
05 Check inside/out	side rear view mirror operation/	7241-927-932		console)		
	ighter* and power outlets			ROAD TEST		
07 Check audio/navigation*/backup camera* systems and set clock 08 Verify Entune/Navigation software version (Display Audio, Non-HDD Type only)* 09 Check sliding roof* 10 Install shift-lock override button cover				A complete road test helps assure customer satisfaction. Drive vehicle over variety of road surfaces and driving conditions. Check for unusual noise and driving performance.		
			3	Enter Odometer Readings Reading Before Test:	Reading After Test:	
11 Check Rear Seat	Entertainment system operation*]		ation	
WALKAROUND INSPECTION				03 Check engine at normal	during warm-up operating temperature	
Start at left front door. Check window and door lock operation (from master p switch, if equipped). Continue around vehicle in a counterclockwise direction checking each door and window operation, child door locks, seat belts, in condition, all lights, luggage compartment contents. Finish by checking hea aim and continue into UNDER HOOD checks. O1 Check Smart Key System*			n or nt	04 Check automatic transmission operation		000000000
03 Check window operation				FINAL INSPECTION	AND CLEANING	MI
05 Check that child safety door locks are in normal (unlocked) position				01 Remove interior protecti tags, etc. (Remove just I 02 Visually inspect all interi damage, fit, dirt, etc 03 Verify floor mat applice retaining clips* 04 Remove Rapgard™ and 05 Wash and clean vehicle 06 Inspect paint finish for so damage, etc	0 000 0	
UNDER HOOD				07 Inspect exterior body pa	rts for proper installation,	
01 Check engine oil level 02 Check brake fluid level 03 Check engine coolant level 04 Check windshield washer fluid level 05 Check battery state-of-charge using Digital Battery				08 Place oil change sticker left corner	on inside of windshield, top first aid kit portfolio* in glove box ealth Check and mounting bracket* (see	0 000 0
System Analyzer (SOC Reading:%) 06 Inspect for fuel, oil, coolant, and other fluid leaks			5	* Inspect or install when equ	ipped/required.	
	n of this form is required to comply with Toyota's	Warrant	ty P		We hereby certify that all on this form have been ch and corrected for prop	ecked
NAME (DI EACE DOWN)		(B) EAC		DINT	operation as required	
NAME (PLEASE PRINT) Date Dealer Name Dealer Code Vehicle Identification Number (Sticker)						
Date	Dealer Name		1	Dealer Code Vehicle Ide	munication Number (Sticker)	

TIRE PRESSURE WARNING SYSTEM (TPWS) VERIFICATION

- Connect Techstream to DLC3.
- 2. Adjust all tires (except the spare tire) to the standard tire inflation pressure, as indicated on the tire and loading information label on the vehicle.
- 3. Cycle the ignition switch to the "IG-ON" mode.

NOTE

To adjust the tire pressure correctly when the outside temperature is significantly colder than shop temperature, perform a Health Check using Techstream and select the "Compensation Tire Pressure" checkbox. Compensation pressures will be displayed on the Health Check results screen. Adjust the tire pressure when the tires are cold.

- 4. Check the tire pressure of all tires using Techstream. If the tire pressure values cannot be displayed, the system is not operating properly. Refer to the Repair Manual.
- 5. Remove the ID number labels that are attached to each wheel and discard.

NOTE

If the tire pressure values are not properly displayed (example: showing -14 psi, -100 kPa, etc.) the data from the transmitter has not been received.

COMPASS CALIBRATION

Refer to the Repair Manual for the Calibration procedure for vehicles equipped with a compass in the rear view mirror.

NOTE

- Do NOT perform calibration of the compass in a place where the Earth's magnetic field is subject to interference (underground parking, under a steel tower, between buildings, roof parking, near a railroad crossing, near a large vehicle, etc.).
- During calibration, do NOT operate electric systems (moon roof, power windows, etc.) as they may interfere with the calibration.


FRONT LICENSE PLATE AND MOUNTING BRACKET INSTALLATION*

Front License Plate Mounting Bracket: P/N 75101-0T010

- Insert the front license plate into the mounting bracket.
- 2. Align the installation holes on the mounting bracket and front license plate with the dimples on the front bumper.
- 3. Screw in the 2 self-tapping screws directly into the dimples to install the front license plate and mounting bracket.

NOTICE

- · Do NOT pre-drill holes into the bumper.
- · Do NOT overtighten the self-tapping screws.



- 2 Front License Plate Mounting Bracket
- 3 License Plate
- 4 Self-Tapping Screws