1515 00 1 1-14

# TOYOTA HIGHLANDER / HIGHLANDER HV 2015 PRE-DELIVERY SERVICE CHECK SHEET

BEFORE INSPECTION	OK	UNDER VEHICLE (ON HOIST)	August 2014
01 Install Short Pin (see page 2)		01 Remove disc brake anti-rust covers/anti-corrosion	
FUNCTIONAL OPERATION	100	02 Inspect tires for defects/damage	
Apply parking brake and cycle ignition "IG-ON"; place gear selector in reverse; tun and rear defogger. Unlock doors; release fuel door, and release the back door.	n on lights	<ul> <li>O3 Adjust spare tire pressure, inspect for damage, and check jack and tool installation</li> <li>O4 Initialize Tire Pressure Warning System (TPWS)</li> </ul>	
<ul> <li>01 Check dome, courtesy, map, and sun visor lights*</li> <li>02 Check warning/indicator lights gauges, and horn</li> <li>03 Check windshield wipers and washers</li> <li>04 Check headlights, instrument lights, turn signals, emergency flashers, and brake lights</li> <li>05 Check inside/outside rear view mirror operation/</li> </ul>		<ul> <li>OS Install when covers appropriate the when covers</li> <li>O6 Inspect for fuel, oil, coolant, and other fluid leaks</li></ul>	
adjustment 06 Check cigarette lighter* and power outlets		ROAD TEST	a select
<ul> <li>07 Check audio/navigation*/backup camera* systems and set clock</li> <li>08 Check multi-information display</li> <li>09 Install shift-lock override button cover</li> <li>10 Check sliding roof*</li> </ul>		driving performance.	
11 Check Rear Seat Entertainment system operation*			
WALKAROUND INSPECTION Start at left front door. Check window and door lock operation (from ma switch, if equipped). Continue around vehicle in a counterclockwise checking each door and window operation, child door locks, seat be condition, all lights, luggage compartment contents. Finish by checking aim and continue into UNDER HOOD checks.	e directior Its, interio	04 Check transmission operation	
<ul> <li>01 Check Smart Key System.</li> <li>02 Check door and door lock operation, including each wireless remote control/theft deterrent system*</li> <li>03 Check window operation</li> <li>04 Check that engine starts with all keys.</li> <li>05 Check that child safety door locks are in normal (unlocked) position</li> </ul>		pull/flutter         07 Inspect for abnormal noise and vibration         08 Inspect for squeaks and rattles         09 Check front and rear* heater and A/C operation         10 Check cruise control operation*         11 Check front seat heater/ventilation operation*         12 Set/calibrate compass* (see page 2)         13 Initialize parking assist monitor system (see page 2)	
06 Check seats and seat belt operation 07 Check rear defogger/rear view mirror defogger* 08 Check side marker, tail, backup, and license plate lights 09 Check luggage compartment trim appearance 10 Check headlight aim		FINAL INSPECTION AND CLEANING           01 Remove interior protective covers, unnecessary labels	
UNDER HOOD	100	retaining clips*	00
01 Check engine oil level.         02 Check brake fluid level.         03 Check engine coolant level.         04 Check inverter coolant level*         05 Check windshield washer fluid level.         06 Check battery state-of-charge using Digital Battery         System Analyzer (SOC Reading:%)%)         07 Inspect for fuel, oil, coolant, and other fluid leaks		<ul> <li>04 Remove Rapgard<sup>™</sup> and clear protective bumper film*</li> <li>05 Wash and clean vehicle</li></ul>	
BATTERY MAINTENANCE*		09 Place Owner's Guide & first aid kit portfolio* in glove b	
01 Perform HV battery check and maintenance		(See page 2)	
* Inspect or install when equipped/required.		11 Perform Techstream Health Check	
Completion and retention of this form is required to comply with Toyota's Warranty Policy.       We hereby certify that all items on this form have been checked and corrected for proper operation as required.			
	(PLEASE	PRINT)	
Date Dealer Name		Dealer Code Vehicle Identification Number (Sticker)	

# SHORT PIN INSTALLATION


To minimize battery discharge the Short Pin has been removed and is stored in the engine compartment Relay Block. Install the Short Pin and confirm all related DTCs are cleared.

#### DTC Clearing Procedure

- Connect Techstream to DLC3.
- 2. Cycle the ignition switch to the "IG-ON" position.
- 3. Using Techstream, check any other codes being output.

#### NOTE

If any DTCs besides B1650 and B1794 remain, repair the applicable system according to the Repair Manual.



## TIRE PRESSURE WARNING SYSTEM (TPWS) INITIALIZATION

Refer to the Repair Manual for the initialization procedure (Highlander / Highlander HV).

## NOTE

To adjust the tire pressure correctly when the outside temperature is significantly colder than shop temperature, perform a Health Check using Techstream and select the "Compensation Tire Pressure" checkbox. Compensation pressures will be displayed on the Health Check results screen. Adjust the tire pressure when the tires are cold.

## COMPASS CALIBRATION

Refer to the Repair Manual for the Calibration procedure (Highlander / Highlander HV) for vehicles equipped with a compass in the rear view mirror.

## NOTE

- Do NOT perform calibration of the compass in a place where the Earth's magnetic field is subject to interference by artificial magnetic fields (underground parking, under a steel tower, between buildings, roof parking, near a railroad crossing, etc.)
- During calibration, do NOT operate electric systems (moon roof, power windows, etc.) as they may interfere with the calibration.

# INITIALIZATION OF PARKING ASSIST MONITOR SYSTEM

Refer to the Repair Manual for the parking assist monitor system initialization procedure (Highlander / Highlander HV).

# FRONT LICENSE PLATE AND MOUNTING BRACKET INSTALLATION\*

The front license plate mounting bracket and 2 self-tapping screws are loaded in the luggage compartment.

- 1. Align the holes on the front license plate and bracket with the dimples on the front of the bumper.
- 2. Install 1 self-tapping screw through the round hole on the front license plate bracket, license plate, and the bumper.
- Install 1 self-tapping screw through the slotted hole on the front license plate bracket, license plate, and the bumper.

## NOTICE

- Do NOT pre-drill holes into the bumper.
- Do NOT overtighten the self-tapping screws.

