

# 2015 PRE-DELIVERY SERVICE CHECK SHEET November 2014

			OTTO TO THE MOVE	111061 2014		
BEFORE INSPECT	TION	OK Adjust/	UNDER VEHICL	LE (ON HOIST)	OK Adjust/ Repair	
	see page 2)			brake anti-rust covers/anti-corrosion		
	naed Parking Guidance System*		02 Inspect tires for	or defects/damage		
FUNCTIONAL OPE			03 Activate and Ir	nitialize Tire Pressure Warning System		
	cycle ignition "IG-ON"; place gear selector in rev	/erse: turi	<b>-</b>	page 2)overs/caps/spare tire wheel covers*		
	er. Unlock doors; release fuel door.	, o, oo, tan	05 Inspect for fue	l, oil, coolant, and other fluid leaks		
	rtesy, map, and sun visor lights*		J     07 \ 1'   1   1   1	the vehicle for damage, rust, etc bolts and nuts on chassis and powertrain		
	dicator lights, gauges, and horn		for looseness.			
	, instrument lights, turn signals,		08 Install rubber t	body plugs*		
emergency flashe	ers, and brake lights		J	transaxle fluid		
	side rear view mirror operation/		ROAD TEST			
06 Check cigarette lighter* and power outlets			A complete road test helps assure customer satisfaction. Drive vehicle over a variety of road surfaces and driving conditions. Check for unusual noise and			
07 Check audio/navigation*/backup camera systems and			driving performance.  Finter Odometer Reading			
08 Verify Entune/Navigation software version (Display						
Audio, Non-HDD Type only)*			Reading Before Test: Reading After Test:			
	mation display and trip information on			gine operationoperation during warm-up		
	verride button cover*		0= 0o ogo	at normal operating temperature		
11 Check sliding roo	f*		04 Check hybrid t	transmission operation		
WALKAROUND IN	ISPECTION			and parking brake operationg operation and off-center/vehicle		
	eck window and door lock operation (from mas		r pull/flutter			
	ntinue around vehicle in a counterclockwise window operation, child door locks, seat belt		_   Or inspect for abi	normal noise and vibrationueaks and rattles		
condition, all lights, lugga aim and continue into UN	ge compartment contents. Finish by checking DER HOOD checks	headligh		nd rear* heater and A/C operation		
			10 Check cruise of	control operation*		
	y system peration		I	eat heater/ventilation operation*		
, ,				TION AND CLEANING		
04 Check that child safety door locks are in normal (unlocked) position*				or protective covers, unnecessary labels,		
05 Check seats and seat belt operation			02 Visually inspec	move just before delivery to customer) ct all interior parts for installation,		
06 Check rear defogger/rear view mirror defogger*			damage, fit, di	rt, etc		
07 Check side marker, tail, backup, and license plate lights. 08 Check luggage compartment light* and trim appearance			,	nat application and install using s*		
09 Adjust spare tire pressure, inspect for damage, and			04 Verify green lie	ght is illuminated on SOS		
check jack and tool installation				ect) button*pard™ and clear protective bumper film*		
10 Check headlight aim  11 Check battery state-of-charge using Digital Battery				an vehicle		
	r (SOC Reading:%)		07 Inspect paint f	inish for scratches, chips, rust, dents,		
UNDER HOOD				or body parts for proper installation,		
01 Check engine oil	level		damage, rust,	etc		
	level		, i i i i	ge sticker on inside of windshield, top		
03 Check engine coolant level			, , , , , , , , , , , , , , , , , , ,	ense plate and mounting bracket*		
05 Check windshield	washer fluid level		(see page 2)	· Ouida and first aid bit a suffaliat		
06 Inspect for fuel, of	il, coolant, and other fluid leaks			Guide and first aid kit portfolio*		
BATTERY MAINTENANCE			12 Perform Techs	stream Health Check		
01 Perform HV battery check and maintenance			* Inspect or instal	* Inspect or install when equipped/required.		
Completion and retention of this form is required to comply with Toyota's Warranty Policy.						
We hereby certify that all items on this form have been checked						
TECHNICIAN'S SIGNATURE SERVICE MANAGER'S SIGNATURE  and corrected for proper						
NAME (PLEASE PRINT) Operation as required.  NAME (PLEASE PRINT)						
Date	Dealer Name	,, LLAGE	Dealer Code	Vehicle Identification Number (Sticker)		
Date	Dealer Name		Dealer Code	vernole luchtinoation rivilibei (Stickei)		

## SHORT PIN INSTALLATION


To minimize battery discharge the Short Pin has been removed and is stored in the engine compartment Relay Block. Install the Short Pin and confirm all related DTCs are cleared.

## **DTC Clearing Procedure**

- 1. Connect Techstream to DLC3.
- 2. Cycle the ignition switch to the "IG-ON" position.
- 3. Using Techstream, check any other codes being output.
- 4. Erase DTCs (B1650, B1794, U0142, and U0155) and Freeze Frame Data.

## NOTE

If any DTCs besides B1650, B1794, U0142, and U0155 remain, repair the applicable system according to the Repair Manual.



## TIRE PRESSURE WARNING SYSTEM (TPWS) ACTIVATION AND INITIALIZATION

### **Activation Procedure**

- 1. Connect Techstream to DLC3.
- 2. Cycle the IG switch to the "IG-ON" position and check that the Low Tire Pressure Warning Light blinks for 1 minute and then remains illuminated.
- 3. Press or remove the valve core to reduce the tire inflation pressure rapidly by 6 psi (0.4 kgf/cm², 40 kPA), or more, within 30 seconds.
- 4. Using Techstream, check for DTCs (C2111-C2114). If no DTCs are stored, continue to step 5. If these DTCs are stored, repeat step 3.
- 5. Adjust all tires to the standard tire inflation pressure, as indicated on the Tire and Loading information label inside the driver's door jamb.
- 6. Check the tire pressure values of all the tires using Techstream. TPWS ECU / Datalist / TIREPRESS 1-4

#### NOTE

If DTCs C2111-C2114 are present after repeating step 3, lift the vehicle and rotate each tire so that the tire pressure warning valve/sensor is at the top of the wheel well. Then repeat step 3.

#### Initialization Procedure

Refer to the Repair Manual for the Initialization procedure.

#### NOTE

To adjust the tire pressure correctly when the outside temperature is significantly colder than shop temperature, perform a Health Check using Techstream and select the "Compensation Tire Pressure" checkbox. Compensation pressures will be displayed on the Health Check results screen. Adjust the tire pressure when the tires are cold.

# FRONT LICENSE PLATE AND MOUNTING BRACKET INSTALLATION

1. Align holes "A" of the mounting bracket with the dimples on the front bumper cover. Mark the location of holes "B" in the front bumper cover.

#### NOTE


- Holes "A" are used for installation of the mounting bracket to the bumper cover.
- Holes "B" are used for installation of the front license plate to the mounting bracket.
- 2. Drill 2 relief holes with a diameter of 11 mm (0.43 in.) at the hole "B" marks on the front bumper cover to prevent the license plate retaining bolt from contacting the cover.
- 3. Install the mounting bracket to the front bumper cover by attaching the 2 self-tapping screws into the dimples.
- 4. Install the front license plate to the mounting bracket using bolts with the following dimensions.

Length: 20.0-25.0 mm (0.79-0.98 in.)

Diameter: 6.0 mm (0.24 in.) Pitch: 1.0 mm (0.04 in.)

## **NOTICE**

- Do NOT pre-drill holes into the bumper.
- Do NOT overtighten the self-tapping screws.



- 1 Bolts
- 2 License Plate
- 3 Self-tapping Screws
- 4 Mounting Bracket
- 5 Mark and Drill Holes
- 6 Dimples