
# **TOYOTA RAV4** 2015 PRE-DELIVERY SERVICE CHECK SHEET

|  |  |                         |    |   | - F  | August 2014 |                         |  |
|--|--|-------------------------|----|---|--|-------------|-------------------------|--|
| <b>BEFORE INSPI</b>  | ECTION   | OK<br>Adjust/<br>Repair |    | UNDER VEH   | ICLE (ON HOIST)  |             | OK<br>Adjust/<br>Repair |  |
|  | use <b>(see page 2)</b>  |                         |    | 01 Remove disc brake anti-rust covers/anti-corrosion<br>wheel film*           02 Inspect tires for defects/damage and adjust air pressure   |  |             |                         |  |
| FUNCTIONAL OPERATION   |  |                         |    | (including spare tire)  |  |             |                         |  |
| Apply parking brake and cycle ignition "IG-ON"; place gear selector in reverse;<br>turn on lights and rear defogger. Unlock doors; release fuel door.  |  |                         |    | page 2)       Image 2)         04 Install wheel covers/caps/spare tire wheel covers*  |  |             |                         |  |
| 02 Check warning/in<br>03 Check windshield<br>04 Check headlights<br>emergency flashe  | <ul> <li>Check dome, courtesy, map, and sun visor lights</li></ul> |                         |    | <ul> <li>05 Inspect for fuel, oil, coolant, and other fluid leaks</li> <li>06 Inspect under the vehicle for damage, rust, etc</li> <li>07 Visually check bolts and nuts on chassis and powertrain for looseness</li> <li>08 Install rubber body plugs* (stored in glove box or center console)</li> </ul>   |  |             |                         |  |
| 05 Check inside/outside rear view mirror operation/<br>adjustment*   |  |                         |    | ROAD TEST   |  |             |                         |  |
| <ul> <li>06 Check cigarette lighter* and power outlets</li> <li>07 Check audio/navigation*/backup camera* systems and set clock</li> <li>08 Check sliding roof*</li> <li>09 Check Rear Seat Entertainment System operation*</li> </ul>   |  |                         |    | A complete road test helps assure customer satisfaction. Drive vehicle over a variety of road surfaces and driving conditions. Check for unusual noise and driving performance.   |  |             |                         |  |
|  |  |                         |    | Enter Odometer Readings Reading Before Test: Reading After Test:  |  |             |                         |  |
| 10 Install shift-lock o  | verride button cover   |                         |    | -   | gine operation   |             |                         |  |
| WALKAROUND INSPECTION  |  |                         |    | 02 Check engine operation during warm-up  |  |             |                         |  |
| Start at left front door. Check window and door lock operation (from master<br>switch, if equipped). Continue around vehicle in a counterclockwise dii<br>checking each door and window operation, child door locks, seat belts, i<br>condition, all lights, luggage compartment contents. Finish by checking he<br>aim and continue into UNDER HOOD checks.<br>01 Check Smart Key System* |  |                         |    | 04 Check automa<br>05 Check brake a<br>06 Check steering<br>07 Inspect for abr<br>08 Inspect for squ<br>09 Check front an   | e at normal operating temperature<br>atic transmission operation<br>and parking brake operation<br>og operation & off-center/vehicle pull/flutter.<br>mormal noise and vibration<br>ueaks and rattles<br>nd rear* heater and A/C operation<br>control operation* |             |                         |  |
| wireless remote control/theft deterrent system*<br>03 Check window operation   |  |                         |    |   | at heater/ventilation operation*   |             | σō                      |  |
| 04 Check that engine starts with all keys<br>05 Check that child safety door locks are in normal   |  |                         |    | FINAL INSPECTION AND CLEANING   |  |             |                         |  |
| <ul> <li>(unlocked) position</li> <li>06 Check seats and seat belt operation</li> <li>07 Check rear defogger/rear view mirror defogger*</li> <li>08 Check side marker, tail, backup, and license plate lights</li> <li>09 Check luggage compartment light* and trim appearance</li> <li>10 Check jack and tool installation</li> <li>11 Check headlight aim</li> </ul>                     |  |                         |    | 01 Remove interior protective covers, unnecessary labels, tags, etc. (Remove just before delivery to customer)       □         02 Visually inspect all interior parts for installation, damage, fit, dirt, etc.       □         03 Verify floor mat application and install using retaining clips*       □         04 Remove Rapgard™ and clear protective bumper film*       □         05 Wash and clean vehicle |  |             |                         |  |
| UNDER HOOD   |  |                         |    | 06 Inspect paint finish for scratches, chips, rust, dents, damage, etc.   |  |             |                         |  |
|  |  |                         |    | 07 Inspect exterior body parts for proper installation,   |  |             |                         |  |
| <ul> <li>01 Check engine oil level</li> <li>02 Check brake fluid level</li></ul>   |  |                         |    | <ul> <li>damage, rust, etc</li></ul>  |  |             |                         |  |
| * Inspect or install when equipped/required.   |  |                         | ┥┟ | COMMENTS:   |  |             |                         |  |
| Completion and retention of this form is required to comply with Toyota's Warranty Policy.   |  |                         |    |   |  |             |                         |  |
| TECHNICIAN'S SIGNATURE       SERVICE MANAGER'S SIGNATURE       We hereby certify that all items on this form have been checked and corrected for proper operation as required.   |  |                         |    |   |  |             | ecked<br>er             |  |
| NAME (PLEASE PRINT) NAME (PLEASE PR  |  |                         |    | RINT) operation as required.  |  |             |                         |  |
| Date   | Dealer Name  | Dealer                  |    | aler Code   | Vehicle Identification Number (Sticker)  |             |                         |  |

# D/C CUT FUSE INSTALLATION

To minimize battery discharge the D/C Cut Fuse has been removed and is stored in the engine compartment Relay Block. Install the D/C Cut Fuse and confirm all related DTCs are cleared.



1 D/C Cut Fuse Storage Location 2 Ins

2 Install D/C Cut Fuse Here

## TIRE PRESSURE WARNING SYSTEM (TPWS) INITIALIZATION

Refer to the Repair Manual for the Initialization Procedure.

#### NOTE

- Please note the spare tire does NOT have a TPWS sensor.
- To adjust the tire pressure correctly when the outside temperature is significantly colder than shop temperature, perform a Health Check using Techstream and select the "Compensation Tire Pressure" checkbox. Compensation pressures will be displayed on the Health Check results screen. Adjust the tire pressure when the tires are cold.

## FRONT LICENSE PLATE & MOUNTING BRACKET INSTALLATION\*

1. Align holes "A" of the mounting bracket with the dimples on the front bumper cover. Mark the location of holes "B" on the front bumper cover.

## NOTE

- Holes "A" are used for installation of the mounting bracket to the bumper cover.
- Holes "B" are used for the installation of the front license plate to the mounting bracket.
- Drill 2 relief holes with a diameter of 11 mm (0.43 in.) at the hole "B" marks on the front bumper cover to prevent the license plate retaining bolt end from contacting cover.

## NOTICE

Do NOT drill at the dimples on the front bumper cover.

- 3. Install the mounting bracket to the front bumper cover by attaching the 2 self-tapping screws into the dimples.
- 4. Install the front license plate to the mounting bracket using bolts with the following measurements:

Length: 15.0 - 23.0 mm (0.59 - 0.91 in.) Diameter: 6.0 mm (0.24 in.) Pitch: 1.0 mm (0.04 in.)

