



Countries:	CANADA, UNITED STATES, PUERTO RICO	Document ID:	IK1200531
Availability:	ISIS, Fleet!ISIS	Revision:	3
Major System:	ENGINES	Created:	9/9/2010
Current Language:	English	Last Modified:	3/6/2014
Other Languages:	Français , Español ,	Author:	Octavio Ortiz
Viewed:	4416		

[Less Info](#)

Hide Details

Coding Information

Copy Link	Copy Relative Link	Bookmark	Add to Favorites	Print	Provide Feedback	Helpful	Not Helpful
		 View My Bookmarks				 1049	 522

Title: 2010 MaxxForce DT, 9 and 10 Idle Quality**Applies To: MaxxForce DT, 9 and 10**

DESCRIPTION

2010 EPA MaxxForce medium duty inline engines may have a rough idle until the engine oil temperature reaches 70 degrees Celsius (158 Fahrenheit). This is due to an open loop mode of operation and is normal. Once the oil temperature reaches 70 degrees Celsius engine management software takes over and the engine will idle smoother.

SYMPTOM

Rough idle at engine oil temperature below 70 degrees Celsius (158 Fahrenheit).

RESOLUTION

Update to latest ECM calibration.

ECM calibrations ending in XBR1 or above include changes aimed at idle quality. While perception is subjective, idle data and technician feedback shows that idle quality is indeed satisfactory with this upgrade. The upgrade is available through NETS as usual.

Hide Details

Feedback Information

Viewed:	4415
Helpful:	1049
Not Helpful:	522
No Feedback Found	