

CC - 2015 FLUID CAPACITY CHART

บา	4	n	Λ1	1

Code)	qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
CC 2	2.0 TFSI 200 hp	6-Spd	N/A	N/A	8.0L (8.5 qt)***	Electro-	1.2 L (1.3qt)	Refrigerant	3.0L (3.1qt)
FWD	(CCTA / CBFA)	(02Q)				Mechanical	(approximately)	Use only R134a	
Manual									Fluid PN
	4.7 L (4.9 q.t)	2.3L (2.4 qt)						Refrig. Capacity	G 052 164*
(3581F2)							VW Brake Fluid	550 ± 5 grams	
(3581Y2)	VW Oil Spec:	<u>Oil PN</u>					Specification:	$(19.4 \pm 0.2 \text{ oz.})$	
(358AF2)	VW 502 00**	G 052 171 A2*							
, ,	Use synthetic oil						Use new fluid only.		
CC	SAE 5W-40,	NA	6-Spd DSG	Capacity			VW 501 14 or	Refrigerant Oil	
FWD	SAE 5W-30		(02E)	included with			FMVSS 116 DOT 4	Use a PAG oil	
Auto			New Fill: 6.9 – 7.2L	transmission.				with R134a	
(3581FD)			(7.3 – 7.6 qt)				Fluid PN	Oil PN & Capacity	
(3581YD)			Change:				B 000 750 *	1) For Sanden use	
(358AFD)			5.2L (5.5 qt)					G 052 154 A2*	
(358AYD)			<u>Mechatronic</u>					110 cc ± 10 cc	
(3586FD)			<u>Only</u>					$(3.7 \pm 0.3 \text{ fl. oz.})$	
(3586YD)			3.0 – 4.0 L						
			(3.1-4.2qt.)					2) For Zexel use	
								G 052 200 A2*	
			<u>Oil PN</u>					120 cc ± 15 cc	
			G 052 182 A2*					$(4.0 \pm 0.5 \text{ fl. oz.})$	
CC - AWD	3.6L VR6 280 hp		6-Spd	(0BS)	9.0L (9.5 qt)***			0) = 5	
4XMOTION	(CNNA)		(09M)	0.95L (1.0 qt)				3) For Denso use	
Auto								G 052 300 A2*	
(5.5 L (5.8 qt.)		New Fill:	Oil PN				140 cc ± 10 cc	
(3584UQ)			7.0L (7.4 qt)	G 052 145 S2*				$(4.7 \pm 0.3 \text{ fl. oz.})$	
	VW Oil Spec:		Oil PN					4) For Delphi use	
	VW 502 00**		G 055 025 A2*	Haldex Clutch				' '	
	Use synthetic oil		Bevel Box	New Fill:				G 052 154 A2* or G 052 300 A2*	
	SAE 5W-40,			0.85L (0.9 qt)				110 cc ± 10 cc	
	SAE 5W-30		New Fill:	Changa				(3.7 ± 0.3 fl. oz.)	
			0.9L (1.0 qt)	Change: 0.7L(0.7qt 22oz)				(3.7 ± 0.3 11. 02.)	
			Oil PN	0.7L(0.741 2202)					
			G 052 145 S2*	Oil PN					
			0 002 170 02	G 060 175 A2*					

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

© 2014 Volkswagen Group of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Volkswagen Group of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Refer to Technical Bulletin 2012855 for engine oils that meet this VW oil specification.

^{***} VW Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J). Dilute with Distilled Water.