

Service

Category Brake

Section Brake Control/Dynamic Control System

Market USA



Applicability

YEAR(S)	MODEL(S)	ADDITIONAL INFORMATION	
2013 – 2014	Camry		

Introduction

Some 2013 – 2014 model year Camry vehicles equipped with the 2AR-FE engine may exhibit an intermittent service brake warning light "ON" condition. Customers may also notice the light will illuminate as the vehicle is being started, and some customers may notice a noise or feeling similar to the ABS activating during normal braking. The brake booster has been updated to address this condition.

Warranty Information

OP CODE	DESCRIPTION	TIME	OFP	T1	T2
BR1402			44610-06471	8C	50

APPLICABLE WARRANTY

- This repair is covered under the Toyota Basic Warranty. This warranty is in effect for 36 months or 36,000 miles, whichever occurs first, from the vehicle's in-service date.
- Warranty application is limited to occurrence of the specified condition described in this bulletin.

Parts Information

PART NUMBER		DADT MARKE	QTY
PREVIOUS	NEW	PART NAME	QII
44610-06471	44610-06470	Booster Assy, Brake	1




Repair Procedure

 Check to see if the BRAKE warning light is currently illuminated with the parking brake OFF and engine ON.

Is the brake light illuminated?

- YES Continue to step 2.
- NO Go to step 5.



Inspect the brake fluid reservoir level.

Refer to the Technical Information System (TIS), applicable model and model year Repair Manual:

- 2013 Camry: Brake – Brake System – "Brake System (Other): Brake Fluid: On-vehicle Inspection"
- 2014 Camry: Brake – Brake System – "Brake System (Other): Brake Fluid: On-vehicle Inspection"

Is the brake fluid level above the minimum level WITHOUT the customer adding additional brake fluid?

- YES Continue to step 3.
- NO If the customer states they have had to add fluid for the light to go OFF, or if the
 brake fluid level is lower than the MIN line, check for leaks and inspect the disc brake pads
 and repair as needed.



Repair Procedure (Continued)

- 3. If the brake light is currently illuminated, check the ABS Data List via Techstream to see if the ABS actuator is commanding the brake light ON.
 - If the brake warning light is on and is being commanded on by ABS ECU-go to step 4.
 - If the brake warning light is illuminated and is not being commanded on by ABS actuator-this bulletin does NOT apply. Continue diagnosis using the applicable Repair Manual.

Figure 2.

ABS/VSC/TRAC					
Parameter	Value	Unit			
ABS Warning Light	OFF				
Brake Warning Light	ON 🧹	-205			
Stop Light SW	OFF				
Parking Brake SW	OFF				
Main Idle SW	ON				
Brake Pedal Load Sensing SW	OFF				
Gear Position	P,N				
Shift Lever Position	P,N				

4. Press and hold the brake pedal down firmly for 3 or more seconds while the engine is idling. Repeat this step three to five times while keeping the engine running.

Is the brake light still illuminated?

- YES If the light stays illuminated, this bulletin does NOT apply. Continue diagnosis using the applicable Repair Manual.
- NO If the brake warning light is no longer illuminated, replace the Vacuum Brake Booster Assembly with the updated part and proceed to step 8.

Refer to TIS, applicable model and model year Repair Manual:

- 2013 Camry: Brake – Brake System – "Brake System (Other): Brake Booster: Removal / Installation"
- 2014 Camry: Brake – Brake System – "Brake System (Other): Brake Booster: <u>Removal / Installation"</u>
- If the BRAKE light is NOT currently illuminated, check the ABS ECU for DTCs that would cause the BRAKE warning light to illuminate.

Are there any related DTCs showing?

- YES This bulletin does NOT apply. Continue diagnosis using the applicable Repair Manual.
- NO Continue to step 6.

Repair Procedure (Continued)

(transportation)

6. Inspect the brake fluid reservoir level.

Refer to TIS, applicable model and model year Repair Manual:

- 2013 Camry: Brake – Brake System – "Brake System (Other): Brake Fluid: On-vehicle Inspection"
- 2014 Camry: Brake – Brake System – "Brake System (Other): Brake Fluid: On-vehicle Inspection"

Is the brake fluid above the minimum level WITHOUT the customer adding additional brake fluid?

- · YES Continue to step 7.
- NO If the customer states they have had to add fluid for the light to go OFF, or if the
 brake fluid level is lower than the MIN line, check for leaks and inspect the disc brake pads
 and repair as needed.
- Visually inspect the parking brake, ABS Actuator, and master cylinder hydraulic lines and connections for any concerns that are causing the BRAKE warning light to illuminate intermittently.
 - If there is no concerns found-replace the Brake Vacuum Booster Assembly with the updated part.

Refer to TIS, applicable model and model year Repair Manual:

- 2013 Camry: Brake – Brake System – "Brake System (Other): Brake Booster: Removal / Installation"
- 2014 Camry: Brake – Brake System – "Brake System (Other): Brake Booster: Removal / Installation"
- If there is a concern found Diagnosis using the applicable Repair Manual.
- 8. Test drive the vehicle confirming that the brake system is operating normally, and that the BRAKE warning indicator light is not abnormally illuminated.