

Tech Tips

TT 72-12-01

Date: April 27, 2012

2011-2014 Touareg – Replacement Procedure for Driver’s Seat Control Module -J810-

December 12, 2014: Update to model year.

After replacement of the Driver seat control module (J810) the vehicle may not recognize the new module. The adaptation test plan may not set the seat module location properly and it may display as a passenger seat control module.

To set the module through Vehicle Self Diagnosis:

- 1) Connect the new Driver's Seat Adjustment Module (J810) on the driver side.
- 2) Disconnect the Passenger Seat Adjustment Module (J720) or remove the SC20 fuse (see ELSA for correct fuse per model).
- 3) Switch Ignition ON: Using VSD, enter address 06 (passenger side seat module).
- 4) Select adaptation channel 1 and change the value to a '2'.
- 5) Switch ignition OFF.
- 6) Reconnect the Passenger side seat module. Vehicle should now recognize both address 06 and 36.
- 7) Set the adaptation (basic settings) of the seat or seats using the test plan or by running the seat through full range of motion including backrest and lumbar.

Guided Functions	Volkswagen V19.14.01 21/12/2011
Functions	7P - Touareg 2010 > only USA/Canada
Selecting vehicle system or function	2011 (B) Sedan CGFA 3.0 L TFSI Hybrid/245kW
36 - Driver's seat adjustment - J810	
36 - Adaption (Rep.Gr.72)	
36 - Driver seat adjustment component protection	
36 - Read measured values, (Rep.Gr.72)	
36 - Final control diagnosis (Rep.Gr.72)	
36 - Code control module (Rep.Gr. 72)	

Figure 1

Guided Functions	Volkswagen V19.14.01 21/12/2011
Function Test	7P - Touareg 2010 > only USA/Canada
J810 - Basic setting	2011 (B) Sedan CGFA 3.0 L TFSI Hybrid/245kW
Calibration/installation location	
This test is used to calibrate the driver seat adjustment and to adapt the installed location.	
What would you like to do?	
-1- Adapt the installed location (driver/front passenger)	-1-
-2- Calibrate driver seat adjustment	-2-
-3- End program	-3-

Figure 2