

Q5 - 2015 FLUID CAPACITY CHART Final July 31, 2014

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
Q5 SUV quattro (8RB52A)	2.0 TFSI 220 hp (CPMB) 4.6 L (4.9 qt) <u>Audi Oil Spec**</u> VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (OBK/OBL) <u>New Fill:</u> 8.6 L approx. (9.0 qt.) <u>Refill</u> 3.6-4.0 L (3.8-4.2 qt.) <u>Oil PN</u> G 060 162 A2* Transfer Case 1.0 L (1.1 qt.) <u>Oil PN</u> G 055 145 A2*	Front F/Drive New Fill: 1.0L (1.1qt) <u>Oil PN</u> G 052 145 S2* Rear F/Drive (0BD) 1.0L (1.1qt) <u>Oil PN</u> G 052 145 S2*	10.0 L (10.5qt)***	Electromechanical	1.0 L (1.1qt) (approximately) <u>VW Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	<u>Refrigerant</u> Use only R134a 630g ± 15g (22.3 ± 0.5 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil Capacity & PN</u> For Denso 150 cc +/- 10 cc (5.1 ± 0.3 oz.) G 052 300 A2*	4.6 L (4.9 qt.) <u>Fluid PN</u> G 052 164*
Q5 Hybrid SUV quattro (8RB5GA)	2.0 TFSI 211 hp (CHJA) 4.6 L (4.9 qt) <u>Audi Oil Spec**</u> VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (OBW) <u>New Fill:</u> 8.6 L approx. (9.0 qt.) <u>Refill</u> 4.0 L (4.2 qt.) <u>Oil PN</u> G 060 162 A2* Transfer Case 1.0 L (1.1 qt.) <u>Oil PN</u> G 052 145 A2*		10.0 L (10.5qt)***			<u>Refrigerant</u> Use only R134a 900g ± 15g (31.7 ± 0.5 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil Capacity & PN</u> For Denso 200cc +/- 20 cc (6.7 ± 0.3 oz.) G 052 300 A2*	

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) G13 (TL-VW774J). **Dilute with Distilled Water.**

Q5 - 2015 FLUID CAPACITY CHART Final July 31, 2014

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
Q5 SUV quattro (8RB57A)	3.0L V6 272 hp (CTUC) 6.8 L (7.2 qt.) <u>Audi Oil Spec**:</u> VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (OBK/OBL) <u>New Fill:</u> 8.6 L approx. (9.0 qt.) <u>Refill</u> 3.6-4.0 L (3.8-4.2 qt.) <u>Oil PN</u> G 060 162 A2* Transfer Case 1.0 L (1.1 qt.) <u>Oil PN</u> G 055 145 A2*	Front F/Drive New Fill: 1.0L (1.1qt) <u>Oil PN</u> G 052 145 S2* Rear F/Drive (0BD) 1.0L (1.1qt) <u>Oil PN</u> G 052 145 S2*	12.0 L (12.7qt)***	Electromechanical	1.0 L (1.1qt) (approximately) <u>VW Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	<u>Refrigerant</u> Use only R134a 630g ± 15g (22.3 ± 0.5 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil Capacity & PN</u> For Denso 150 cc +/- 10 cc (5.1 ± 0.3 oz.) G 052 300 A2*	4.6 L (4.9 qt.) <u>Fluid PN</u> G 052 164*
Q5 SUV quattro (8RB5VA)	3.0L TDI V6 240 hp (CPNB) 6.4 L (6.8 qt.) <u>Audi Oil Spec**:</u> VW 507 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	G 055 145 A2*		12.0 L (12.7qt)***	<u>AdBlue® Tank</u> 23.0L (6.0 gal)**** <u>ISO Standard</u> 22241-1 Only fill with filling device VAS6542 & holding device SET740.	<u>Refrigerant</u> Use only R134a 630g ± 15g (22.2 ± 0.5 oz.) <u>Oil Capacity & PN</u> For Denso 150 cc +/- 10 cc (5.1 ± 0.3 oz.) G 052 300 A2*		

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) G13 (TL-VW774J). Dilute with Distilled Water.

**** Part Numbers for AdBlue® Reducing Agent: 0.5 gal (1.89 L) G 052 910 A2 for warranty repairs, 2.5 gal (10.0L) GUS 052 910 A3 for maintenance services.

SQ5 - 2015 FLUID CAPACITY CHART Final July 31, 2014

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
SQ5 quattro (8RB5CA)	3.0L V6 354 hp (CTUD) 6.8 L (7.2 qt.) <u>Audi Oil Spec**:</u> VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (OBK/OBL) <u>New Fill:</u> 8.6 L approx. (9.0 qt.) <u>Refill</u> 3.6-4.0 L (3.8-4.2 qt.) <u>Oil PN</u> G 060 162 A2* Transfer Case 1.0 L (1.1 qt.) <u>Oil PN</u> G 055 145 A2*	Front F/Drive New Fill: 1.0L (1.1qt) <u>Refill</u> 0.9 L (0.9 qt.) <u>Oil PN</u> G 052 145 S2* Rear F/Drive (0BC) 0.9L (0.9qt) <u>Oil PN</u> G 052 145 S2*	12.0 L (12.7qt)***	Electromechanical	1.0 L (1.1qt) (approximately) <u>VW Brake Fluid</u> <u>Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	<u>Refrigerant</u> Use only R134a 630g ± 15g (22.3 ± 0.5 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil Capacity & PN</u> For Denso 150 cc +/- 10 cc (5.1 ± 0.3 oz.) G 052 300 A2*	4.6 L (4.9 qt) <u>Fluid PN</u> G 052 164*

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

** Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) G13 (TL-VW774J). Dilute with Distilled Water.