Audi Service



2015 MY Scheduled Maintenance Intervals

The first scheduled service is due at 5,000 miles (8,000km) or 1 year after delivery, whichever occurs first. Thereafter, all remaining scheduled services are due every 10,000 miles or 1 year after previous service, whichever occurs first.

Engine DUI/OF Filter - change oil and replace filter Addition for Addition that winder growth fresh fluid (maximum capacity: 24 liters) and adapt and the confidence of the c	10,000 lines of 1 year after previous service, whichever occurs first.			
Engine Oil/Oil Filter - change oil and replace filter Addisor Fillion - fillion ompletely with fresh fillion dismanum capacity. 24 litera) and adapt control with the find fillion shall with regional grafter fillion fillion increased with the find of fault with regional grafter fillion fillion increased with the find of fault with regional grafter fillion fillion increased with the finder of the with the fillion of the fillion of the fillion fillion of the fillion of	Miles (in thousands)	5/25/45/65/85/105/125	15/55/95/135	35/75/115
Addition Flade - fill completely with free filled disconvenience Scale for Addition Flade (See Flade F	Kilometers (in thousands)	8/40/70/100/130/160/190	25/85/145/205	55/115/175
Addition Flade - fill completely with free filled disconvenience Scale for Addition Flade (See Flade F	Faring Oil (Oil Filter about all and applies filter			
International Control Contro	· ·			
Engine Compartment - check for foreiso Oncobord Diagnosis - check Visual Check - check the chassis for possible paint damage and corrosion, from the indiced and outside, with the doors as well as hood and trunk lids open Battery - check for feant terminals (on corrosion), properly mounted housing, and no damages replace if necessary. Small (12-wolf) Side Battery - located in the trunk compartment on left Side - check for clean terminals (on corrosion), properly mounted housing and no damages replace if necessary. Small (12-wolf) Side Battery - located in the trunk compartment on left Side - check for clean terminals on corrosion), properly mounted housing and no damages replace if necessary. Due tand Pollen littler - replace at 35,000 miles (55,000 km) or 6 years, whichever occurs first. Thereafter, every 40,000 miles (05,000 km) or 6 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 6 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 6 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 6 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 6 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 6 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 6 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 6 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 6 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 6 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 6 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 6 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 6 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 9 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 9 years, whichever occurs first. Thereafter, every 90,000 miles (05,000 km) or 9 years, whic	learned values for AdBlue tank under guided fault finding after filling fluid	and A7 3.0L TDI, O7 3.0L TDI and A8	TDI, Q7 3.0L TDI and A8 3.0L TDI only	Q5 3.0L TDI, A6 3.0L TDI and A7 3.0L TDI, Q7 3.0L TDI and A8 3.0L TDI only
Street S				•
Visual Cheek - check the chaste for possible paint damage and corrodor, from the imide and outside, with the doors as well as hood and trust (like pen later) in the check for clean terminals for corrosion), properly mounted housing, and no damage replace of battery of the check for clean terminals for corrosion), properly mounted housing and no damage replace of battery of the clean terminals for corrosion, properly mounted housing and no damages replace of recessary. Small (12-vold) Side Battery , located in the trust compartment on left-side - check for clean terminals for corrosion), properly mounted housing and no damages replace of recessary. Dout and Pollen Fitter - replace Spark Plays - replace at \$5,000 miles (\$5,000 km) or 6 years, whichever occurs first. Therefore, revery 40,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Therefore, revery 30,000 miles (\$6,000 km) or 6 years, whichever occurs first. Ther				
inside and outside, with the doors as well as hood and trunk lids open bastery - check for clean terminals for corrosion, properly mounted housing, and no dramage; replace if necessary. Also, check the and level of battery programs of the property of the property of the programs of the programs of the property of the programs of the	•	Flex Fuel vehicles only	Flex Fuel vehicles only	Flex Fuel vehicles only
and not damage; replace if necessary. Also, check the aid level of battery only if the level can be seen through the housing and full in necessary small (12 volt) Side Battery - located in the trunk compartment on left side - check for clean terminals to corrison's, properly mounted housing and no damage, replace source of the clean terminals to corrison's, properly mounted housing and no damage, replace source of the clean terminals to corrison's, properly mounted housing and no damage, replace source of the clean terminals of the compared of the clean terminals of t	inside and outside, with the doors as well as hood and trunk lids open		•	•
for clean terminals (no corrosino), properly mounted housing and no damage, replace if necessary Dust and Pollen Filter - replace for clean terminals (no corrosino), properly mounted housing and no damage, replace if necessary Dust and Pollen Filter - replace at \$5,000 miles (\$5,000 km) or 6 years, whichever occurs first. Thereafter, every 40,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$0,000 km) or 6 years, whiche	Battery – check for clean terminals (no corrosion), properly mounted housing, and no damage; replace if necessary. Also, check the acid level of battery only if the level can be seen through the housing and fill if necessary		except Q5 hybrid	except Q5 hybrid
Spark Plugs - replace at \$5,000 miles (\$5,000 km) or 6 years, whichever occurs first. Occurs First - replace at \$5,000 miles (\$6,0000 km) or 6 years, whichever occurs first. Thereafter, every 60,000 miles (\$9,0000 km) or 6 years, whichever occurs first. Thereafter, every 60,000 miles (\$9,0000 km) or 6 years, whichever occurs first. Thereafter, every 60,000 miles (\$9,0000 km) or 6 years, whichever occurs first. Thereafter, every 60,000 miles (\$9,0000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,0000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,0000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,0000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (\$9,000 km) or 6 years, whichever occurs first. Thereafter, every 30,0	Small (12-volt) Side Battery – located in the trunk compartment on left side – check for clean terminals (no corrosion), properly mounted housing and no damage; replace if necessary		Q5 hybrid only	Q5 hybrid only
Thereaffer, every 40,000 miles (90,000 km) or 6 years, whichever occurs first. Thereaffer, every 60,000 miles (90,000 km) or 6 years, whichever occurs first. Thereaffer, every 60,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 60,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs first. Thereaffer, every 30,000 miles (95,000 km) or 6 years, whichever occurs	Dust and Pollen Filter – replace		•	•
Interfact (e., very 90,000 miles (55,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (45,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (45,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (45,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (45,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (45,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (45,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (45,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (45,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (45,000 km) or 6 years, whichever occurs first. Thereafter, every 30,000 miles (45,000 km) or 6 years, whichever occurs first. All Cleaner - clean housing, replace filter element - clean housing, replace filter element - clean for constant propagation of the first filter element - clean for constant propagation of the first filter element - clean for constant propagation of the first filter element - clean filter occurs first filter element - clean filter occurs first filter element - clean filter element elect and for constant filter element - clean filter element elect and for constant filter element - clean filter element elect and for constant filter element - clean filter element elect and for constant filter element - clean filter element - clea				A8 W12, all vehicles with 2.0L TFSI
Thereafter, every 3,0,000 miles (45,000 km) or 6 years, whichever occurs first Power Steering Fluid – check, add if necessary Air Cleaner – clean housing, replace filter element —clean housing, replace filter element —clean housing, replace if necessary Ribbed V Belt and Tensioner – check condition and replace if necessary Ribbed V Belt – check condition, replace if necessary —replace only the belt for the compressor drive (front belt) Snow Screen for Air Cleaner – clean Fuel Filter – replace Dises Particulate Filter (DPP) – perform after the first 115K miles (USA)/175,000 km Clanadio in 110K miles (USA)/125,000 km (Canadio) after a Disesel Particulate filter (DPP) Perplacement, check ash loading according to manufacturer's work procedure, replace* Plenum Panel – remove cover for plenum panel to check water drain and clean if necessary Plenum Panel – remove cover for plenum panel to check water drain and clean if necessary Tires and Spare Wheel – check for wear and damage, check tire pressure, reset Tire Pressure Monitoring System (TPMS) Tires – rotate, reset TPMS Wiper Blades – check condition and replace if necessary (USA only) Wiper Blades – check confiction and replace if necessary (USA only) Wiper Blades – check confiction of pracking lights, low beams, high beams, fog lights, black-up lights, glove box illumination, control lights and MMI (if applicable) Tires – rotate, reset TPMS Wiper Blades – check confiction of praking lights, low beams, high beams, fog lights, black-up lights, reset for pressure for foreke lights, blinkers and hazard lights Service Reminder Display – reset Mon-toning System (TPMS) Door Hinges and Straps – lubricate Dor Hinges and Straps – lubricate ***Option** ***	Thereafter, every 60,000 miles (90,000 km) or 6 years, whichever		 55K only: vehicles with the 1.8L (A3), 3.0L V6 TFSI, 4.2L V8 FSI and 5.2L V10 FSI engines 	
Air Cleaner – clean housing, replace filter element — clean for element — clean housing, replace filter element — clean filter element — cle	Thereafter, every 30,000 miles (45,000 km) or 6 years, whichever			 35K only: 2.0L TFSI Flex Fuel engines only
- clean housing, replace filter element Ribbed V Belt and Tensioner - check condition and replace if necessary Ribbed V Belt - check condition, replace if necessary. Check tension of belt drive with manual tensioner and retension if necessary - replace only the belt for the compressor drive (front belt) Snow Screen for Air Cleaner - clean Snow Screen for Air Cleaner - clean Fuel Filter - replace Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) or 110K miles (USA)/165,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) after a Diesel Particulate Filter (DPF) - perform after the fir	Power Steering Fluid - check, add if necessary			A8, Q7 only
Ribbed V Belt and Tensioner – check condition and replace if necessary Ribbed V Belt – check condition, replace if necessary. Check tension of belt drive with manual tensioner and retension if necessary - replace only the belt for the compressor drive (front belt) Snow Screen for Air Cleaner – clean Snow Screen for Air Cleaner – clean Puel Filter – replace Diesel Particulate Filter (DPF) – perform after the first 115K miles (USA)/175,000 km (Canada) or 110K miles (USA)/155,000 km (Canada) after a Diesel Particulate Filter (DPF) Plenum Panel – remove cover for plenum panel to check water drain and clean if necessary Tires and Spare Wheel – check for wear and damage, check tire pressure, reset Tire Pressure Monitoring System (TPMS) Tires – rotate, reset TPMS Wiper Blades – check condition (Canada only) Wiper Blades – check condition (Canada only) Wiper Blades – check condition of parking lights, low beams, high beams, fog lights, blinkers and hazard lights Service Reminder Display – reset Hom. — check function of parking lights, low beams, high beams, fog lights, black-up lights, rear fog lights, license plate lights, blinkers and hazard lights Service Reminder Display – reset Hom. — check function of brake lights, blinkers and hazard lights Service Reminder Display – reset Hom. — check function of brake lights, blinkers and hazard lights Service Reminder Display – reset Hom. — check function of brake lights, blinkers and hazard lights.	Air Cleaner – clean housing, replace filter element		 55K only: except RS 5, S6, S7, RS 7, A8 3.0L V6 TFSI, A8 3.0L V6 TDI, 	RS 5, S6, S7, A8 3.0L V6 TDI, A8 3.0L V6 TFSI, A8 4.0L V8 TFSI, TTS and
Ribbed V Bett and tensioner – check condition, replace in necessary — replace only the belt for the compressor drive (front belt) Snow Screen for Air Cleaner – clean Ay 54, 34, 34, 34, 34, 34, 34, 34, 34, 34, 3				RS 7 only
with manual tensioner and retension if necessary - replace only the belt for the compressor drive (front belt) Snow Screen for Air Cleaner - clean Ad. 344, standard, 54, A5 Cabrinder, 05, 050 winds Special Filter - replace Truel Filter - replace Diesel Particulate Filter (DPF) - perform after the first 115K miles (USA)/175,000 km (Canada) or 110K miles (USA)/165,000 km (Canada) after a Diesel Particulate Filter (DPF) replacement, beck ash loading according to manufacturer's work procedure, replace** If necessary Plenum Panel - remove cover for plenum panel to check water drain and clean if necessary Tires and Spare Wheel - check for wear and damage, check tire pressure, reset Tire Pressure Monitoring System (TPMS) - check for wear and damage, check tire pressure and renewal date of tire repairs set (where applicable), reset Tire Pressure Monitoring System (TPMS) Wiper Blades - check condition (Canada only) Wiper Blades - check function of parking lights, low beams, high beams, fog lights, blinkers and hazard lights Rear Lighting - check function of parking lights, low beams, high beams, fog lights, black-up lights, rear fog lights, license plate lights, blinkers and hazard lights Rear Lighting - check function of brake lights (including third brake light), taillights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights Service Reminder Display - reset Horn - check function Dor Hinges and Straps - lubricate	Ribbed V Belt and Tensioner – check condition and replace if necessary		R8 Coupe, R8 Spyder only	R8 Coupe, R8 Spyder only
- replace only the belt for the compressor drive (front belt) 5. Sow Screen for Air Cleaner – clean 6. M. 54, almad, A5, A5 Cabridet, O5 Sprind and Control of Sprind and Control and Control of Sprind and Control of Spr	Ribbed V Belt – check condition, replace if necessary. Check tension of belt drive			75K only
Fuel Filter – replace Diesel Particulate Filter (DPF) – perform after the first 115K miles (USA)/175,000 km (Canada) or 110K miles (USA)/165,000 km (Canada) after a Diesel Particulate Filter (DPF) replacement, check ash loading according to manufacturer's work procedure, replace** (Fig. 4) 2.0. Tiol. Ask 3.0. Tiol. Ask	•		 55K only: all vehicles with the 3.0L V6 TFSI 	 115K only: all vehicles with the 3.0L V6 TFSI
Diesel Particulate Filter (DPF) – perform after the first 115K miles (USA)/175,000 km (Canada) or 110K miles (USA)/165,000 km (Canada) after a Diesel Particulate Filter (DPF) replacement; check ash loading according to manufacturer's work procedure, replace** (fine accessary) Plenum Panel – remove cover for plenum panel to check water drain and clean if necessary Plenum Panel – check for wear and damage, check tire pressure, reset Tire Pressure Monitoring System (TPMS) — check for wear and damage, check tire pressure and renewal date of tire repair set (where applicable), reset Tire Pressure Monitoring System (TPMS) Wiper Blades – check condition and replace if necessary (USA only) Wiper Blades – check condition (Canada only) Wiper Washer/Headlight Washer – check adjustment and function, add fluid if necessary Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable) Front Lighting – check function of parking lights, low beams, high beams, fog lights, blinkers and hazard lights Rear Lighting – check function of brake lights, liching third brake light), taillights, back-up lights, grear fog lights, license plate lights, blinkers and hazard lights Service Reminder Display – reset Horn – check function Door Hinges and Straps – lubricate	Snow Screen for Air Cleaner – clean		S5, S5 Cabriolet, Q5, SQ5 and Q5 hybrid only	S5, S5 Cabriolet, Q5, SQ5 and Q5 hybrid only
Tires and Spare Wheel – check for wear and damage, check tire pressure, reset Tire Pressure Monitoring System (TPMS) - check for wear and damage, check tire pressure and renewal date of tire repair set (where applicable), reset Tire Pressure Monitoring System (TPMS) Tires – rotate, reset TPMS Wiper Blades – check condition and replace if necessary (USA only) Wiper Blades – check condition (Canada only) Wiper Blades – check condition (Canada only) Wiper Washer/Headlight Washer – check adjustment and function, add fluid if necessary Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable) Front Lighting – check function of brake lights, license plate lights, blinkers and hazard lights Service Reminder Display – reset Horn – check function Door Hinges and Straps – lubricate	Fuel Filter – replace		 A3 2.0L TDI, A6 3.0L TDI, A7 3.0L TDI, A8 3.0L TDI, Q5 3.0L TDI and Q7 3.0L TDI only 	A6 3.0L TDI, A7 3.0L TDI, A8 3.0L TDI, Q5 3.0L TDI and Q7 3.0L TDI only
Clean if necessary Tires and Spare Wheel – check for wear and damage, check tire pressure, reset Tire Pressure Monitoring System (TPMS) — check for wear and damage, check tire pressure and renewal date of tire repair set (where applicable), reset Tire Pressure Monitoring System (TPMS) Tires – rotate, reset TPMS Wiper Blades – check condition and replace if necessary (USA only) Wiper Blades – check condition (Canada only) Wiper Washer/Headlight Washer – check adjustment and function, add fluid if necessary Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable) Front Lighting – check function of parking lights, low beams, high beams, fog lights, blinkers and hazard lights Rear Lighting – check function of brake lights (including third brake light), taillights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights Service Reminder Display – reset Horn – check function Door Hinges and Straps – lubricate	Diesel Particulate Filter (DPF) – perform after the first 115K miles (USA)/175,000 km (Canada) or 110K miles (USA)/165,000 km (Canada) after a Diesel Particulate Filter (DPF) replacement; check ash loading according to manufacturer's work procedure, replace** if necessary	 Canada: 175 km only: A3 2.0L TDI, A6 3.0L TDI, A7 3.0L TDI, A8 3.0L TDI, Q5 3.0L TDI and 		
Pressure Monitoring System (TPMS) - check for wear and damage, check tire pressure and renewal date of tire repair set (where applicable), reset Tire Pressure Monitoring System (TPMS) Tires – rotate, reset TPMS Wiper Blades – check condition and replace if necessary (USA only) Wiper Blades – check condition (Canada only) Wiper Blades – check condition (Canada only) Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable) Front Lighting – check function of parking lights, low beams, high beams, fog lights, blinkers and hazard lights Rear Lighting – check function of brake lights (including third brake light), taillights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights Service Reminder Display – reset Horn – check function Door Hinges and Straps – lubricate	Plenum Panel – remove cover for plenum panel to check water drain and clean if necessary		•	•
date of tire repair set (where applicable), reset Tire Pressure Monitoring System (TPMS) Tires – rotate, reset TPMS Wiper Blades – check condition and replace if necessary (USA only) Wiper Blades – check condition (Canada only) Wiper Blades – check condition (Canada only) Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable) Front Lighting – check function of parking lights, low beams, high beams, fog lights, blinkers and hazard lights Rear Lighting – check function of brake lights (including third brake light), taillights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights Service Reminder Display – reset Horn – check function Door Hinges and Straps – lubricate	~ ·	•		
Wiper Blades – check condition and replace if necessary (USA only) Wiper Blades – check condition (Canada only) Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable) Front Lighting – check function of parking lights, low beams, high beams, fog lights, blinkers and hazard lights Rear Lighting – check function of brake lights (including third brake light), taillights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights Service Reminder Display – reset Horn – check function Door Hinges and Straps – lubricate	date of tire repair set (where applicable), reset Tire Pressure		•	•
Wiper Blades – check condition (Canada only) Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable) Front Lighting – check function of parking lights, low beams, high beams, fog lights, blinkers and hazard lights Rear Lighting – check function of brake lights (including third brake light), taillights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights Service Reminder Display – reset Horn – check function Door Hinges and Straps – lubricate	Tires – rotate, reset TPMS	• 5K only		
Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable) Front Lighting – check function of parking lights, low beams, high beams, fog lights, blinkers and hazard lights Rear Lighting – check function of brake lights (including third brake light), taillights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights Service Reminder Display – reset Horn – check function Door Hinges and Straps – lubricate	Wiper Blades – check condition and replace if necessary (USA only)	•	•	•
add fluid if necessary Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable) Front Lighting – check function of parking lights, low beams, high beams, fog lights, blinkers and hazard lights Rear Lighting – check function of brake lights (including third brake light), taillights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights Service Reminder Display – reset Horn – check function Door Hinges and Straps – lubricate	Wiper Blades – check condition (Canada only)	•	•	•
MMI (if applicable) Front Lighting – check function of parking lights, low beams, high beams, fog lights, blinkers and hazard lights Rear Lighting – check function of brake lights (including third brake light), taillights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights Service Reminder Display – reset Horn – check function Door Hinges and Straps – lubricate	Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary	•	•	•
blinkers and hazard lights Rear Lighting – check function of brake lights (including third brake light), taillights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights Service Reminder Display – reset Horn – check function Door Hinges and Straps – lubricate Or, IT, ITS, R8 Coupe and R8 Spyder only	Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable)			•
back-up lights, rear fog lights, license plate lights, blinkers and hazard lights Service Reminder Display – reset Horn – check function Door Hinges and Straps – lubricate O7, TT, TTS, R8 Coupe and R8 Spyder only	Front Lighting – check function of parking lights, low beams, high beams, fog lights, blinkers and hazard lights		•	•
Horn – check function Door Hinges and Straps – lubricate O7, TT, TTS, R8 Coupe and R8 Spyder only	Rear Lighting – check function of brake lights (including third brake light), taillights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights		•	•
Door Hinges and Straps – lubricate Q7, TT, TTS, R8 Coupe and R8 Spyder only	Service Reminder Display – reset	•	•	_
	Horn – check function		•	•
Doors – lubricate door hinges, straps, locks and hood latch	Door Hinges and Straps - lubricate		 Q7, TT, TTS, R8 Coupe and R8 Spyder only 	
	Doors – lubricate door hinges, straps, locks and hood latch			•



2015 MY Scheduled Maintenance Intervals (continued)

The first scheduled service is due at 5,000 miles (8,000km) or 1 year after delivery, whichever occurs first. Thereafter, all remaining scheduled services are due every 10,000 miles or 1 year after previous service, whichever occurs first.

Miles (in thousands)	5/25/45/65/85/105/125	15/55/95/135	35/75/115
Kilometers (in thousands)	8/40/70/100/130/160/190	25/85/145/205	55/115/175
Hood Lid Hinges – lubricate		R8 Coupe, R8 Spyder, TT and TTS only	R8 Coupe, R8 Spyder, TT and TTS only
All Sunroof Systems – clean guide rails and lubricate with grease		•	•
Front Latch for Cabriolet Roof – lubricate		 A3 Cabriolet, A5 Cabriolet and S5 Cabriolet only 	 A3 Cabriolet, A5 Cabriolet and S5 Cabriolet only
Brake System - check for damage, leaks, pad thickness, fluid level	•	•	•
Brake Discs – check thickness			•
Exhaust System – check for damage, leaks		•	•
Front and Rear Axle – check for excessive play, check dust seals on ball joints and tie rod ends		•	•
Drive Shaft Boots – check		•	•
Automatic Transmission and Final Drive - check for leaks		•	•
Manual Transmission and Final Drive - check for leaks		•	•
Continuously Variable Transmission (multitronic) – change ATF			•
DSG/S Tronic® – change MTF oil for gear box		RS 5 only	RS 5 only
DSG/S Tronic – change ATF oil and replace transmission filter element for clutch hydraulics			A3, S4, S5, S5 Cabriolet, S6, S7, RS 5, TT, TTS, R8 Coupe and R8 Spyder
Tiptronic Gear Box – change ATF			Q5 hybrid only
Rear Sport Differential – change ATF for clutch hydraulics and differential oil			RS 5 and RS 7 only
Underbody – check for damage and leaks		•	•
Road Test – check engine performance, clutch, manual/automatic transmission, braking (including hand and foot brake), steering, wheels, wheel bearings, drive shaft, horn and hybrid vehicles (electric drive for operational readiness)		•	•
Timber Balk and an at 110K wiles (175,000 km) or TTC Charles and itime of time a balk to a facility			

Timing Belt - replace at 110K miles (175,000 km) on TTS. Check condition of timing belt tensioning system, dampening pulleys and idler pulleys, and replace if necessary

Brake Fluid – replace every 2 years regardless of mileage

Cloth Top – check function and rollover protection every 2 years regardless of mileage (A5/S5 Cabriolet and R8 Spyder only)

AdBlue Fluid - replace every 4 years regardless of miles/kilometers only if AdBlue has not been filled within the last 4 years (Q7 3.0L TDI, A8 3.0L TDI, A7 3.0L TDI, A7 3.0L TDI and Q5 3.0L TDI only)

Crash Active Headrest – check function every 2 years regardless of miles/kilometers (A8 only)

Haldex Clutch - change oil every 3 years regardless of mileage/kilometers (A3, Q3, TT and TTS only)

*Does not include 2.0L TFSI Flex Fuel engines.

Audi of America, Inc. believes the information and specifications to be correct at the time of printing. Specifications, maintenance intervals, standard features and options subject to change without notice.

^{**}If DPF replacement is not necessary, perform check every 20,000 miles (30,000 km) thereafter until replacement becomes necessary. Subsequent DPF replacement interval is a minimum of 120,000 miles (195,000 km) thereafter.