

SB-10054774-6543

Service Bulletin

1-14

Section

5 - Aerodynamic Devices

Description

Ship loose sleeper roof fairings

Release Date

1/13/2014

Revision History

1/24/2014: Added information relating to the installation of the fairing and specified gaps allowed between cab roof and fairing

Introduction

Model 579 and 567 72" and 80" sleeper roof fairings will be shipped with the vehicle from the factory. This bulletin provides instructions to remove the fairing from the vehicle and separate it from the shipping structure.

Warranty

This bulletin is for information only. Warranty does not apply.

Procedure

Please read this [procedure](#) before attempting to unload the sleeper roof fairing from the vehicle when it comes from the factory.

NOTE: When installing the roof fairing, be sure to maintain **1/2" (12.7 mm) gap** between the fairing and the cab/sleeper.

Attachments

[FSB 1-14 procedure](#)

Access to PACCAR's Enterprise Portal is provided as a benefit of doing business with PACCAR. All applications and content accessed through this system are confidential and proprietary and the property of PACCAR Inc and its suppliers, and must be kept strictly confidential pursuant to the contract licensing such access. Disclosure, publication, release or distribution of any material found on PACCAR systems to any person other than employees with a need to know such information is strictly prohibited. All activity on this system is monitored. If PACCAR suspects or discovers any unauthorized activity, access may be immediately terminated without prior notification. Violators may be subject to legal action.

© Copyright 2014 PACCAR Inc. All rights reserved. We welcome your [feedback](#) on this page. For technical questions or concerns about this page, please contact the [DealerNet Webmaster](#).