



TT437: 2014 TOURING WINDSHIELD WARRANTY REPLACEMENT

June 24, 2014

SB-10056038-7106




APPLIES TO	SYMPTOMS
All 2014 fairing equipped Touring and Trike models	• Cosmetic Information

See Figure 1. There are two common conditions found when windshields are returned for warranty:

- Damage with sharp cutting tool (1) when windshield is removed from seat during PDI
- Scratches (2) or cracks from improper windshield installation

Neither of these types of damage are covered under warranty.



1. Cutting tool damage

2. Scratches from improper installation

Figure 1. Windshield Damage

Proper Windshield Installation

NOTE

Although they appear similar, 2014 and later Touring windshields do not install the same as earlier model years.

The following procedure replaces the windshield installation procedure in the 2014 Touring Service Manual (99483-14) and 2014 PDI Manual (99947-14C).

1. Remove the three screws along the top of the outer fairing.
2. Loosen but do not remove the two upper inner fairing screws.

NOTE

Forcing the windshield/wind deflector keyholes down over the fairing bosses can split or scratch the windshield.

3. See Figure 2. Install windshield.
 - a. Gently spread the inner and outer fairings at the windshield opening.
 - b. Fit the keyhole on one end of the windshield over the raised boss on the inner fairing.
 - c. Fit the center keyhole over the center raised inner fairing boss.
 - d. Fit the keyhole on the opposite end of the windshield over the inner fairing raised boss.
4. Start the three windshield screws.

NOTICE

Over tightening windshield screws can crack windshield and/or fairing. (00451b)

5. Starting with the center screw, tighten to 25-30 **in-lbs** (2.8-3.4 Nm).
6. Tighten the upper inner fairing screws to 20-30 **in-lbs** (2.3-3.4 Nm).




Figure 2. Windshield/Wind Deflector Keyhole