



GROUP
Body

MODEL
2015MY
K900 (KH)

NUMBER
PS299

DATE
March 2014



TECHNICAL OPERATIONS

SUBJECT: CORRECT PROCEDURE FOR RAISING WINDSHIELD WIPERS

When servicing the windshield wipers on K900 (KH) vehicles during PDI, always use the procedure outlined below to raise the wiper arms to the fully vertical position in order to avoid damaging the paint on the rear edge of the hood. It is important to note that K900 wipers are recessed under the hood to provide better appearance and reduced wind noise characteristics.

Raising the windshield wiper arms:

1. Press the Start Button twice to turn the vehicle ignition ON and press it again to turn it OFF.
2. Within 3 seconds after turning the vehicle ignition OFF, raise the wiper blade control stalk and hold it for more than two (2) seconds (see image A).
3. The wiper arms will move upward and stop in the fully vertical position (see image B). The wiper arms may now be moved away from the windshield for any needed PDI process or service procedures.
4. Once finished servicing the wipers, press the Start Button twice to turn the vehicle ignition ON. Then, move the wiper blade control stalk up to return the wipers to the "parked" position.
5. Finally, press the Start Button once to turn the vehicle ignition to the OFF position.

All dealer staff should become familiar with this procedure to prevent paint damage when using a raised wiper arm as a sign for vehicle readiness status or for locating the vehicle.

