

A5, A5 Cabriolet S5,RS5 2015 FLUID CAPACITY CHART 31July 2014 Final

/ 10 	gabiloiet e	Oji (OO ZO	10 1 2012		9117 (1 (1	Toury 2014 I mai	, , ,	000
Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
A5	2.0L TFSI 220 hp	6-Spd	N/A	Rear F/Drive	10.0 L (10.5 qt)***	1.0 L (1.1qt)	Refrigerant	4.5L (4.8 qt)
Coupe	(CAED)	(0B2)		(0BC)		(approximately)	Use only R134a	(4.)
quattro	4.6L (4.9 qt)	(==)		New Fill:		(550 g ± 15 g	Fluid PN
,,,,,,,,	- (- 17	4.5L (4.7qt)		0.9L (1.0 qt)		Audi Brake Fluid	(19.5 oz. ± 0.5 oz.)	G 052 164*
(8T35G9)	Audi Oil Spec**	- (17		(1,7		Specification:	(
`Manual ´	VW 502 00**	Oil PN		Oil PN			Refrigerant Oil	
	Use synthetic oil	G 055 532 A2*		G 052 145 S2*		Use new fluid only.	Use a PAG oil	
A5	SAE 5W-40,		CVT (0AW)	Front F/Drive		·	with R134a	
Cabriolet	SAE 5W-30 or		New Fill:	New Fill:		FMVSS 116 DOT 4		
FWD	SAE 0W-40		8.0 L (8.5 qt)	1.1L (1.2 qt)		or SAE J 1703		
							Oil Capacity	
(8F75GH)			Change:	Oil PN			Denso	
Auto			5.5 – 6.0 L	G 055 190 A2*			150 cc +/- 10 cc	
			(5.8 - 6.3 qt)			Fluid PN	$(5.0 \pm 0.3 \text{ fl. oz.})$	
			Oil PN			B 000 750 *		
			G 052 516 A2*				Fluid PN	
A5	2.0L TFSI 211 hp		8-Spd	Front F/Drive			G 052 300 A2*	
quattro	(CPMB)		Tiptronic	New Fill:				
	4.6L (4.9 qt)		(OBK/OBL)	1.0L (1.1qt)				
			New Fill:	Transfer Case				
(8F752A)	Audi Oil Spec**	N/A	8.6 L (9.0 qt)	New Fill:				
Cabrio	VW 502 00**			1.1L (1.1qt)				
	Use synthetic oil SAE 5W-40,		Change:	Change:				
	SAE 5W-40,		3.6 - 4.0L	0.8L (0.84 qt.)				
	SAE 0W-40		(3.8 - 4.2 qt.)	0" 51				
A5			O'I DN	Oil PN				
Coupe			Oil PN	G 055 145 A2				
quattro			G 060 162 A2	Rear F/Drive (0BD)				
				New Fill:				
(8T352A)				1.0L (1.1 qt)				
				1.0L (1.1 qt)				
				Oil PN				
				G 052 145 S2*				
			1	0 002 140 02			1	

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

© 2014 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.

A5, A5 Cabriolet S5,RS5 2015 FLUID CAPACITY CHART 31 July 2014 Final



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
S5	3.0L V6 333 hp	6-Spd	N/A	Front F/Drive	12.0 L (12.6 qt)***	1.0 L (1.1qt)	Refrigerant	4.5L (4.8 qt)
Coupe	(CTUB)	(0B4)		New Fill:		approximately	Use only R134a	
quattro	6.8L (7.2 qt)			1.0L (1.1qt)			550 g ± 15 g	Fluid PN
		3.8L (4.0 qt)				Audi Brake Fluid	$(19.5 \text{ oz.} \pm 0.5)$	G 052 164*
(8T3549)				Oil PN		Specification:	oz.)	
Manual	Audi Oil Spec**	Oil PN		G 052 145 S2*				
	VW 502 00**	G 052 911 A2*				Use new fluid	Refrigerant-RS5	
A5/S5	Use synthetic oil SAE 5W-40,		7-Spd DSG	Transfer Case		only.	Use only R134a	
Coupe	SAE 5W-30 or	N/A	(0B5)	New Fill:			570 g ± 20 g	
quattro	SAE 0W-40		New Fill:	4.35L (4.5 qt)		FMVSS 116 DOT	(20.1 oz. ± 0.7	
			7.0 - 7.5L			4	oz.)	
(8T354Y)			(7.3 - 7.9 qt)	<u>Oil PN</u> G 052 532 A2*		or SAE J 1703		
Cabriolet			Change:				Refrigerant Oil	
quattro			6.7L (7.0 qt)	Rear F/Drive			Use a PAG oil	
(8F754Y)			approx.	(0BC / 0BF)		Fluid PN	with R134a	
,			1 1	New Fill:		B 000 750 *		
RS5	4.2L V8 450 hp	N/A	Oil PN	0.9L (1.0 qt)	15.0 L (15.8qt)***			
Coupe	(CFSA)		G 052 529 A2*		(1)		Oil Capacity	
quattro	9.7L (10.2 qt)			Oil PN			Denso	
	, , , ,			G 052 145 S2*			150 cc +/- 10 cc	
(8T35XY)							(5.0 ± 0.3 fl. oz.)	
,	Audi Oil Spec**							
RS5	VW 502 00**						Fluid PN	
Cabriolet	Use synthetic oil SAE 5W-40,						G 052 300 A2*	
quattro	SAE 5W-40, SAE 5W-30 or SAE 0W-40							
(8F75XY)								

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

© 2014 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.