



Phone: 706-356-5379

Fax: 706-356-4431

www.carry-ontrailer.com

Service Bulletin

PURPOSE:

Field retrofit for the spring assist gate. The rear ramp gate with spring assist may disengage from the offset U-bolt latch causing the rear ramp gate to fall from its upright position.

SCOPE:

6' and 7' wide tandem axle trailers with spring assist rear ramp gate.

ACTION:

At no charge to you, Carry-On Trailer customer service will send you a retrofit repair kit to lock the rear ramp gate into the lowest position of the spring assist bracket. Contact customer service at 800-240-3121 or customer.service@carry-ontrailer.com.

PART # 11GATEREPAIRKIT

EACH REPAIR KIT WILL INCLUDE

- (4) 3/8" ID fender washers
- (2) 3/8" x 1" hex head cap bolt
- (2) 3/8" nylock nut
- (2) restraint straps



INSTALLATION OF THE RETROFIT REPAIR KIT

Step 1: With the rear ramp gate in its down position, place the restraint strap in the slotted hinge bracket at the bottom of the ramp and press into place. Place the arched end of the restraint strap against the hinge bolt.



Step 2: Install one flat washer on the carriage bolt and insert through the restraint strap. Install second flat washer on the bolt and screw on the nylock nut. Tighten with a 9/16" wrench



Step 3: Repeat installation steps for the otherside.