

	GROUP <b>Chassis</b>	MODEL <b>2016MY ~ Optima (JFa)</b>
	NUMBER <b>PS438</b>	DATE <b>October 2015</b>
 		
SUBJECT:                   OPTIMA (JFa) – ALIGNMENT SPECIFICATIONS		

This article provides the alignment specifications for 2016MY Optima (JFa). In the event a wheel alignment is needed, ensure your alignment equipment has the correct specifications programmed into the PC database. Any warranty claims submitted with the improper alignment specifications may be subject to chargeback. A before and after print-out MUST be submitted with each warranty claim and MUST include the VIN, RO Number, Model and Model Year.

**NOTE: Do NOT refer to the alignment specifications for Optima (JFa) in the service information on KGIS. The information is incorrect and will be corrected in the near future. In the meantime, if a vehicle requires an alignment, refer the alignment specifications in the table below.**

Optima (JFa) Alignment Specifications:	
Front Toe:	Specification
Individual	0.0° ± 0.1°
Total	0.0° ± 0.2°
Front Camber & Caster	Specification
Front Camber	-0.5° ± 0.5°
Front Caster	4.68° ± 0.5°
Rear Toe:	Specification
Individual	0.085° ± 0.1°
Total	0.17° ± 0.2°
Rear Camber	Specification
	-1.0° ± 0.5°