
March 31, 201501616 Version 1

Fuel Gauge Does Not Work and the Low Fuel Indicator Blinks with Fuel in the Tank

AFFECTED VEHICLES

Year	Model	VIN Range
2001–15	Civic CNG	ALL

SYMPTOM

The fuel gauge does not work and the low fuel indicator blinks with fuel in the tank.

TROUBLESHOOTING PROCEDURE

NOTE:

- If the PCM has any DTCs, do the DTC troubleshooting in the electronic service manual first before continuing.
 - See the electronic service manual for specific procedures called out in this bulletin.
1. Do a battery cable reset. For details, see *ServiceNews* article “Try a Battery Cable Reset for Those Odd Electrical Problems,” posted in **January 2012**. You can also see this demonstrated in the *Tech2Tech* video “Try a Battery Cable Reset!”

Does the problem go away?


YES – Check for contamination in both fuel filters A and B and replace if needed. If the problem happens again, replace the thermostatic valve. If the problem persists, replace fuel pressure regulator P1.

NO – Go to step 2.

2. Close the manual shutoff valve.
3. Remove PGM-FI main relay 2.
4. Turn the ignition to ON.

<p>CUSTOMER INFORMATION: The information in this bulletin is intended for use only by skilled technicians who have the proper tools, equipment, and training to correctly and safely maintain your vehicle. These procedures should not be attempted by “do-it-yourselfers,” and you should not assume this bulletin applies to your vehicle, or that your vehicle has the condition described. To determine whether this information applies, contact an authorized Honda automobile dealer.</p>
--

5. Measure the voltage between the fuel pressure regulator terminal No. 1 and body ground.



Is there more than 3 volts?


YES – Go to step 6.

NO – Substitute a known-good PCM, then recheck. If the symptom goes away, replace the original PCM.

6. Disconnect the fuel temperature sensor on the fuel rail.
7. With the vehicle in a well-ventilated area or outside, loosen the sensor until gas escapes. After the gas has vented, go to step 8.

NOTE: When venting the sensor, the O-ring must be replaced.

8. Measure the voltage between the fuel pressure regulator terminal No. 1 and body ground.




Is there more than 3 volts?

YES – Go to step 9.

NO – Replace fuel pressure regulator P1.

9. Turn the ignition to OFF.
10. Unplug the fuel pressure regulator switch 2-pin connector.
11. Check for continuity between terminal No. 2 and body ground on the connector side.

FUEL PRESSURE REGULATOR SWITCH 2P CONNECTOR




Connector side of female terminals

Is there continuity?

YES – Go to step 12.

NO – Repair an open in the wire between the fuel pressure regulator switch and G201 (2001–05 models) and G401 (2006–15 models).

12. Measure the voltage between terminal No. 1 and body ground on the connector side.



Is there more than 3 volts?

YES – Go to step 13.

NO – Repair an open in the wire between the fuel pressure regulator switch and PCM connector terminal E28 (2001–05 models) A-41 (2006-11 models) A-23 (2012–15 models).

13. Replace fuel pressure regulator P1, and recheck.

Does the low fuel indicator blink?

YES – Do a fuel leak inspection. If there is no leak, substitute a known-good PCM, then recheck. If the symptom goes way, replace the original PCM.

NO – No further action is needed. Return the vehicle to your customer.

END