

To: All Toyota Cold Climate Dealers
From: Product Support Division

Toyota Corrosion-Resistant Compound Campaign Spray Equipment Verification

We have determined that there may have been some instances where dealerships received the incorrect spray wands for the 712AM paraffin wax based product. Dealers should have been supplied internal spray wands that are 8mm in diameter. In the event that you received a 6mm wand, please **STOP** use of this wand and contact Quality Compliance so that we may provide the correct equipment.

How to differentiate between the two wands:

The tips/nozzles are distinguishable for each of the wands. Shown below are the differences in the wand tips/nozzles.

Figure 1



-Figure 1 shows the 8mm wand. **This is the CORRECT wand.** Notice that the tips/nozzles, on both ends, sit flush to the plastic tubing.

Figure 2



-Figure 2 shows the 6mm wand. **This wand should NO LONGER be used.** This nozzle has a tapered tip and has a compression fitting at the end that connects to the spray gun.

To acquire new 8MM nozzles, or any other CRC Equipment, please email Quality Compliance at quality_compliance@toyota.com or call the Hotline at **310-468-5516**.

Gun Maintenance Reminder

- Once you are finished spraying:
 - Disconnect the air supply.
 - DO NOT PULL THE TRIGGER.** Doing so will cause the chemical to back feed through the gun.
 - Slowly twist the canister, until the air pressure depletes, then retighten.
 - Leave the spray tube attached and place originally equipped cap on the tip (for internal wand).
 - Leave the spray tube attached and wrap the tip with Saran Wrap® (for external wand).
- **NEVER** disassemble and/or attempt to clean the gun.
- If needed, you may wipe the gun down with a towel.
- **NEVER** use brake/parts cleaner on the gun or the spray nozzles.