



# Service Bulletin

## INFORMATION

**Subject:** Intake Manifold Inspection/Replacement After Severe Internal Engine Damage

**Models:** 2016 and Prior GM Passenger Cars and Trucks

**Attention:** This Bulletin also applies to any of the above models that may be Export vehicles.

*This Bulletin has been revised to add graphics and additional information. Please discard Corporate Bulletin Number 00-06-01-026F.*

### General Information

- When replacing an engine due to internal damage, extreme care should be taken when transferring the intake manifold to the new Genuine GM Part service engine long block. The internal engine damage may have resulted in the potential discharge of internal engine component debris into the intake manifold via broken pistons and/or bent, broken, or missing intake valves.
- After removing the intake manifold from the engine, the technician **MUST** carefully inspect all of the cylinder head intake ports to see if the valve heads are still present and not bent. Usually when the valve heads are missing or sufficiently bent, internal engine component debris will be present to varying degrees in the intake port of the cylinder head. If this debris is present in **ANY** of the cylinder head intake ports, the intake manifold should be replaced.
- This replacement is required due to the complex inlet runner and plenum configuration of most of the intake manifolds, making thorough and complete component cleaning difficult and nearly impossible to verify the complete removal of debris. Reinstallation of an intake manifold removed from an engine with deposits of internal engine component debris may result in the ingestion of any remaining debris into the new Genuine GM Part service engine. This will cause damage or potential failure of the new Genuine GM Part service engine long block.

### Broken Valves, Broken Pistons and Piston to Cylinder Head Damage — Catalytic Converter Failures

#### Broken Valves, Broken Pistons and Piston to Cylinder Head Damage

Broken valves, broken pistons and piston to cylinder head damage all create material debris that scatters throughout the induction system.

- ⇒ If **ANY** of the above were to occur, the intake manifold **MUST** be replaced or subsequent severe engine damage will occur. This replacement is required due to the complex inlet runner and plenum configuration of most of the intake manifolds, making thorough and complete component cleaning difficult and impossible to verify the complete removal of all debris.

#### Catalytic Converter Failures


When catalytic converter failures occur and the inner brick becomes plugged and breaks apart, the catalytic converter material can be sucked back into the engine during valve overlap and transfer throughout the intake manifold and into the cylinder. Any such material transfer can cause heavy wear to piston rings and cylinder walls. Misfires and oil consumption are the by products of ingested catalytic converter material into the combustion chamber and cylinder bores.

### Typical Intake Manifold Debris Views After Internal Engine Damage


#### View of Debris in Aluminum Intake Manifold — Throttle Body Opening



**View of Debris in Aluminum Intake Manifold — Ports to Cylinder Heads**




**View of Debris in Plastic Intake Manifold — Throttle Body Opening**



### Internal View of Plastic Intake Manifold Lower Half — Plenum and Runner Complexity

**Notice:** The plastic intake manifold **CANNOT** be disassembled.

### Internal View of Plastic Intake Manifold Lower Half — Plenum and Runner Complexity



**This internal view shows the plenum and runner complexity and is the reason why the intake manifold **CANNOT** be completely cleaned of debris.**

1. Intake port to cylinder head opening.
2. Areas where debris can collect.
3. Areas where debris can collect.
4. Areas where debris can collect.

Ultrasonic welding is an industrial technique whereby high-frequency ultrasonic acoustic vibrations are locally applied to workpieces, (in this case the plastic

intake manifold) that are being held together under pressure to create a solid-state weld. It is commonly used for plastics and for joining dissimilar materials. In ultrasonic welding, there are no connective bolts, nails, soldering materials, or adhesives necessary to bind the materials together.

---

GM bulletins are intended for use by professional technicians, NOT a "do-it-yourselfer". They are written to inform these technicians of conditions that may occur on some vehicles, or to provide information that could assist in the proper service of a vehicle. Properly trained technicians have the equipment, tools, safety instructions, and know-how to do a job properly and safely. If a condition is described, DO NOT assume that the bulletin applies to your vehicle, or that your vehicle will have that condition. See your GM dealer for information on whether your vehicle may benefit from the information.



WE SUPPORT VOLUNTARY TECHNICIAN CERTIFICATION