



Countries: BAHAMAS, BOLIVIA, BELIZE, CANADA, CHILE, TAIWAN, COLOMBIA, COSTA RICA, DOMINICAN REPUBLIC, ECUADOR, EL SALVADOR, TRINIDAD AND TOBAGO, UNITED STATES, URUGUAY, VENEZUELA, ARUBA, NICARAGUA, PERU, PUERTO RICO, Curaçao, GUAM, GUATEMALA, GUYANA, HAITI, HONDURAS, JAMAICA, KOREA, SOUTH KOREA, PANAMA

Document ID: IK2200075

Availability: ISIS, Bus ISIS, FleetISIS

Major System: BUS BODY

Current Language: English

Other Languages: [Français](#), [Español](#),

Viewed: 471

Revision: 5

Created: 6/25/2008

Last Modified: 10/29/2015

Author: Will (Mark) Wiley

[Less Info](#)

Hide Details

Coding Information

Copy Link	Copy Relative Link	Bookmark	Add to Favorites	Print	Provide Feedback	Helpful	Not Helpful
		 View My Bookmarks				 75	 35

Title: FE and RE Bus Windshield Glass Discoloration (Fogging)

Applies To: RE, FE Buses

Issue:

Windshield glass discoloring or fogging at the bottom edge. The discoloring or fogging is the result of moisture in the seal rubber penetrating between the 2 layers of glass.



Solution:

Replacement windshield glass should be edge sealed by applying 2 separate coats of poly urethane, poly urethane primer, or acrylic paint to the windshield prior to installation. Apply sealer to the bottom edge and approx six (6) inches up on vertical edge of the glass. This seals the edge of the laminated glass to reduce moisture intrusion. After the windshield has been installed, any excess sealer left exposed on the glass can be removed with a razor blade.



 Hide Details**Feedback Information**

Viewed: 470

Helpful: 75

Not Helpful: 35

No Feedback Found

Copyright © 2015 Navistar, Inc.