



2008 A4 / S4 A

Engine	Part	Part Number	Quantity
2.0L TFSI: BWT	Oil Filter	06D115562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SA2E-5W-30, or SAE-0W-40	N/A	4.5L (4.8qt)
	Drain Plug + Gasket	N 90813202	1
	Air Filter	06C133843	1

Engine	Part	Part Number	Quantity
3.2L V6 TFSI: BKH	Oil Filter	06E115562A	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.5L (6.9qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	06C133843	1

Engine	Part	Part Number	Quantity
	Oil Filter	079198405A	1
4.2L V8: BHF	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	9.0L (9.5qt)
	Drain Plug Gasket	N 0138503	1
	Air Filter	079133843A	1

Miscellaneous	Part	Part Number	Quantity
	Pollen Filter (20K Only)	8E0819439	1
	Driver's Wiper Blade (Left)	4B1955425C	1
Miscellaneous	Passenger's Wiper Blade (Right)	4B1955425C	1
	Battery	000915105DHDSP	1
	Battery	000915105DKDSP	1

6-16-2015





A4 2008 FLUID CAPACITY CHART updated 13 Oct. 2011 (Page 1 of 2)

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield and Headlight Fluid
A4 FWD Sedan (8EC5EC) A4 FWD Sedan (8EC5EH) Cabriolet (8HE5EH) A4 quattro Sedan (8EC5E9) Avant (8EC5E9) A4 quattro Sedan (8EC5EL) Avant (8EC5EL) Cabriolet (8ED5EL)	2.0 TFSI 200 hp (BWT) 4.5L (4.8qt) Audi Oil Spec**	6-Spd (01X) 3.0L (3.2qt) Oil PN G 052 911 A2* NA 6-Spd (02X) 3.5L (3.7qt) Oil PN G 052 911 A2*	CVT (01J) New Fill: 7.7L (8.1qt) Change: 4.5 – 4.8L (4.8 – 5.1qt) Oil PN G 052 180 A2* NA 6-Spd Tiptronic (09L) New Fill: 9.0L (9.5qt) Change: 8.0L (8.5qt) approx. Oil PN G 055 005 A2* or G 055 162 A2*	NA Front F/Drive New Fill: 1.3L (1.4qt) Oil PN G 052 145 S2* Front F/Drive New Fill: 1.1L (1.2qt) Oil PN G 052 145 S2* Transfer Case 1.5L (1.6 qt.) Oil PN G 052 515 A2 Rear F/Drive (0AR) New Fill: 0.9L (1.0qt) Oil PN G 052 145 S2* Oil PN G 052 515 A2 Rear F/Drive (0AR) New Fill: 0.9L (1.0qt) Oil PN G 052 145 S2* Oil PN Oil PN	9.0L 9.5qt)***	1.0 L (1.1qt) (approximately) Fluid PN G 002 000 * or G 004 000*	1.0 L (1.1qt) (approximately) Audi Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750 *	Refrigerant Use only R134a A4 500 ± 20g (17.6 ± 0.7 oz.) RS4 440 ± 20g (15.5 ± 0.7 oz.) Refrigerant Oil Use a PAG oil with R134a Except 8 cyl. 120 ± 10cc (4.0 ± 0.3 fl. oz.) Regul 130 ± 10cc (4.3 ± 0.3 fl. oz.) Fluid PN See ETKA	Cabrio 4.5L (4.8qt) Cabriolet 4.8L (5.1qt) Sedan 4.1L (4.4 qt.) Fluid PN G 052 164*





A4 2008 FLUID CAPACITY CHART (Page 2 of 2)

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield and Headlight Fluid
A4 FWD Sedan (8EC5PH) A4 quattro Sedan (8EC5P9) Avant (8ED5P9) A4 quattro Sedan (8EC5PL) Avant (8EC5PL) Avant (8EC5PL) Avant (8ED5PL)	3.2L V6 255 hp (BKH) 6.5L (6.9qt) Audi Oil Spec**	6-Spd (02X) 3.5 L (3.7 qt) Oil PN G 052 911 A2*	CVT (01J) New Fill: 7.7L (8.1qt) Change: 4.5 – 4.8L (4.8 – 5.1qt) Oil PN G 052 180 A2* NA 6-Spd Tiptronic (09L) New Fill: 9.0L (9.5qt) Change: 8.0L (8.5qt) approx. Oil PN G 055 005 A2* or G 055 162 A2*	Front F/Drive New Fill: 1.3L (1.4qt) Oil PN G 052 190 A2* Rear F/Drive (01R) 1.5L (1.6 qt.) Rear F/Drive (0AR) 0.9L (1.0 qt.) Oil PN G 052 145 S2* Frt F/Drive New Fill: 1.1L (1.2qt) Oil PN G 052 145 S2* Transfer Case 1.5L (1.6 qt.) Oil PN G 052 515 A2 Rear F/Drive (0AR) New Fill: 0.9L (1.0qt) Oil PN G 052 515 A2 Rear F/Drive (0AR) New Fill: 0.9L (1.0qt) Oil PN G 052 145 S2*	9.0L (9.5qt)***	1.0 L (1.1qt) (approximately) Fluid PN G 002 000 * or G 004 000*	1.0 L (1.1qt) (approximately) Audi Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750 *	Refrigerant Use only R134a A4 500 ± 20g (17.6 ± 0.7 oz.) RS4 440 ± 20g (15.5 ± 0.7 oz.) Refrigerant Oil Use a PAG oil with R134a Except 8 cyl. 120 ± 10cc (4.0 ± 0.3 fl. oz.) Regriderant See ETKA	Cabrio 4.5L (4.8qt) Cabriolet 4.8L (5.1qt) Sedan 4.1L (4.4 qt.) Fluid PN G 052 164*

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

© 2011 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 17-08-27 (2010043) for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.





S4 and RS4 2008 FLUID CAPACITY CHART (updated 17 Jan 2012)

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield and Headlight Fluid
S4 quattro Sedan (8EC54L) Avant (8ED54L) Cabriolet (8HE54L)	4.2L V8 340 hp (BHF) 9.0L (9.5qt) Audi Oil Spec**	NA	6-Spd Tiptronic (09L) New Fill: 9.8L (10.4qt) Change: 8.0L (8.5qt) approx. Oil PN G 055 005 A2* or G 055 162 A2*	Front F/Drive New Fill: 1.1L (1.2qt) Oil PN G 052 145 S2* Rear F/Drive (0AR) New Fill: 0.9L (1.0qt) Oil PN	12.2L (12.9qt)***	1.0 L (1.1qt) (approximately) Fluid PN G 002 000 * or G 004 000*	1.0 L (1.1qt) (approximately) Audi Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN	Refrigerant Use only R134a A4 500 ± 20g (17.6 ± 0.7 oz.) RS4 440 ± 20g (15.5 ± 0.7 oz.) Refrigerant Oil Use a PAG oil	4.1L (4.3qt) Sedan 4.8L (5.1qt) Cabriolet Fluid PN G 052 164*
S4 quattro <u>Sedan</u> (8EC549) <u>Avant</u> (8ED549)		6-Spd (0A3) 3.2L (3.4qt) Oil PN G 052 911 A2*	NA NA	G 052 145 S2* Rear F/Drive (0AR) New Fill: 0.9 L (1.0 qt) Oil PN G 052 145 S2*			B 000 750 *	with R134a Except 8 cyl. 120 ± 10cc (4.0 ± 0.3 fl. oz.) 8 cyl 130 ± 10cc	
Cabriolet (8HE549) RS 4 quattro Sedan (8EC5X9) Cabriolet (8HE5X9)	4.2L V8 420 hp (BNS) 9.9L (10.5qt) Audi Oil Spec** 9.9L (10.5 qt.)	_			11.5L (12.2qt)***			(4.3 ± 0.3 fl. oz.) Fluid PN See ETKA	

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.