



Engine	Part	Part Number	Quantity
<b>3.2L V6: CALA</b>	Oil Filter	06E115562A	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.5L (6.9qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use o-ring:	8K0133843 N 90964301	1 1

Engine	Part	Part Number	Quantity
<b>4.2L V8: CAUA</b>	Oil Filter	079198405E	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	9.1L (9.6qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use o-ring:	8K0133843 N 90964301	1 1

Miscellaneous	Part	Part Number	Quantity
<b>Miscellaneous</b>	Pollen Filter (20K Only) PR-9AK	8K0819439	1
	Pollen Filter (20K Only) PR-9AQ	8K0819439B	1
	Driver's Wiper Blade (Left) >> 01.10.2007	8T1955425A	1
	Driver's Wiper Blade (Left) 01.10.2007 >>	8K1955425A	1
	Passenger's Wiper Blade (Right) >> 01.10.2007	8T1955426A	1
	Passenger's Wiper Blade (Right) 01.10.2007 >>	8K1955426A	1
	Battery	000915105DHDSP	1
	Battery	000915105DKDSP	1
	Battery	000915105DLDSP	1



## A5 and S5 - 2008 FLUID CAPACITY CHART updated 25 June 2010

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Rear Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield Fluid
<b>A5 Coupe quattro</b>  (8T35F9) Manual	<b>3.2L V6 265 hp (CALA)</b> 6.5L (6.9 qt)  <u>Audi Oil Spec**</u>	<b>6-Spd (0B2)</b>  4.8L (5.1qt) <u>Oil PN</u> G 052 911 A2*	<b>N/A</b>	<b>(0BD)</b> 1.0L (1.1 qt)  <u>Oil PN</u> G 052 145 S2*	9.0 L (9.5 qt)***	1.0 L (1.1qt) (approximately)  <u>Fluid PN</u> G 002 000 * or G 004 000*	1.0 L (1.1qt) (approximately)  <u>Audi Brake Fluid Specification:</u>  Use new fluid only.  FMVSS 116 DOT 4 or SAE J 1703	<u>Refrigerant</u> Use only R134a  600 ± 20g (21.1 ± 0.7 oz.)  <u>Refrigerant Oil</u> Use a PAG oil with R134a  <u>Oil Capacity</u> For Denso  150 cc +/- 10 cc (5.0 ± 0.3 fl. oz.)  <u>Fluid PN</u> G 052 300 A2*	4.5L (4.8 qt)  <u>Fluid PN</u> G 052 164*
<b>A5 Coupe quattro</b>  (8T35FL) Automatic		<b>N/A</b>	<b>6-Spd (0B6)</b> New Fill: 10.4L (11.0qt)  <u>Oil PN</u> G 060 162 A2*						
<b>S5 Coupe quattro</b>  (8T35B9) Manual	<b>4.2L V8 354 hp (CAUA)</b> 9.1L (9.6 qt)  <u>Audi Oil Spec**</u>	<b>6-Spd (0B4)</b>  3.8L (4.0 qt) <u>Oil PN</u> G 052 911 A2*	<b>N/A</b>	<b>(0BC)</b> 0.9L (1.0 qt)  <u>Oil PN</u> G 052 145 S2*	12.2 L (12.9qt)***		<u>Fluid PN</u> B 000 750 *		
<b>S5 Coupe quattro</b>  (8T35BL) Automatic		<b>N/A</b>	<b>6-Spd (0B6)</b> New Fill: 10.4L (11.0qt)  <u>Oil PN</u> G 060 162 A2*	<u>Transfer Case</u> 1.0 L (1.1 qt.)  <u>Oil PN</u> G055 154 A2					

**For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.**

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\*Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

\*\*\* Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.