



Engine	Part	Part Number	Quantity
3.2L V6: CALB	Oil Filter	06E115562A	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.2L (6.6qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use o-ring:	8K0133843 N 90964301	1 1

Miscellaneous	Part	Part Number	Quantity
Miscellaneous	Pollen Filter (20K Only) PR-9AK	8K0819439	1
	Pollen Filter (20K Only) PR-9AQ	8K0819439B	1
	Driver's Wiper Blade (Left)	8R1955425B	1
	Passenger's Wiper Blade (Right)	8R1955426B	1
	Rear Wiper Blade	8R0955425	1
	Battery	000915105CEDSP	1

Resetting the service interval display

Your authorized Audi dealer will reset the display after performing a service on your vehicle. You are able to reset the oil change display only.

Select the **CAR** > **Service interval display** > **Reset oil change interval**



Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service Reminder remains stored even when the vehicle battery is disconnected.



Q5 - 2009 FLUID CAPACITY CHART updated 25 June 2010

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
Q5 SUV quattro (8RB5EL)	3.2L V6 270 hp (CALB) 6.2L (6.6qt) Audi Oil Spec: VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	NA	6-Spd Tiptronic (0B6) <u>New Fill:</u> 10.4L (11.0qt) Oil PN G 060 162 A2* Transfer Case 1.0L (1.1 qt.) Oil PN G 055 145 A2	Front F/Drive <u>New Fill:</u> 1.0L (1.1qt) Rear F/Drive (0BD) <u>New Fill:</u> 1.0L (1.1qt) Oil PN G 052 145 S2*	8.7 L (9.2 qt)***	1.0 L (1.1qt) (approximately) Fluid PN G 002 000* or G 004 000*	1.0 L (1.1qt) (approximately) VW Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750*	Refrigerant Use only R134a 600 ± 0.7 g (21.1 ± 0.7 oz.) Refrigerant Oil Use a PAG oil with R134a 150 ± 10 cc (5.1 ± 0.3 fl. oz.)	4.6 L (4.9 qt) Fluid PN G 052 164*

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

** Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.

© 2010 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.