Executive Service



2010 A4/S4

Engine	Part	Part Number Quantity		
	Oil Filter	1		
2.0L TFSI: CAEB	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)	
2.0L 1751. CAED	Drain Plug Gasket	N 0138157	1	
	Air Filter	8R0133843K	1	

Engine	Part	Part Number	Quantity
	Oil Filter	06E115562A	1
3.0L V6: CCBA	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.2L (6.6qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use o-ring:	8K0133843 N 90964301	1

Miscellaneous	Part	Part Number	Quantity
	Pollen Filter (20K Only) PR-9AK	8K0819439	1
	Pollen Filter (20K Only) PR-9AQ	8K0819439B	1
	Driver's Wiper Blade (Left)	8K1955425A	1
	Passenger's Wiper Blade (Right)	8K1955426A	1
Miscellaneous	Battery	000915105CDDSP	1
Miscellaneous	Battery	000915105CEDSP 000915105CFDSP	1
	Battery		1
	Battery	000915105DHDSP	1
	Battery	000915105DKDSP	1
	Battery	000915105DLDSP	1

6-16-2015

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.

Executive Service

2010 A4/S4



Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select the CAR > Service interval display > Reset oil change interval.



Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

6-16-2015

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.

A4, A4 Avant and S4 -2010 FLUID CAPACITY CHART updated 5 Oct 2012

			Aud
Truth	in	Engin	ooring



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
A4 FWD Sedan (8K256H) A4 quattro Sedan-Manual (8K2569) A4 quattro Sedan-Auto (8K256L) Avant-Auto (8K556L)	2.0L TFSI 211 hp (CAEB) 4.6L (4.9qt) <u>Audi Oil Spec**</u>	N/A 6-Spd (0B2) 4.8L (5.1qt) <u>Oil PN</u> G 055 532 A2* N/A	CVT (0AW) <u>New Fill:</u> 8.0L (8.5qt) <u>Change:</u> 5.5 - 7.0L (5.8 - 7.4) <u>Oil PN</u> G 052 516 A2* N/A	Front F/Drive New Fill: 1.1L (1.2qt) Oil PN G 055 190 A2* Rear F/Drive (0BC) New Fill: 0.9L (1.0qt) Oil PN G 052 145 S2* Front F/Drive New Fill: 1.0L (1.1qt) Oil PN G 052 145 S2* Rear F/Drive (0BD) New Fill: 1.1L (1.1qt) Oil PN G 052 145 S2*	7.0 L (7.4 qt)***	Capacity information not available <u>Fluid PN</u> G 002 000* or G 004 000*	1.0 L (1.1qt) (approximately) <u>VW Brake Fluid</u> <u>Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	Refrigerant Use only R134a 600 ± 20 g (21.1 ± 0.7 oz.) Refrigerant Oil Use a PAG oil with R134a Oil Capacity & PN For Denso 150 cc +/- 10 cc G 052 300 A2*	4.5 L (4.8 qt) <u>Fluid PN</u> G 052 164*

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 17-09-12 (2010043) for engine oils that meet this Audi standard.

*** Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.

Page 1 of 2

© 2012 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

A4, A4 Avant and S4 -2010 FLUID CAPACITY CHART updated 5 Oct 2012 Truth in Engineering

Vehicle

(Sales Code)

S4

quattro

(8K2549)

Manual

Engine Oil

approx. qty.

w/filter change

3.0L V6 333 hp

(CCBA)

6.2L (6.6qt)

Audi Oil Spec**

Manual Trans	Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
6-Spd	N/A	Rear F/Drive	11.1 L (11.7qt)***	Capacity	1.0 L (1.1qt)	Refrigerant	4.5 L (4.8 qt)
(0B4)		(0BD)		information not	(approximately)	Use only R134a	
3.8L (4.0qt)				available			Fluid PN
		New Fill:				600 ± 20 g	G 052 164*
Oil PN		1.0L (1.1qt)		Fluid PN	VW Brake Fluid	(21.1 ± 0.7 oz.)	
G 052 911 A2*				G 002 000*	Specification:		

	Audi Oli Spec	G 052 911 AZ			G 002 000	specification.		
				Oil PN	or			
				G 052 145 S2*	G 004 000*	Use new fluid only.	Refrigerant Oil	
							Use a PAG oil	
						FMVSS 116 DOT 4	with R134a	
S4		N/A	7-Spd DSG	Front F/Drive		or SAE J 1703		
quattro			(0B5)	New Fill:				
				5.0L (5.3qt)			Oil Capacity & PN	
(8K254Y)			New Fill:				For Denso	
Auto			7.5L (7.9qt)	Oil PN		Fluid PN		
				G 052 513 A2*		B 000 750*	150 cc +/- 10 cc	
			Change:				G 052 300 A2*	
			6.7L (7.0qt)					
			approx.	Rear F/Drive				
				(0BC / 0BF)				
			<u>Oil PN</u>	New Fill:				
			G 052 529 A2*	0.9L (1.0qt)				
				<u>Oil PN</u>				
				G 052 145 S2*				

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 17-09-12 (2010043) for engine oils that meet this Audi standard.

*** Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.

© 2012 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

Page 2 of 2

