



2010 A6 / S6

-			
^		\sim	
	•	$\overline{}$	

Engine	Part	Part Number	Quantity	
3.2L TFSI: CALA	Oil Filter	06E115562A	1	
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.5L (6.9qt)	
	Drain Plug Gasket	N 0138157	1	
	Air Filter Also use o-ring:	4F0133843 N 90964301	1	

Engine	Part	Part Number	Quantity	
3.0L V6 TFSI: CCAA	Oil Filter	06E115562A	1	
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.5L (6.9qt)	
	Drain Plug Gasket	N 0138157	1	
	Air Filter Also use o-ring:	4F0133843 N 90964301	1	

Engine	Part	Part Number	Quantity
4.2L V8: BVJ	Oil Filter	079198405E	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40		8.5L (9.0qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use o-ring:	4F0133843 N 90964301	1

Engine	Part	Part Number	Quantity	
	Oil Filter	079198405E	1	
5.2L V10: BXA	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	10.0L (10.6qt)	
	Drain Plug Gasket	N 0138157	1	
	Air Filter	07L133843E	1	

6-16-2015

Executive Service



2010 A6 / S6

Miscellaneous	Part	Part Number	Quantity
	Pollen Filter Kit (20K Only) PR-9AK	4F0898438	1
	Pollen Filter Kit (20K Only) PR-9AQ	4F0898438C	1
Miscellaneous	Driver's Wiper Blade (Left)	4F1955425F	1
	Passenger's Wiper Blade (Right)	4F1955426C	1
	Battery	000915105CEDSP	1
	Battery	000915105DLDSP	1

Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select function button CAR > Systems* > Service Interval display > Reset oil change interval.



Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service
 Reminder remains stored even when the vehicle battery is disconnected.

6-16-2015

A6 and S6 - 2010 FLUID CAPACITY CHART updated 25 June 2010



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Auto Trans	Front Final Drives	Rear Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
A6 FWD	3.2L V6 265 hp (CALA)	CVT (01J) New Fill: 7.5L (7.9qt)	Front F/Drive	NA	9.6L (10.1 qt)***	Capacity Information Not	1.0 L (1.1qt) (approximately)	Refrigerant Use only R134a 530 ± 20g	4.8 L (5.1 qt)
(4F25RH)	6.5L (6.9qt)	<u>Change:</u> 4.5 - 5.0L	New Fill: 1.3L (1.4qt)			Available	VW Brake Fluid	$(18.7 \pm 0.7 \text{ oz.})$	G 052 164*
	Audi Oil Spec**	(4.8–5.3qt) <u>Oil PN</u> G 052 180 A2*	<u>Oil PN</u> G 052 190 A2*			Fluid PN G 002 000 * or	Specification: Use new fluid only.	Refrigerant Oil Use a PAG oil	
A6 quattro	3.0L V6 300 hp (CCAA)	6-Spd Tiptronic (09L)	Front F/Drive	Transfer Case 0.6 L (0.6 qt.)		G 004 000*	FMVSS 116 DOT 4 or SAE J 1703	with R134a	
(4F25VL) Sedan	6.5L (6.9qt) Audi Oil Spec**	<u>New Fill:</u> 9.8L (10.4qt) Change:	New Fill: 1.1L (1.2qt)	<u>Oil PN</u> G 055 145 A2				For Denso use:	
(4F55VL) Avant A6	4.2L V8 350 hp	8.0L (8.5qt)	Oil PN G 052 145 S2*	Rear F/Drive (0AR)	12.0L (12.7 qt)***		Fluid PN B 000 750*	130 cc +/- 10 cc G 052 300 A2*	
quattro	(BVJ)	G 060 162 A2*		0.9L (1.0qt)	12.0L (12.7 qt)				
(4F25DL)	8.5L (9.0qt) Audi Oil Spec**			Oil PN G 052 145 S2*					
S6 quattro	5.2L V10 435 hp (BXA)	6-Spd Tiptronic (09E)	Front F/Drive		15.0L (15.9 qt)***				
(4F25SL)	10L (10.6qt)	<u>New Fill:</u> 10.4L (11qt)	New Fill: 1.2L (1.3qt)						
	Audi Oil Spec**	<u>Change:</u> 10L (10.6qt) <u>Oil PN</u> G 055 005 A2*	<u>Oil PN</u> G 055 145 A2*						

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

© 2010 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 17-09-12 (2010043) for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.