



Engine	Part	Part Number	Quantity
2.0L TFSI: CAEB	Oil Filter	06J115403Q	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	8R0133843K	1

Engine	Part	Part Number	Quantity
3.0L V6: CCBA	Oil Filter	06E115562A	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.2L (6.6qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use o-ring:	8K0133843 N 90964301	1

Miscellaneous	Part	Part Number	Quantity
Miscellaneous	Pollen Filter (20K Only) PR-9AK	8K0819439	1
	Pollen Filter (20K Only) PR-9AQ	8K0819439B	1
	Driver's Wiper Blade (Left)	8K1955425A	1
	Passenger's Wiper Blade (Right)	8K1955426A	1
	Battery	000915105CDDSP	1
	Battery	000915105CEDSP	1
	Battery	000915105CFDSP	1
	Battery	000915105DHDSP	1
	Battery	000915105DKDSP	1
Battery	000915105DLDSP	1	

6-16-2015

Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select the **CAR** > **Service interval display** > **Reset oil change interval**.



Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

A4, A4 Avant and S4 -2011 FLUID CAPACITY CHART 5 Oct 2012

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
A4 FWD Sedan (8K256H)	2.0L TFSI 211 hp (CAEB) 4.6L (4.9qt) <u>Audi Oil</u> <u>Spec**</u>	N/A	CVT (0AW) New Fill: 8.0L (8.5qt) Change: 5.5 – 7.0L (5.8 – 7.4qt) Oil PN G 052 516 A2*	Front F/Drive New Fill: 1.1L (1.2qt) Oil PN G 055 190 A2*	7.0 L (7.4 qt)**	1.0 L (1.1qt) approximately Fluid PN G 002 000* or G 004 000*	1.0 L (1.1qt) approximately VW Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750*	Refrigerant Use only R134a 600g ± 20g (21.1 ± 0.7 oz.) Refrigerant Oil Use a PAG oil with R134a Oil Capacity & PN For Denso 150 cc +/- 10 cc G 052 300 A2*	4.5 L (4.8 qt) Fluid PN G 052 164*
A4 quattro Sedan-Manual (8K2569)		6-Spd (0B2) 4.8L (5.1qt) Oil PN G 055 532 A2*	N/A	Rear F/Drive (0BC) New Fill: 0.9L (1.0qt) Oil PN G 052 145 S2*					
A4 quattro Sedan-Auto (8K256A) Avant-Auto (8K556A)		N/A	6-Spd Tiptronic (0B6) New Fill: 10.4L (11.0qt) Oil PN G 060 162 A2* 8-Spd Tiptronic (0BK/OBL) New Fill: 9.0L (9.5qt) Oil PN G 060 162 A2	Front F/Drive New Fill: 1.0L (1.1qt) Oil PN G 052 145 S2* Transfer Case 1.0 L (1.1 qt.) Oil PN G 055 145 A2 Rear F/Drive (0BD) New Fill: 1.1L (1.1qt) Oil PN G 052 145 S2*					

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi standard.

*** Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.

A4, A4 Avant and S4 -2011 FLUID CAPACITY CHART 5 Oct 2012

Audi
Truth in Engineering



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
S4 quattro (8K2549) Manual	3.0L V6 333 hp (CCBA) 6.2L (6.6qt) <u>Audi Oil Spec**</u>	6-Spd (0B4) 3.8L (4.0qt) <u>Oil PN</u> G 052 911 A2*	N/A	Rear F/Drive (0BD) <u>New Fill:</u> 1.0L (1.1qt) <u>Oil PN</u> G 052 145 S2*	11.1 L (11.7qt)***	1.0 L (1.1qt) approximately <u>Fluid PN</u> G 002 000* or G 004 000*	1.0 L (1.1qt) approximately <u>VW Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	<u>Refrigerant</u> Use only R134a 600g ± 20g (21.1 ± 0.7 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil Capacity & PN</u> For Denso 150 cc +/- 10 cc G 052 300 A2*	4.5 L (4.8 qt) <u>Fluid PN</u> G 052 164*
S4 quattro (8K254Y) Auto		N/A	7-Spd DSG (0B5) <u>New Fill:</u> 7.5L (7.9qt) <u>Change:</u> 6.7L (7.0qt) approx. <u>Oil PN</u> G 052 529 A2*	Front F/Drive <u>New Fill:</u> 5.0L (5.3qt) <u>Oil PN</u> G 052 513 A2* Transfer Case 5.0 L (5.3 qt.) <u>Oil PN</u> G 052 513 A2 Rear F/Drive (0BC / 0BF) <u>New Fill:</u> 0.9L (1.0qt) <u>Oil PN</u> G 052 145 S2*					

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 17-09-12 (2010043) for engine oils that meet this Audi standard.

*** Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.