



Engine	Part	Part Number	Quantity
2.0L TFSI: CAEB	Oil Filter	06J115403Q	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter – Coupe	8R0133843K	1
	Air Filter - Cabrio	8R0133843D	1

Engine	Part	Part Number	Quantity
3.0L V6: CCBA	Oil Filter	06E115562A	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.2L (6.6qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use o-ring:	8K0133843 N 90964301	1 1

Engine	Part	Part Number	Quantity
4.2L V8: CAUA	Oil Filter	079198405E	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	8.8L (9.3qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use o-ring:	8K0133843 N 90964301	1 1

Miscellaneous	Part	Part Number	Quantity
Miscellaneous	Pollen Filter (20K Only) PR-9AK	8K0819439	1
	Pollen Filter (20K Only) PR-9AQ	8K0819439B	1
	Driver's Wiper Blade (Left)	8K1955425A	1
	Passenger's Wiper Blade (Right) Coupe	8K1955426A	1
	Passenger's Wiper Blade (Right) Cabrio	8F1955426A	1
	Battery	000915105DHDSP	1
	Battery	000915105DKDSP	1
	Battery	000915105DLDSP	1

6-16-2015

Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select **CAR** > **Service Interval display** > **Reset oil change interval**.



Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

A5, A5 Cabriolet and S5, S5 Cabriolet - 2011 FLUID CAPACITY CHART

25 October 2010

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid	
A5 Coupe quattro (8T3569) Manual	2.0L TFSI 211 hp (CAEB) 4.6L (4.9 qt) <u>Audi Oil Spec**</u>	6-Spd (0B2) 4.8L (5.1qt) <u>Oil PN</u> G 052 911 A2*	N/A	Rear F/Drive (0BC) <u>New Fill:</u> 0.9L (1.0 qt) <u>Oil PN</u> G 052 145 S2*	7.8 L (8.2 qt)***	1.0 L (1.1qt) (approximately) <u>Fluid PN</u> G 002 000 * or G 004 000*	1.0 L (1.1qt) (approximately) <u>Audi Brake Fluid Specification:</u> Use new fluid only.	<u>Refrigerant</u> Use only R134a 600 g ± 20 g (21.1 oz. ± 0.7 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a	4.5L (4.8 qt) <u>Fluid PN</u> G 052 164*	
A5 Cabriolet FWD (8F756H) Auto			CVT (0AW) <u>New Fill:</u> 8.0 L (8.5 qt) <u>Change:</u> 5.5 – 6.0 L (5.8 – 6.3 qt) <u>Oil PN</u> G 052 516 A2*	Front F/Drive <u>New Fill:</u> 1.1L (1.2 qt) <u>Oil PN</u> G 055 190 A2*	7.0 L (7.4 qt)***		1.0 L (1.1qt) (approximately) <u>Fluid PN</u> B 000 750 *	FMVSS 116 DOT 4 or SAE J 1703		<u>Oil Capacity</u> Denso 150 cc +/- 10 cc (5.0 ± 0.3 fl. oz.) <u>Fluid PN</u> G 052 300 A2*
A5 quattro (8T356L) Coupe-Auto (8F756A) Cabrio-Auto			N/A	6-Spd (0B6) <u>New Fill:</u> 10.4 L (11.0 qt) <u>Oil PN</u> G 060 162 A2*	Front F/Drive <u>New Fill:</u> 1.0L (1.1qt) Transfer Case <u>New Fill:</u> 1.1L (1.1qt) <u>Oil PN</u> G 055 145 A2		7.8 L (8.2 qt)*** Coupe 7.0 L (7.4 qt)*** Cabriolet	9.0 L (9.5 qt)***		
A5 Coupe quattro (8T356A) Automatic				8-Spd Tiptronic (0BK/OBL) <u>New Fill:</u> 9.0 L (9.5 qt) <u>Oil PN</u> G 060 162 A2	Rear F/Drive (0BD) <u>New Fill:</u> 1.1L (1.1 qt) <u>Oil PN</u> G 052 145 S2*					

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.

A5, A5 Cabriolet and S5, S5 Cabriolet - 2011 FLUID CAPACITY CHART

25 October 2010

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
S5 Coupe quattro (8T35B9) Manual	4.2L V8 354 hp (CAUA) 8.8L (9.3 qt) <u>Audi Oil Spec**</u>	6-Spd (0B4) 3.8L (4.0 qt) <u>Oil PN</u> G 052 911 A2*	N/A	Rear F/Drive (0BC) 0.9L (1.0 qt) <u>Oil PN</u> G 052 145 S2*	12.2 L (12.9qt)***	1.0 L (1.1qt) approximately <u>Fluid PN</u> G 002 000 * or G 004 000*	1.0 L (1.1qt) approximately <u>Audi Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750 *	<u>Refrigerant</u> Use only R134a 600 g ± 20 g (21.1 oz. ± 0.7 oz.) <u>Refrigerant-RS5</u> Use only R134a 570 g ± 20 g (20.1 oz. ± 0.7 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil Capacity</u> Denso 150 cc +/- 10 cc (5.0 ± 0.3 fl. oz.) <u>Fluid PN</u> G 052 300 A2*	4.5L (4.8 qt) <u>Fluid PN</u> G 052 164*
			N/A	6-Spd (0B6) <u>New Fill:</u> 10.4L (11.0 qt) <u>Oil PN</u> G 060 162 A2*					
S5 Cabriolet quattro (8F754Y) Automatic	3.0L V6 333 hp (CCBA) 6.2L (6.6 qt) <u>Audi Oil Spec**</u>	N/A	7-Spd DSG (0B5) <u>New Fill:</u> 7.5L (7.9 qt) <u>Change:</u> 6.7L (7.0 qt) approx. <u>Oil PN</u> G 052 529 A2*	Transfer Case <u>New Fill:</u> 5.0L (5.3 qt) <u>Oil PN</u> G 052 513 A2*	11.1 L (11.7qt)***				
		Rear F/Drive (0BC / 0BF) <u>New Fill:</u> 0.9L (1.0 qt) <u>Oil PN</u> G 052 145 S2*							

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.