



Engine	Part	Part Number	Quantity
3.2L TFSI: CALA	Oil Filter	06E115562A	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.5L (6.9qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use o-ring:	4F0133843 N 90964301	1

Engine	Part	Part Number	Quantity
3.0L V6 TFSI: CCAA	Oil Filter	06E115562A	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.5L (6.9qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use o-ring:	4F0133843 N 90964301	1

Engine	Part	Part Number	Quantity
4.2L V8: BVJ	Oil Filter	079198405E	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	8.5L (9.0qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use o-ring:	4F0133843 N 90964301	1

Engine	Part	Part Number	Quantity
5.2L V10: BXA	Oil Filter	079198405E	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	10.0L (10.6qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	07L133843E	1

6-16-2015



Miscellaneous	Part	Part Number	Quantity
<i>Miscellaneous</i>	Pollen Filter Kit (20K Only) PR-9AK	4F0898438	1
	Pollen Filter Kit (20K Only) PR-9AQ	4F0898438C	1
	Driver's Wiper Blade (Left)	4F1955425F	1
	Passenger's Wiper Blade (Right)	4F1955426C	1
	Battery	000915105CEDSP	1
	Battery	000915105DLDSP	1

Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select function button **CAR** > **Systems*** > **Service Interval display** > **Reset oil change interval.**



Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

A6 and S6 - 2011 FLUID CAPACITY CHART

13 Sept 2010

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Auto Trans	Front Final Drives	Rear Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
A6 FWD (4F25RH)	3.2L V6 265 hp (CALA) 6.5L (6.9qt) <u>Audi Oil Spec**</u>	CVT (01J) <u>New Fill:</u> 7.5L (7.9qt) <u>Change:</u> 4.5 - 5.0L (4.8-5.3qt) Oil PN G 052 180 A2*	Front F/Drive New Fill: 1.3L (1.4qt) Oil PN G 052 190 A2*	NA	9.6L (10.1 qt)***	1.0 L (1.1qt) (approximately) Fluid PN G 002 000 * or G 004 000*	1.0 L (1.1qt) (approximately) VW Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750*	Refrigerant Use only R134a 530 ± 20g (18.7 ± 0.7 oz.) Refrigerant Oil Use a PAG oil with R134a Oil PN & Capacity For Denso use: 130 cc ± 10 cc (4.4 ± 0.3 fl. oz.) G 052 300 A2*	4.8 L (5.1 qt) Fluid PN G 052 164*
A6 quattro (4F25VL) Sedan (4F55VL) Avant	3.0L V6 300 hp (CCAA) 6.5L (6.9qt) <u>Audi Oil Spec**</u>	6-Spd Tiptronic (09L) <u>New Fill:</u> 9.8L (10.4qt) <u>Change:</u> 8.0L (8.5qt) Oil PN G 060 162 A2*	Front F/Drive New Fill: 1.1L (1.2qt) Oil PN G 052 145 S2*	Transfer Case 0.6 L (0.6 qt.) Oil PN G 055 145 A2 Rear F/Drive (0AR) 0.9L (1.0qt) Oil PN G 052 145 S2*	12.0L (12.7 qt)***				
A6 quattro (4F25DL)	4.2L V8 350 hp (BVJ) 8.5L (9.0qt) <u>Audi Oil Spec**</u>	6-Spd Tiptronic (09E) <u>New Fill:</u> 10.4L (11qt) <u>Change:</u> 10L (10.6qt) Oil PN G 055 005 A2*	Front F/Drive New Fill: 1.2L (1.3qt) Oil PN G 055 145 A2*		15.0L (15.9 qt)***				
S6 quattro (4F25SL)	5.2L V10 435 hp (BXA) 10L (10.6qt) <u>Audi Oil Spec**</u>	6-Spd Tiptronic (09E) <u>New Fill:</u> 10.4L (11qt) <u>Change:</u> 10L (10.6qt) Oil PN G 055 005 A2*	Front F/Drive New Fill: 1.2L (1.3qt) Oil PN G 055 145 A2*		15.0L (15.9 qt)***				

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.