



Engine	Part	Part Number	Quantity
<b>2.0L TFSI: CAEB</b>	Oil Filter	06J115403Q	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	8R0133843K	1

Engine	Part	Part Number	Quantity
<b>3.2L V6: CALB</b>	Oil Filter	06E115562A	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.2L (6.6qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter Also use o-ring:	8K0133843 N 90964301	1 1

Miscellaneous	Part	Part Number	Quantity
<b>Miscellaneous</b>	Pollen Filter (20K Only) PR-9AK	8K0819439	1
	Pollen Filter (20K Only) PR-9AQ	8K0819439B	1
	Driver's Wiper Blade (Left)	8R1955425B	1
	Passenger's Wiper Blade (Right)	8R1955426B	1
	Rear Wiper Blade	8R0955425	1
	Battery	000915105CEDSP	1

### Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select function button **CAR** > **Service interval display** > **Reset oil change interval**.



#### Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



#### Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

# Q5 - 2011 FLUID CAPACITY CHART 25 June 2010

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
<b>Q5</b> SUV quattro  (8RB56A)	<b>2.0 TFSI 211 hp (CAEB)</b>  4.6L (4.9 qt)  <u>Audi Oil Spec**</u>	<b>NA</b>	<b>8-Spd Tiptronic (OBK/OBL)</b>  New Fill: 9.0L (9.5qt)  <u>Oil PN</u> <b>G 060 162 A2</b>  <b>Transfer Case</b> 1.0L (1.1 qt.) <u>Oil PN</u> G 055 145 A2	<b>Front F/Drive</b> New Fill 1.1L (1.2 qt.)  <b>Rear F/Drive (0BD)</b>  1.0L (1.1qt)  <u>Oil PN</u> G 052 145 S2*	8.7 L (9.2 qt)***	1.0 L (1.1qt) (approximately)  <u>Fluid PN</u> G 002 000* or G 004 000*	1.0 L (1.1qt) (approximately)  <u>VW Brake Fluid Specification:</u>  Use new fluid only.  FMVSS 116 DOT 4 or SAE J 1703  <u>Fluid PN</u> B 000 750*	<u>Refrigerant</u> Use only R134a 600g ± 20g (21.1 ± 0.7 oz.)  <u>Refrigerant Oil</u> Use a PAG oil with R134a  <u>Oil Capacity &amp; PN</u> For Denso  150 cc +/- 10 cc (5.1 ± 0.3 oz.)  G 052 300 A2*	4.6 L (4.9 qt)  <u>Fluid PN</u> G 052 164*
<b>Q5</b> SUV quattro  (8RB5EL)	<b>3.2L V6 270 hp (CALB)</b>  6.2L (6.6qt)  <u>Audi Oil Spec:</u> VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	<b>NA</b>	<b>6-Spd Tiptronic (0B6)</b>  New Fill: 10.4L (11.0qt)  <u>Oil PN</u> G 060 162 A2*  <b>Transfer Case</b> New Fill: 1.0L (1.1 qt.)  <u>Oil PN</u> G 052 515 A2	<b>Front F/Drive</b> New Fill: 1.0L (1.1qt)  <u>Oil PN</u> G 052 145 S2*  <b>Rear F/Drive (0BD)</b>  1.0L (1.1qt)  <u>Oil PN</u> G 052 145 S2*	8.7 L (9.2 qt)***				

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\*Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

\*\*\* Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.