Executive Service

2011 Q7



Engine	Part	Part Number	Quantity	
	Oil Filter	06E115562A	1	
3.0L V6: CJWC	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)	
3.0L vo. cyvvc	Drain Plug Gasket	N 0138157	1	
	Air Filter PR-1L0	7L0129620	1	
	Air Filter PR-1L2	7L0129620A	1	

Engine	Part	Part Number	Quantity	
	Oil Filter	06E115562A	1	
3.0L V6: CJWB	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)	
3.0L VO. CJVVB	Drain Plug Gasket	N 0138157	1	
	Air Filter PR-1L0	7L0129620	1	
	Air Filter PR-1L2	7L0129620A	1	

Engine	Part	Part Number	Quantity	
	Oil Filter	057115561M	1	
3.0L V6 TDI: CATA	VW 507 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	8.2L (8.7qt)	
J.OL VO IDI. CATA	Drain Plug Gasket	N 0138157	1	
	Air Filter PR-1L0	7L0129620	1	
	Air Filter PR-1L2	7L0129620A	1	

Miscellaneous	Part	Part Number	Quantity	
	Pollen Filter (20K Only)	7H0819631A	1	
	Driver's Wiper Blade (Left)	4L1955425B	1	
	Passenger's Wiper Blade (Right)	4L1955426A	1	
Miscellaneous	Rear Wiper Blade	4L0955425	1	
Miscellaneous	Battery	000915105CEDSP	1	
	Battery	000915105DHDSP	1	
	Battery	000915105DKDSP	1	
	Battery	000915105DLDSP	1	

6-16-2015

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.

Executive Service

2011 Q7



Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select function button CAR > Systems* > Service interval display > Reset oil change interval.



Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service
 Reminder remains stored even when the vehicle battery is disconnected.

6-16-2015

Q7 - 2011 FLUID CAPACITY CHART

updated 21 June 2011



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	6 Speed Auto Trans	8 Speed Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
Q7 SUV quattro (4LB5ZA)	3.0L V6 272 hp (CJWC) 6.8L (7.2 qt.) Audi Oil Spec: VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	6-Spd Tiptronic (0AT) New Fill: 8.6L(9.1qt) Oil PN G 055 025 A2*	8-Spd Tiptronic (0C8) New Fill: 10.6L (11.2 qt) Oil PN G 055 540 A2*	Front F/Drive New Fill: 1.0L (1.1qt) Oil PN G 052 145 S2* Transfer Case New Fill: 0.65L (0.7 qt.) Oil PN	9.0L (9.5 qt)***	1.0 L (1.1qt) (approximately) Fluid PN G 002 000* or G 004 000*	1.0 L (1.1qt) (approximately) VW Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703	Refrigerant Use only R134a 1-Evaporator 700g ± 50g (24.7 oz. ± 1.8 oz.) 2-Evaporators 1050g ± 50g (37 oz. ± 1.8 oz.) Refrigerant Oil	4.5 L (4.8 qt) Fluid PN G 052 164*
Q7 SUV quattro (4LB5XA)	3.0L V6 333 hp (CJWB) 6.8L (7.2 qt.) Audi Oil Spec: VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	6-Spd Tiptronic (09D) New Fill: 9.0L (9.5qt) Oil PN G 055 025 A2*		G 052 536 A2* Rear F/Drive (0AB) New Fill: 1.3L (1.4qt) Oil PN G 052 145 S2*			<u>Fluid PN</u> B 000 750*	Use a PAG oil with R134a Oil Capacity 1-Evaporator 145cc ± 15cc (4.9 oz. ± 0.5 oz.) 2-Evaporators 245cc ± 15cc	
Q7 TDI SUV quattro (4LB5RA)	3.0L V6 225 hp Diesel (CATA) 8.2L (8.7 qt.) Audi Oil Spec: VW 507 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40		8-Spd Tiptronic (0C8) New Fill: 12.8L (13.5 qt) Oil PN G 055 540 A2*		23.0L (6.0 gal)**** ISO Standard 22241-1 Only fill with filling device VAS6542 & holding device SET740.			(8.3 oz. ± 0.5 oz.) <u>Oil PN</u> G 052 300 A2*	

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.

^{****} Part Numbers for AdBlue® Reducing Agent: 0.5 gal (1.89 L) G 052 910 A2, 2.6 gal (10.0L) G 052 910 A4.

^{© 2011} Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.