



Engine	Part	Part Number	Quantity
2.0L TFSI: CETA	Oil Filter	06J115403Q	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.5L (4.8qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	1K0129620D	1

Engine	Part	Part Number	Quantity
2.0L TFSI: CDMA	Oil Filter	06D115562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.5L (4.8qt)
	Drain Plug + Gasket	N 90813202	1
	Air Filter	1K0129620	1

Miscellaneous	Part	Part Number	Quantity
Miscellaneous	Pollen Filter (20K Only)	1K1819653B	1
	Pollen Filter (20K Only)	TBD	1
	Driver's Wiper Blade (Left)	8J1955425A	1
	Passenger's Wiper Blade (Right)	8J1955426A	1
	Battery	000915105CDDSP	1
	Battery	000915105DHDSP	1

To reset the display

The dealership performing the service resets the display when the service has been completed.

The display is resets as follows:

- Switch the ignition on.
 - Pull the knob ⇒ *fig. 19*. The message appears: **Oil change!**



Fig. 19 Section of instrument cluster: Service interval display

- Pull the knob until the display **Oil change in ----- mi (km)--- days** appears in the display. If the reset button is not pulled within 5 seconds, the display reset mode closes.



Tips

- If a malfunction is present (red symbol), the distance remaining cannot be called up.
- Do not reset the display between service intervals. Doing so will result in an incorrect display.
- If the battery is disconnected, the Service Interval display values are retained.
- If the service was not performed at the correct time or the service interval display was not reset after service was performed, the additional mileage driven or the elapsed days will be shown as negative numbers.

TT and TTS - 2011 FLUID CAPACITY CHART 25 June 2010

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Rear Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
TT - quattro (8J35VL) Coupe (8J95VL) Roadster	2.0L TFSI 200 hp (CETA) 4.5L (4.8 qt) <u>Audi Oil Spec:</u> VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	N/A	6-Spd DSG (02E) <u>New Fill:</u> 6.9 L (7.3 qt) <u>Change:</u> 5.5 L (5.8 qt) approx. <u>Oil PN</u> G 052 182 A2*	0BR 0.95 L (1.0 qt) <u>Oil PN</u> G 052 145 S2* Haldex Clutch <u>New Fill:</u> 0.85 L (0.9 qt) <u>Replacement:</u> 0.7 L (0.8 qt)	9.0 L (9.5 qt)***	Electro-Mechanical (No Fluid)	1.0 L (1.1 qt) (approximately) <u>VW Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	<u>Refrigerant Use only R134a</u> 500 ± 25 g (17.6 ± 0.9 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Denso Compressor</u> 90 ± 10 cc (3.0 oz. ± 0.3 oz.) <u>Part Number</u> G 052 300 A2 <u>Sanden Compressor</u> 110 cc ± 10 cc (3.7 oz. ± 0.3 oz.) <u>Part Number</u> G 052 154 A2	4.0 L (4.3 qt) <u>Fluid PN</u> G 052 164*
TTS - quattro (8J354L) Coupe (8J954L) Roadster	2.0L TFSI 265 hp (CDMA) 4.5L (4.8 qt) <u>VW Oil Spec:</u> VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40		Bevel Box <u>New Fill:</u> 0.9 L (1.0 qt) <u>Oil PN</u> G 052 145 S2*	<u>Oil PN</u> G 055 175 A2*	8.6 L (9.1 qt)***				

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Refer to Technical Bulletin 17-09-12 (2010043) for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.