Executive Service



Engine	Part	Part Number	Quantity	
2.0L TFSI: CCTA, CBFA	Oil Filter	06J115403Q	1	
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.8qt)	
	Drain Plug Gasket	N 0138157	1	
	Air Filter	1K0129620D	1	

Engine	Part	Part Number	Quantity
2.0L TDI: CBEA	Oil Filter	071115562C	1
	VW 507 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.0L (4.2qt)
	Drain Plug Gasket	N 90813202	1
	Air Filter	1K0129620E	1

Miscellaneous	Part	Part Number	Quantity
	Pollen Filter (20K Only)	1K1819653B	1
Miscellaneous	Pollen Filter (20K Only)		1
	Driver's Wiper Blade (Left)	8P1955425H	1
	Passenger's Wiper Blade (Right)	8P1955426H	1
	Rear Wiper Blade	8E9955425C	1
	Battery	000915105CCDSP	1
	Battery	000915105DEDSP	1
	Battery	000915105DGDSP	1
	Battery	000915105DHDSP	1

Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to the Audi specifications.

– Switch the ignition on.

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.





– Pull the knob \Rightarrow *fig. 19.* The message, **Service due!** appears.



Fig. 19 Section of instrument cluster: Service interval display

Pull the knob until the display **Oil change in ----- mi (km)--- days** appears in the display. If the RESET button is not pulled within 5 seconds, the display reset mode closes.



If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.

i) Tips

2012 A3

- If a malfunction is present (red symbol), the distance remaining cannot be called up.
- Do not reset the display between service intervals. Doing so will result in an incorrect display.
- If the battery is disconnected, the Service Interval Display values are retained.
- On vehicles with the Driver
 Information System, you can also call up the service interval display.
- If the service was not performed at the correct time or the service interval display was not reset after service was performed, the additional mileage driven or the elapsed days will be shown as negative numbers.

6-16-2015

^{© 2015} Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.

A3 - 2012 FLUID CAPACITY CHART updated 30 Jan 2013

Audi Truth in Engineering

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Rear Final Drive	Cooling System	Brake System	A/C System	Windshield Fluid
A3 FWD	2.0 TFSI 200 hp (CCTA/CBFA)	6-Spd (02Q) 2.3L (2.4qt)	N/A	N/A	10.0 L (10.5 qt)***	1.0 L (1.1qt) (approximately)	Refrigerant Use only R134a	3.0 L (3.1qt)
(8PA59C) (8PA5YC-PZEV)	4.6L (4.8qt)	<u>Oil PN</u>				<u>Audi Brake</u>	Refrig. Capacity 525 +/- 25 g	<u>Fluid PN</u> G 052 164*
Manual	Audi Oil Spec: VW 502 00** Use synthetic oil	G 052 171 A2*				Fluid Specification:	(18.5 ± 0.8 oz.)	
	SAE 5W-40, SAE 5W-30 or SAE 0W-40					Use new fluid only.	Refrigerant Oil Use a PAG oil	
A3 FWD - Auto		NA	6-Spd DSG®	Conscitu		FMVSS 116 DOT 4	with R134a Oil PN &	
(8PA59X) (8PA5YX-PZEV)			(02E) New Fill:	Capacity included with transmission.		or SAE J 1703 Fluid PN	Capacity 1) For Sanden use	
A3 TDI FWD	2.0L 140 hp (CBEA)		6.9 - 7.2L (7.3 - 7.6qt)		8.0L (8.4 qt)***	B 000 750 *	110 cc +/- 10 cc (3.7 ± 0.3 fl. oz.)	
(8PA5PX)	4.0L (4.2qt)		<u>Change:</u> 5.2 – 5.5L				2) For Zexel use 120 cc +/- 15 cc	
	Audi Oil Spec: VW 507 00**		(5.5 – 5.8 qt) approx.				(4.0 ± 0.3 fl. oz.)	
A3 quattro	2.0 TFSI 200 hp (CCTA/CBFA)		<u>Oil PN</u> G 052 182 A2*	02D / OAV 0.95L (1.0 qt) Oil PN	10.0L (10.5 qt)***		3) For Denso use 140 cc +/- 10 cc (4.7 ± 0.3 fl. oz.)	
(8PA59L) Auto	4.6L (4.8qt)			G 052 145 A1*			G 052 300 A2*	
	Audi Oil Spec: VW 502 00** Use synthetic oil		Bevel Box	Haldex Clutch <u>New Fill:</u> 0.85L (0.9qt)			G 052 154 A2*	
	SAE 5W-40, SAE 5W-30 or SAE 0W-40		<u>New Fill:</u> 0.9L (1.0qt) <u>Oil PN</u>	Replacement: 0.65L(0.7qt)				
			G 052 145 S2*	<u>Oil PN</u> G 060 175 A2*				

© 2013 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.