



| Engine                 | Part   | Part Number | Quantity     |
|------------------------|--|-------------|--------------|
| <b>2.0L TFSI: CAEB</b> | Oil Filter   | 06J115403Q  | 1            |
|                        | VW 502 00 Use synthetic oil<br>SAE 5W-40, SAE-5W-30, or<br>SAE-0W-40 | N/A         | 4.6L (4.9qt) |
|                        | Drain Plug Gasket  | N 0138157   | 1            |
|                        | Air Filter   | 8R0133843K  | 1            |

| Engine               | Part   | Part Number             | Quantity     |
|----------------------|--|-------------------------|--------------|
| <b>3.0L V6: CCBA</b> | Oil Filter   | 06E115562A              | 1            |
|                      | VW 502 00 Use synthetic oil<br>SAE 5W-40, SAE-5W-30, or<br>SAE-0W-40 | N/A                     | 6.2L (6.6qt) |
|                      | Drain Plug Gasket  | N 0138157               | 1            |
|                      | Air Filter<br>Also use o-ring:                                       | 8K0133843<br>N 90964301 | 1            |

| Miscellaneous        | Part                            | Part Number    | Quantity |
|----------------------|---------------------------------|----------------|----------|
| <b>Miscellaneous</b> | Pollen Filter (20K Only) PR-9AK | 8K0819439      | 1        |
|                      | Pollen Filter (20K Only) PR-9AQ | 8K0819439B     | 1        |
|                      | Driver's Wiper Blade (Left)     | 8K1955425A     | 1        |
|                      | Passenger's Wiper Blade (Right) | 8K1955426A     | 1        |
|                      | Battery                         | 000915105CDDSP | 1        |
|                      | Battery                         | 000915105CEDSP | 1        |
|                      | Battery                         | 000915105CFDSP | 1        |
|                      | Battery                         | 000915105DHDSP | 1        |
|                      | Battery                         | 000915105DKDSP | 1        |
| Battery              | 000915105DLDSP                  | 1              |          |

### Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select the **CAR** function button > **Service interval display** > **Reset oil change interval**.



#### Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



#### Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

# A4, A4 Avant and S4 - 2012 FLUID CAPACITY CHART updated 5 Oct 2012

| Vehicle<br>(Sales Code)  | Engine Oil<br>approx. qty.<br>w/filter change  | Manual<br>Trans  | Auto<br>Trans   | Final Drives  | Cooling<br>System | Power<br>Steering   | Brake System   | A/C System  | Windshield<br>& Headlight<br>Fluid                  |
|--|--|--|---|---|-------------------|---|--|---|---|
| <b>A4</b><br>FWD<br><br><u>Sedan</u><br>(8K256H)   | <b>2.0L TFSI 211 hp</b><br><b>(CAEB)</b><br><br>4.6L (4.9qt)<br><br><u>Audi Oil</u><br><u>Spec**</u> | N/A  | <b>CVT (0AW)</b><br>New Fill:<br>8.0L (8.5qt)<br><br>Change:<br><b>5.5 – 7.0L</b><br><b>(5.8 – 7.4qt)</b><br><u>Oil PN</u><br>G 052 516 A2*   | <b>Front F/Drive</b><br><br>New Fill:<br>1.1L (1.2qt)<br><br><u>Oil PN</u><br>G 055 190 A2*   | 7.0 L (7.4 qt)*** | 1.0 L (1.1qt)<br>approximately<br><br><u>Fluid PN</u><br>G 002 000*<br>or<br>G 004 000* | 1.0 L (1.1qt)<br>approximately<br><br><u>VW Brake Fluid</u><br><u>Specification:</u><br><br>Use new fluid only.<br><br>FMVSS 116 DOT 4<br>or SAE J 1703<br><br><u>Fluid PN</u><br>B 000 750* | <u>Refrigerant</u><br>Use only R134a<br>600g ± 20g<br>(21.1 ± 0.7 oz.)<br><br><u>Refrigerant Oil</u><br>Use a PAG oil<br>with R134a | 4.5 L (4.8 qt)<br><br><u>Fluid PN</u><br>G 052 164* |
| <b>A4</b><br>quattro<br><br><u>Sedan-Manual</u><br>(8K2569)                                    |  | <b>6-Spd</b><br><b>(0B2)</b><br><br>4.8L (5.1qt)<br><u>Oil PN</u><br>G 055 532 A2* | N/A   | <b>Rear F/Drive</b><br><b>(0BC )</b><br>New Fill:<br>0.9L (1.0qt)<br><br><u>Oil PN</u><br>G 052 145 S2*   |                   |   |  | <u>Oil Capacity &amp; PN</u><br>For Denso<br><br>150 cc +/- 10 cc<br>G 052 300 A2*  |   |
| <b>A4</b><br>quattro<br><br><u>Sedan-Auto</u><br>(8K256A)<br><br><u>Avant-Auto</u><br>(8K556A) |  | N/A  | <b>6-Spd</b><br><b>Tiptronic</b><br><b>(0B6)</b><br>New Fill:<br>10.4L (11.0qt)<br><u>Oil PN</u><br>G 060 162 A2*<br><br><b>8-Spd</b><br><b>Tiptronic</b><br><b>(0BK/OBL)</b><br>New Fill:<br>9.0L (9.5qt)<br><br><u>Oil PN</u><br>G 060 162 A2 | <b>Front F/Drive</b><br>New Fill:<br>1.0L (1.1qt)<br><u>Oil PN</u><br>G 052 145 S2*<br><b>Transfer Case</b><br>1.0 L (1.1 qt.)<br><u>Oil PN</u><br>G 055 145 A2<br><b>Rear F/Drive</b><br><b>(0BD)</b><br>New Fill:<br>1.1L (1.1qt)<br><br><u>Oil PN</u><br>G 052 145 S2* |                   |   |  |   |   |

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\*Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi standard.

\*\*\* Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.

# A4, A4 Avant and S4 - 2012 FLUID CAPACITY CHART updated 5 Oct 2012

| Vehicle<br>(Sales Code)                        | Engine Oil<br>approx. qty.<br>w/filter change                                      | Manual<br>Trans  | Auto<br>Trans   | Final Drives  | Cooling<br>System  | Power<br>Steering   | Brake System  | A/C System  | Windshield<br>& Headlight<br>Fluid                  |
|--|--|--|---|---|--------------------|---|---|---|---|
| <b>S4</b><br>quattro<br><br>(8K2549)<br>Manual | <b>3.0L V6 333 hp<br/>(CCBA)</b><br><br>6.2L (6.6qt)<br><br><u>Audi Oil Spec**</u> | <b>6-Spd<br/>(0B4)</b><br>3.8L (4.0qt)<br><br><u>Oil PN</u><br>G 052 911 A2* | N/A   | <b>Rear F/Drive<br/>(0BD)</b><br><br><u>New Fill:</u><br>1.0L (1.1qt)<br><br><u>Oil PN</u><br>G 052 145 S2*   | 11.1 L (11.7qt)*** | 1.0 L (1.1qt)<br>approximately<br><br><u>Fluid PN</u><br>G 002 000*<br>or<br>G 004 000* | 1.0 L (1.1qt)<br>approximately<br><br><u>VW Brake Fluid<br/>Specification:</u><br><br>Use new fluid only.<br><br>FMVSS 116 DOT 4<br>or SAE J 1703 | <u>Refrigerant</u><br>Use only R134a<br>600g ± 20g<br>(21.1 ± 0.7 oz.)<br><br><u>Refrigerant Oil</u><br>Use a PAG oil<br>with R134a | 4.5 L (4.8 qt)<br><br><u>Fluid PN</u><br>G 052 164* |
|  |  | N/A  | <b>7-Spd DSG<br/>(0B5)</b><br><br><u>New Fill:</u><br>7.5L (7.9qt)<br><br><u>Change:</u><br>6.7L (7.0qt)<br>approx.<br><br><u>Oil PN</u><br>G 052 529 A2* | <b>Front F/Drive</b><br><u>New Fill:</u><br>5.0L (5.3qt)<br><u>Oil PN</u><br>G 052 513 A2*<br><br><b>Transfer Case</b><br>5.0 L (5.3 qt.)<br><u>Oil PN</u><br>G 052 513 A2<br><br><b>Rear F/Drive<br/>(0BC / 0BF)</b><br><u>New Fill:</u><br>0.9L (1.0qt)<br><br><u>Oil PN</u><br>G 052 145 S2* |                    |   | Use new fluid only.<br><br>FMVSS 116 DOT 4<br>or SAE J 1703<br><br><u>Fluid PN</u><br>B 000 750*  | <u>Oil Capacity &amp; PN</u><br>For Denso<br><br>150 cc +/- 10 cc<br>G 052 300 A2*  |   |

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\*Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 201004 for engine oils that meet this Audi standard.

\*\*\* Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.