Executive Service

2012 A5 / S5 Coupe / Cab



Engine	Part	Part Number	Quantity	
	Oil Filter	06J115403Q	1	
2.0L TFSI: CAEB	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)	
2.02 // 51. CALD	Drain Plug Gasket	N 0138157	1	
	Air Filter – Coupe	8R0133843K	1	
	Air Filter - Cabrio	8R0133843D	1	

Engine	Part	Part Number	Quantity	
	Oil Filter	06E115562A	1	
3.0L V6: CCBA	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.2L (6.6qt)	
	Drain Plug Gasket	N 0138157	1	
	Air Filter	8K0133843	1	
	Also use o-ring:	N 90964301	1	

Engine	Part	Quantity	
	Oil Filter	079198405E	1
4.2L V8: CAUA	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	8.8L (9.3qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	8K0133843	1
	Also use o-ring:	N 90964301	1

Miscellaneous	Part	Part Number	Quantity
	Pollen Filter (20K Only) PR-9AK	8K0819439	1
	Pollen Filter (20K Only) PR-9AQ	8K0819439B	1
	Driver's Wiper Blade (Left)	8K1955425A	1
Miscellaneous	Passenger's Wiper Blade (Right) Coupe	8K1955426A	1
Miscellaneous	Passenger's Wiper Blade (Right) Cabrio	8F1955426A	1
	Battery	000915105DHDSP	1
	Battery	000915105DKDSP	1
	Battery	000915105DLDSP	1

6-16-2015

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.

Executive Service



Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

2012 A5 / S5

Coupe / Cab

Select CAR > Service Interval display >Reset oil change interval.



Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.

i) Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

6-16-2015

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.

A5, A5 Cabriolet and S5, S5 Cabriolet -2012 FLUID CAPACITY CHART created 14 Oct. 2011



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
A5 Coupe quattro	2.0L TFSI 211 hp (CAEB) 4.6L (4.9 qt)	6-Spd (0B2)	N/A	Rear F/Drive (0BC) New Fill:	7.8 L (8.2 qt)***	1.0 L (1.1qt) (approximately)	1.0 L (1.1qt) (approximately)	Refrigerant Use only R134a 600 g ± 20 g	4.5L (4.8 qt) Fluid PN
(8T3569)	Audi Oil Spec**	4.8L (5.1qt)		0.9L (1.0 qt)		<u>Fluid PN</u> G 002 000 *	Audi Brake Fluid Specification:	(21.1 oz. ± 0.7 oz.)	G 052 164*
Manual		<u>Oil PN</u> G 052 911 A2*		<u>Oil PN</u> G 052 145 S2*		or G 004 000*	Use new fluid only.	<u>Refrigerant Oil</u> Use a PAG oil with R134a	
A5 Cabriolet			CVT (0AW) New Fill:	Front F/Drive New Fill:	7.0 L (7.4 qt)***		FMVSS 116 DOT		
FWD			8.0 L (8.5 qt)	1.1L (1.2 qt)			4 or SAE J 1703	<u>Oil Capacity</u> Denso	
(8F756H) Auto			<u>Change:</u> 5.5 – 6.0 L (5.8 – 6.3 qt)	<u>Oil PN</u> G 055 190 A2*				150 cc +/- 10 cc (5.0 ± 0.3 fl. oz.)	
			<u>Oil PN</u> G 052 516 A2*				<u>Fluid PN</u> B 000 750 *	<u>Fluid PN</u> G 052 300 A2*	
A5 quattro			6-Spd (0B6)	Front F/Drive New Fill:	7.8 L (8.2 qt)*** Coupe	-			
(8T356L) Coupe-Auto		N/A	<u>New Fill:</u> 10.4 L (11.0 qt)	1.0L (1.1qt) Transfer Case					
(8F756A) Cabrio-Auto			<u>Oil PN</u> G 060 162 A2*	<u>New Fill:</u> 1.1L (1.1qt) <u>Oil PN</u> G 055 145 A2	7.0 L (7.4 qt)*** Cabriolet				
A5	-		8-Spd Tiptronic	Rear F/Drive	9.0 L (9.5 qt)***	-			
Coupe quattro			(OBK/OBL) <u>New Fill:</u> 9.0 L (9.5 qt)	(0BD) <u>New Fill:</u> 1.1L (1.1 qt)					
(8T356A) Automatic			<u>Oil PN</u> G 060 162 A2	<u>Oil PN</u> G 052 145 S2*					

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.

Page 1 of 2

© 2011 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

A5, A5 Cabriolet and S5, S5 Cabriolet -2012 FLUID CAPACITY CHART created 14 Oct. 2011



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
S5 Coupe quattro (8T35B9) Manual S5 Coupe quattro (8T35BL) Automatic	4.2L V8 354 hp (CAUA) 8.8L (9.3 qt) Audi Oil Spec**	6-Spd (0B4) 3.8L (4.0 qt) <u>Oil PN</u> G 052 911 A2* N/A	N/A 6-Spd (0B6) <u>New Fill:</u> 10.4L (11.0 qt) <u>Oil PN</u> G 060 162 A2*	Rear F/Drive (0BC) 0.9L (1.0 qt) Oil PN G 052 145 S2* Front F/Drive New Fill: 1.0L (1.1qt) Oil PN G 052 145 S2*	12.2 L (12.9qt)***	1.0 L (1.1qt) approximately <u>Fluid PN</u> G 002 000 * or G 004 000*	1.0 L (1.1qt) approximately <u>Audi Brake Fluid</u> <u>Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750 *	Refrigerant Use only R134a 600 g ± 20 g (21.1 oz. ± 0.7 oz.) Refrigerant-RS5 Use only R134a 570 g ± 20 g (20.1 oz. ± 0.7 oz.) Refrigerant Oil Use a PAG oil with R134a Oil Capacity	4.5L (4.8 qt) <u>Fluid PN</u> G 052 164*
S5 Cabriolet quattro (8F754Y) Automatic	3.0L V6 333 hp (CCBA) 6.2L (6.6 qt) <u>Audi Oil Spec**</u>	N/A	7-Spd DSG (0B5) <u>New Fill:</u> 7.5L (7.9 qt) <u>Change:</u> 6.7L (7.0 qt) approx. <u>Oil PN</u> G 052 529 A2*	Transfer Case <u>New Fill:</u> 5.0L (5.3 qt) <u>Oil PN</u> G 052 513 A2* Rear F/Drive (0BC / 0BF) <u>New Fill:</u> 0.9L (1.0 qt) <u>Oil PN</u> G 052 145 S2*	11.1 L (11.7qt)***			Denso 150 cc +/- 10 cc (5.0 ± 0.3 fl. oz.) <u>Fluid PN</u> G 052 300 A2*	

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.

Page 2 of 2

© 2011 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.