Executive Service

2012 A6



Engine	Part	Part Number	Quantity	
	Oil Filter	06J115403Q	1	
2.0L TFSI: CAEB	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)	
	Drain Plug Gasket	N 0138157	1	
	Air Filter	4G0133843K	1	

Engine	Part	Part Number	Quantity	
	Oil Filter	06E115562A	1	
3.0L TFSI: CGXB	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)	
	Drain Plug Gasket	N 0138157	1	
	Air Filter	4G0133843	1	

Miscellaneous	Part	Part Number	Quantity	
	Pollen Filter (20K Only)	4H0819439	1	
	Driver's Wiper Blade (Left)	4G1955425A	1	
	Passenger's Wiper Blade (Right)	8F1955426A	1	
	Battery	000915105CB	1	
	Battery	000915105CDDSP	1	
Miscellaneous	Battery	000915105CEDSP	1	
	Battery	000915105CFDSP	1	
	Battery	000915105DHCSP	1	
	Battery	000915105DKDSP	1	
	Battery	000915105DLDSP	1	
	Battery	000915105EE	1	

6-16-2015

Executive Service

2012 A6



Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select the CAR function button > Car systems control button > Servicing & checks > Service Interval displays > Reset oil change interval.



Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service
 Reminder remains stored even when the vehicle battery is disconnected.

6-16-2015

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.

A6 - 2012 FLUID CAPACITY CHART 04 April 2011



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Auto Trans	Front Final Drives	Rear Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
A6 FWD (4G25MH)	2.0L TFSI 211 hp (CAEB) 4.6L (4.9qt) Audi Oil Spec** VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	CVT (0AW) New Fill: 8.0L (8.5qt) Change: 5.5 - 6.0L (5.8-6.3qt) Oil PN G 052 516 A2*	Front F/Drive New Fill: 1.1L (1.2qt) Oil PN G 055 190 A2*	NA	9.6L (10.1 qt)***	1.0 L (1.1qt) (approximately) Fluid PN G 002 000 * or G 004 000*	1.0 L (1.1qt) (approximately) VW Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703	Refrigerant Use only R134a 570 ± 20g (20.1 ± 0.7 oz.) Refrigerant Oil Use a PAG oil with R134a Oil PN & Capacity For Denso use: 120 cc ± 10 cc	5.25L (5.5qt) Fluid PN G 052 164*
A6 quattro (4G251A) Sedan	3.0L TFSI 310 hp (CGXB) 6.8L (7.2 qt) Audi Oil Spec**: VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (OBKE) New Fill: 8.6L (9.0 qt) Refill: 3.6-4.0L (3.8-4.2 qt.) Oil PN G 060 162A2*	Front F/Drive New Fill: 1.0L (1.0 qt.) Refill: 0.9L (1.0 qt.) Oil PN G 052 145 A2*	Transfer Case New Fill: 1.0L (1.0 qt.) Refill: 0.85L (0.9 qt.) Oil PN G 055 145 A2 Rear F/Drive (0BC/OBF) 0.9L (1.0 qt) Oil PN G 052 145 S2*	12.0L (12.7 qt)***		<u>Fluid PN</u> B 000 750*	(4.0 ± 0.3 fl. oz.) G 052 300 A2*	

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

© 2011 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.