



Engine	Part	Part Number	Quantity
4.2L V8: CDRA	Oil Filter	079198405E	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	7.7L (8.1qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	4H0129620M	1

Engine	Part	Part Number	Quantity
6.3L W12: CEJA	Oil Filter	07C115562E	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	11.5L (12.1qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	4H0129620M	1

Miscellaneous	Part	Part Number	Quantity
Miscellaneous	Pollen Filter (20K Only)	4H0819439	1
	Driver's Wiper Blade (Left)	4H1955425B	1
	Passenger's Wiper Blade (Right)	4H1955426B	1
	Battery	000915105CDDSP	1
	Battery	000915105CEDSP	1
	Battery	000915105CFDSP	1
	Battery	000915105DLDSP	1



Resetting the indicator

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select the **CAR** function button > **Car systems** control button > **Servicing & checks** > **Service interval displays** > **Reset oil change interval**.



Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

A8 - 2012 FLUID CAPACITY CHART 13 May 2011

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
A8 quattro 4H25AA (NWB) 4H85AA (LWB)	4.2L V8 372 hp (CDRA) 7.7L (8.1 qt) <u>Audi Oil Spec:</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	N/A	8-Spd Tiptronic (0BK) <u>New Fill:</u> 8.6L (9.1qt) <u>Refill:</u> 3.6-4.0L (3.8-4.2 qt) <u>Oil PN</u> G 060 162 A2* Transfer Case w/separate oiling 1.0L (1.1 qt) <u>Oil PN</u> G 055 145 A2* Transfer Case common oiling with Front F/Drive 2.0L (2.1 qt) <u>Oil PN</u> G 055 145 A2*	Front F/Drive w/ separate oiling <u>New Fill:</u> 1.1L (1.2qt) <u>Refill:</u> 0.9L (1.0 qt) <u>Oil PN</u> G 052 145 S2* Rear F/Drive (0BF) 0.9L (1.0qt) <u>Oil PN</u> G 052 145 S2* Hydraulic Control Unit 0.85L (0.9 qt) <u>Oil PN</u> G 052 515 A2*	15.0L (15.9 qt)***	1.0 L (1.1qt) (approximately) <u>Fluid PN</u> G 002 000* or G 004 000*	1.0 L (1.1qt) (approximately) <u>VW Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	<u>Refrigerant</u> Use only R134a <u>Single Evaporator:</u> 780± 20g (27.5 oz ± 0.7 oz) <u>Dual Evaporator:</u> 930 ± 20g (32.8 oz ± 0.7 oz) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil Capacity</u> 130 cc ± 10 cc (4.4± 0.3 fl. oz.) <u>Oil Part No.</u> G 052 154 A2*	5.0 L (5.25 qt) <u>Fluid PN</u> G 052 164*

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

*** Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.**

****Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.**

***** Audi Coolant Additive Specification and Part Number:** (color is purple) G 12 plus-plus PN- G 012 A8G.

A8 L W12 - 2012 FLUID CAPACITY CHART 20 Mar. 2013

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Auto Trans	Transfer Case	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
A8L quattro (4H85GA)	6.3L W12 500 hp (CEJA) 11.5L (12.1 qt) <u>Audi Oil Spec:</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40 Funnels or aftermarket speed filling devices are not allowed when filling the engine with oil	8-Spd Tiptronic (0BK) <u>New Fill:</u> 8.6L (9.1qt) <u>Refill:</u> 3.6-4.0L (3.8-4.2 qt) <u>Oil PN</u> G 060 162 A2*	w/separate oiling 1.0L (1.1 qt) <u>Oil PN</u> G 055 145 A2* Common oiling with Front F/Drive 2.0L (2.1 qt) <u>Oil PN</u> G 055 145 A2*	Front F/Drive w/ separate oiling <u>New Fill:</u> 1.1L (1.2qt) <u>Refill:</u> 0.9L (1.0 qt) <u>Oil PN</u> G 052 145 S2* Rear F/Drive (0BF) 0.9L (1.0qt) <u>Oil PN</u> G 052 145 S2* Hydraulic Control Unit 0.85L (0.9 qt) <u>Oil PN</u> G 052 515 A2*	15.0L (15.9 qt)**	1.0 L (1.1qt) (approximately) <u>Fluid PN</u> G 002 000* or G 004 000*	1.0 L (1.1qt) (approximately) <u>VW Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	<u>Refrigerant</u> Use only R134a <u>Single Evaporator:</u> 780± 20g (27.5 oz ± 0.7 oz) <u>Dual Evaporator:</u> 930 ± 20g (32.8 oz ± 0.7 oz) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil Capacity</u> 130 cc ± 10 cc (4.4± 0.3 fl. oz.) <u>Oil Part No.</u> G 052 154 A2*	5.0 L (5.25 qt) <u>Fluid PN</u> G 052 164*

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard. **Funnels or aftermarket speed filling devices are not allowed when filling the engine with oil

*** Audi Coolant Additive Specification and Part Number: **G A13 A8J M1**