



Engine	Part	Part Number	Quantity
3.0L V6: CJWE	Oil Filter	06E115562A	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter PR-1L0	7L0129620	1
	Air Filter PR-1L2	7L0129620A	1

Engine	Part	Part Number	Quantity
3.0L V6: CJWB	Oil Filter	06E115562A	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter PR-1L0	7L0129620	1
	Air Filter PR-1L2	7L0129620A	1

Engine	Part	Part Number	Quantity
3.0L V6 TDI: CATA	Oil Filter	057115561M	1
	VW 507 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	8.2L (8.7qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter PR-1L0	7L0129620	1
	Air Filter PR-1L2	7L0129620A	1

Miscellaneous	Part	Part Number	Quantity
Miscellaneous	Pollen Filter (20K Only)	7H0819631A	1
	Driver's Wiper Blade (Left)	4L1955425B	1
	Passenger's Wiper Blade (Right)	4L1955426A	1
	Rear Wiper Blade	4L0955425	1
	Battery	000915105CEDSP	1
	Battery	000915105DHDSP	1
	Battery	000915105DKDSP	1
	Battery	000915105DLDSP	1

Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select function button **CAR** > control button **Systems*** > **Service interval display** > **Reset oil change interval** or **CAR** control button > **Car systems*** > **Servicing & checks** > **Service intervals** > **Reset oil change interval**.



Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

6-16-2015

Q7 - 2012 FLUID CAPACITY CHART updated 15 June 2012

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	8 Speed Auto Trans	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
Q7 SUV quattro (4LB5KA)	3.0L V6 280 hp (CJWE) 6.8L (7.2 qt.) <u>Audi Oil Spec**:</u> VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (0C8) New Fill: 10.6L (11.2 qt) <u>Oil PN</u> G 055 540 A2*	Front F/Drive New Fill: 1.0L (1.1qt) <u>Oil PN</u> G 052 145 S2* Transfer Case New Fill: 0.65L (0.7 qt.) <u>Oil PN</u> G 052 536 A2 Rear F/Drive (0AB) New Fill: 1.3L (1.4qt) <u>Oil PN</u> G 052 145 S2*	9.0L (9.5 qt)***	1.0 L (1.1qt) (approximately) <u>Fluid PN</u> G 002 000* or G 004 000*	1.0 L (1.1qt) (approximately) <u>VW Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	<u>Refrigerant</u> Use only R134a <u>1-Evaporator</u> 700g ± 50g (24.7 oz. ± 1.8 oz.) <u>2-Evaporators</u> 1050g ± 50g (37 oz. ± 1.8 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil Capacity</u> <u>1-Evaporator</u> 145cc ± 15cc (4.9 oz. ± 0.5 oz.) <u>2-Evaporators</u> 245cc ± 15cc (8.3 oz. ± 0.5 oz.) <u>Oil PN</u> G 052 300 A2*	4.5 L (4.8 qt) <u>Fluid PN</u> G 052 164*
Q7 TDI SUV quattro (4LB5RA)	3.0L V6 225 hp Diesel (CATA) 8.2L (8.6qt) <u>Audi Oil Spec:</u> VW 507 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (0C8) New Fill: 12.8L (13.5 qt) <u>Oil PN</u> G 055 540 A2*		<u>AdBlue® Tank</u> 23.0L (6.0 gal)**** <u>ISO Standard</u> 22241-1 Only fill with filling device VAS6542 & holding device SET740.				

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.