



Engine	Part	Part Number	Quantity
<b>2.0L TFSI: CAEB</b>	Oil Filter	06J115403Q	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	4G0133843K	1

Engine	Part	Part Number	Quantity
<b>3.0L TFSI: CTUA</b>	Oil Filter	06E115562A	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	4G0133843	1

Engine	Part	Part Number	Quantity
<b>4.0L FSI: CEUC</b>	Oil Filter	079198405D	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	8.3L (8.8qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	4G0133843	1

Miscellaneous	Part	Part Number	Quantity
<b>Miscellaneous</b>	Pollen Filter (20K Only)	4H0819439	1
	Driver's Wiper Blade (Left)	4G1955425A	1
	Passenger's Wiper Blade (Right)	8F1955426A	1
	Battery	000915105CB	1
	Battery	000915105CDDSP	1
	Battery	000915105CEDSP	1
	Battery	000915105CFDSP	1
	Battery	000915105DH CSP	1
Battery	000915105DKDSP	1	



Miscellaneous	Part	Part Number	Quantity
<i>Miscellaneous</i>	Battery	000915105DLDSP	1
	Battery	000915105EE	1

## Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select the **CAR** function button > **Car systems\*** control button > **Servicing & checks** > **Service Intervals** > **Reset oil change interval.**



### Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



### Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

# A6/S6 - 2013 FLUID CAPACITY CHART update 15 Nov. 2012

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Auto Trans	Front Final Drives	Rear Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
<b>A6</b> FWD (4G25MH)	<b>2.0L TFSI 211 hp (CAEB)</b> 4.6L (4.9qt)  <b>Audi Oil Spec**</b> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	<b>CVT (0AW)</b> <b>New Fill:</b> 8.0L (8.5qt)  <b>Change:</b> 5.5 - 6.0L (5.8–6.3qt) <b>Oil PN</b> G 052 516 A2*	<b>Front F/Drive</b>  New Fill: 1.1L (1.2qt)  <b>Oil PN</b> G 055 190 A2*	<b>NA</b>	10.0L (10.5 qt)***	Electro- mechanical	1.0 L (1.1qt) (approximately)  <b>VW Brake Fluid            Specification:</b>  Use new fluid only.  FMVSS 116 DOT 4 or SAE J 1703	<b>Refrigerant</b> Use only R134a 570 ± 20g (20.1 ± 0.7 oz.)  <b>Refrigerant Oil</b> Use a PAG oil with R134a  <b>Oil PN &amp; Capacity</b> For Denso use:  120 cc ± 10 cc (4.0 ± 0.3 fl. oz.)  G 052 300 A2*	w/o headlight wash 3.5L (3.5 qt.)  with headlight wash 4.9L (5.2 qt.)  <b>Fluid PN</b> G 052 164*
		<b>A6</b> quattro (4G25MA) Sedan	<b>8-Spd            Tiptronic            (0BKE)</b>  <b>New Fill:</b> 8.6L (9.0 qt)  <b>Refill:</b> 3.6-4.0L (3.8-4.2 qt.)  <b>Oil PN</b> G 060 162A2*	<b>Front F/Drive</b> <b>New Fill:</b> 1.0L (1.0 qt.)  <b>Refill:</b> 0.9L (1.0 qt.)  <b>Oil PN</b> G 052 145 A2*	<b>Transfer Case</b> <b>New Fill:</b> 1.0L (1.0 qt.)  <b>Refill:</b> 0.85L (0.9 qt.)  <b>Oil PN</b> G 055 145 A2  <b>Rear F/Drive            (0BC/0BF)</b> 0.9L (1.0 qt)  <b>Oil PN</b> G 052 145 S2*	10.0L (10.5 qt)***		<b>Fluid PN</b> B 000 750*	

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\*Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

\*\*\* Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.

# A6/S6 - 2013 FLUID CAPACITY CHART

update 15 Nov. 2012

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Auto Trans	Front Final Drives	Rear Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
<b>A6</b> quattro  (4G251A) Sedan	<b>3.0L TFSI</b> <b>310 hp (CTUA)</b>  6.8L (7.2 qt.)  <u>Audi Oil Spec**:</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	<b>8-Spd Tiptronic (OBKE)</b>  <u>New Fill:</u> 8.6L (9.0 qt)  <u>Refill:</u> 3.6-4.0L (3.8-4.2 qt.)  <u>Oil PN</u> G 060 162A2*	<b>Front F/Drive</b> <u>New Fill:</u> 1.0L (1.0 qt.)  <u>Refill:</u> 0.9L (1.0 qt.)  <u>Oil PN</u> G 052 145 A2*	<b>Transfer Case</b> <u>New Fill:</u> 1.0L (1.0 qt.)  <u>Refill:</u> 0.85L (0.9 qt.)  <u>Oil PN</u> G 055 145 A2  <b>Rear F/Drive (OBC/OBF)</b> 0.9L (1.0 qt)  <u>Oil PN</u> G 052 145 S2*	12.0L (12.7 qt)***	Electro-mechanical	1.0 L (1.1qt) (approximately)  <u>VW Brake Fluid Specification:</u>  Use new fluid only.  FMVSS 116 DOT 4 or SAE J 1703  <u>Fluid PN</u> B 000 750*	<u>Refrigerant</u> Use only R134a 570 ± 20g (20.1 ± 0.7 oz.)  <u>Refrigerant Oil</u> Use a PAG oil with R134a  <u>Oil PN &amp; Capacity</u> For Denso use:  120 cc ± 10 cc (4.0 ± 0.3 fl. oz.)  G 052 300 A2*	w/o headlight wash 3.5L (3.5 qt.)  with headlight wash 4.9L (5.2 qt.)  <u>Fluid PN</u> G 052 164*
<b>S6</b> quattro  (4G253Y) Sedan	<b>4.0L FSI</b> <b>420 hp (CEUC)</b>  8.3L (8.8 qt.)  <u>Audi Oil Spec:</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	<b>7-Spd S-tronic (OB5)</b>  <u>Automatic portion</u>  <u>New Fill:</u> 7.5L (7.9 qt)  <u>Change:</u> 6.7L (7.0 qt.)  <u>Oil PN</u> G 052 529 A2	<b>Front F/Drive</b> <u>New Fill:</u> 1.0L (1.0 qt.)  <u>Refill:</u> 0.9L (1.0 qt.)  <u>Oil PN</u> G 052 145 A2*	<b>Transfer Case</b> <u>New Fill:</u> 4.35L (4.5 qt.)  <u>Oil PN</u> G 055 532 A2  <b>Rear F/Drive (OBC/OBF)</b> 0.9L (1.0 qt.)  <u>Oil PN</u> G 052 145 S2*	15.0L (15.8 qt)***				

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\*Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

\*\*\* Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.