# **Executive Service**

## 2013 Q5



Engine	Part	Part Number	Quantity	
2.0L TFSI: CPMA	Oil Filter	06J115403Q	1	
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)	
	Drain Plug Gasket	N 0138157	1	
	Air Filter	8R0133843K	1	

Engine	Part	Part Number	Quantity		
2.0L TFSI Hybrid: CHJA	Oil Filter	06J115403Q	1		
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)		
	Drain Plug Gasket	N 0138157	1		
	Air Filter	8R0133843K	1		

Engine	Part	Part Number	Quantity	
	Oil Filter	06E115562A	1	
3.0L V6: CTUC	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)	
	Drain Plug Gasket	N 0138157	1	
	Air Filter	8K0133843	1	
	Also use o-ring:	N 90964301	1	

Miscellaneous	Part	Quantity	
	Pollen Filter (20K Only) PR-9AK	8K0819439	1
	Pollen Filter (20K Only) PR-9AQ	8K0819439B	1
	Driver's Wiper Blade (Left)	8R1955425B	1
	Passenger's Wiper Blade (Right)	8R1955426B	1
Miscellaneous	Rear Wiper Blade	8R0955425	1
Miscellaneous	Battery	000915105CCDSP	1
	Battery	000915105CDDSP	1
	Battery	000915105CEDSP	1
	Battery	000915105CFDSP	1
	Battery	8R0915105	1

6-15-2015

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.

## **Executive Service**

2013 Q5



### Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select the CAR function button > Service interval display > Reset oil change interval or CAR function button > Car systems\* control button > Servicing & checks > Service intervals > Reset oil change interval.



#### Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Do not exceed the time interval for the next service, even if the vehicle mileage is low.



#### Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

6-15-2015

### Q5 - 2013 FLUID CAPACITY CHART 15 Nov 2012



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
<b>Q5</b> SUV quattro (8RB52A)	2.0 TFSI 211 hp (CPMA)  4.6 L (4.9 qt)  Audi Oil Spec** VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or	8-Spd Tiptronic (OBK/OBL) New Fill: 8.6 L approx. (9.0 qt.) Refill 3.6-4.0 L	Front F/Drive New Fill: 1.0L (1.1qt)  Oil PN G 052 145 S2*  Rear F/Drive (0BD)	10.0 L (10.5qt)***	Electromechanical	1.0 L (1.1qt) (approximately)  VW Brake Fluid Specification: Use new fluid only.	Refrigerant Use only R134a 600g ± 15g (21.1 ± 0.5 oz.)  Refrigerant Oil Use a PAG oil with R134a	4.6 L (4.9 qt.)  Fluid PN G 052 164*
<b>Q5</b> SUV quattro (8RB57A)	3.0L V6 272 hp (CTUC)  6.8 L (7.2 qt.)  Audi Oil Spec**: VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	(3.8-4.2 qt.)  Oil PN G 060 162 A2*  Transfer Case 1.0 L (1.1 qt.) Oil PN G 055 145 A2*	1.0L (1.1qt)  Oil PN G 052 145 S2*	12.0 L (12.7qt)***		FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750*	Oil Capacity & PN For Denso  150 cc +/- 10 cc (5.1 ± 0.3 oz.)  G 052 300 A2*	

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

© 2012 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

<sup>\*</sup> Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

<sup>\*\*</sup>Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

<sup>\*\*\*</sup> Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.

### Q5 Hybrid - 2013 FLUID CAPACITY CHART 15 Nov 2012



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
Q5 Hybrid quattro (8RB5GA)	2.0 TFSI 245 hp (CHJA)  4.6L (4.9 qt)  Audi Oil Spec** VW 502 00 Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (OBWA)  New Fill: 8.6 L approx. (9.0 qt.)  Refill 4.0L (4.2 qt.)  Oil PN G 060 162 A2*  Transfer Case 1.0L (1.1 qt.)  Refill 0.8 L (0.8 qt.)  Oil PN G 055 145 A2*	Front F/Drive New Fill: 1.0L (1.1qt)  Refill 0.9 L (0.9 qt.)  Oil PN G 052 145 S2*  Rear F/Drive (0BC)  0.9L (0.9qt)  Oil PN G 052 145 S2*	10.0 L (10.5qt)***	Electromechanical	1.0 L (1.1qt) (approximately)  VW Brake Fluid Specification:  Use new fluid only.  FMVSS 116 DOT 4 or SAE J 1703  Fluid PN B 000 750*	Refrigerant Use only R134a 840g ± 20g (29.6 ± 0.7 oz.)  Refrigerant Oil Use a PAG oil with R134a  Oil Capacity & PN For Denso  150 cc +/- 10 cc (5.1 ± 0.3 oz.)  G 052 300 A2*	4.6 L (4.9 qt)  Fluid PN  G 052 164*

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

© 2012 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

<sup>\*</sup> Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

<sup>\*\*</sup>Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

<sup>\*\*\*</sup> Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.