



Engine	Part	Part Number	Quantity
<b>2.0L TFSI: CETA</b>	Oil Filter	06J115403Q	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.5L (4.8qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	1K0129620D	1

Engine	Part	Part Number	Quantity
<b>2.0L TFSI: CDMA</b>	Oil Filter	06D115562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.5L (4.8qt)
	Drain Plug + Gasket	N 90813202	1
	Air Filter	1K0129620	1

Miscellaneous	Part	Part Number	Quantity
<b>Miscellaneous</b>	Pollen Filter (20K Only)	1K1819653B	1
	Pollen Filter (20K Only)	TBD	1
	Driver's Wiper Blade (Left)	8J1955425A	1
	Passenger's Wiper Blade (Right)	8J1955426A	1
	Battery	000915105CDDSP	1
	Battery	000915105DHDSP	1

## Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

- Switch the ignition on.
- Pull the knob ⇒ *fig. 19*. The message, **Service due!** appears.



- Pull the knob until the display **Oil change in ----- mi (km)--- days** appears. If the **RESET** button is not pulled within 5 seconds, the display reset mode closes.



### Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage is low, the maximum period of one year from one service to the next must not be exceeded.



### Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

6-15-2015

# TT-TTS-TTRS - 2013 FLUID CAPACITY CHART 27 August 2012

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
<b>TT - quattro</b>  (8J35VL) Coupe  (8J95VL) Roadster	<b>2.0L TFSI 211 hp (CETA)</b> 4.5L (4.8 qt)  <u>Audi Oil Spec:</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	N/A	<b>6-Spd DSG (02E)</b>  <u>New Fill:</u> 6.9 L (7.3 qt)  <u>Change:</u> 5.5 L (5.8 qt) approx.  <u>Oil PN</u> G 052 182 A2*  <b>Bevel Box</b> <u>New Fill:</u> 0.9 L (1.0 qt)  <u>Oil PN</u> G 052 145 S2*	<b>Rear F/Drive (0BR)</b> 0.95 L (1.0 qt)  <u>Oil PN</u> G 052 145 S2*  <b>Haldex Clutch (4)</b> <u>New Fill:</u> 0.85 L (0.9 qt)  <u>Replacement:</u> 0.7 L (0.8 qt)  <u>Oil PN</u> G 055 175 A2*  <b>(0AV)</b> 0.95 L (1.0 qt)  <b>Haldex Clutch (2)</b> <u>New Fill:</u> 0.85 L (0.9 qt)  <u>Replacement:</u> 0.7 L (0.8 qt)  <u>Oil PN</u> G 055 175 A2*	9.0 L (9.5 qt)***	Electro-Mechanical	1.0 L (1.1 qt) (approximately)  <u>VW Brake Fluid Specification:</u>  Use new fluid only.  FMVSS 116 DOT 4 or SAE J 1703  <u>Fluid PN</u> B 000 750*	<u>Refrigerant Use only R134a</u> 500 ± 25 g (17.6 ± 0.9 oz.)  <u>Refrigerant Oil</u> Use a PAG oil with R134a  <u>Denso Compressor</u>  90 ± 10 cc (3.0 oz. ± 0.3 oz.)  <u>Part Number</u> G 052 300 A2  <u>Sanden Compressor</u>  110 cc ± 10 cc (3.7 oz. ± 0.3 oz.)  <u>Part Number</u> G 052 154 A2*	4.0 L (4.3 qt)  <u>Fluid PN</u> G 052 164*
<b>TTS - quattro</b>  (8J354L) Coupe  (8J954L) Roadster	<b>2.0L TFSI 265 hp (CDMA)</b> 4.5L (4.8 qt)  <u>VW Oil Spec:</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40		<b>6-Spd DSG (02E)</b>  <u>New Fill:</u> 6.9 L (7.3 qt)  <u>Change:</u> 5.5 L (5.8 qt) approx.  <u>Oil PN</u> G 052 182 A2*  <b>Bevel Box</b> <u>New Fill:</u> 0.9 L (1.0 qt)  <u>Oil PN</u> G 052 145 S2*	<b>Rear F/Drive (0BR)</b> 0.95 L (1.0 qt)  <u>Oil PN</u> G 052 145 S2*  <b>Haldex Clutch (4)</b> <u>New Fill:</u> 0.85 L (0.9 qt)  <u>Replacement:</u> 0.7 L (0.8 qt)  <u>Oil PN</u> G 055 175 A2*  <b>(0AV)</b> 0.95 L (1.0 qt)  <b>Haldex Clutch (2)</b> <u>New Fill:</u> 0.85 L (0.9 qt)  <u>Replacement:</u> 0.7 L (0.8 qt)  <u>Oil PN</u> G 055 175 A2*	8.6 L (9.1 qt)***		1.0 L (1.1 qt) (approximately)  <u>VW Brake Fluid Specification:</u>  Use new fluid only.  FMVSS 116 DOT 4 or SAE J 1703  <u>Fluid PN</u> B 000 750*	<u>Refrigerant Use only R134a</u> 500 ± 25 g (17.6 ± 0.9 oz.)  <u>Refrigerant Oil</u> Use a PAG oil with R134a  <u>Denso Compressor</u>  90 ± 10 cc (3.0 oz. ± 0.3 oz.)  <u>Part Number</u> G 052 300 A2  <u>Sanden Compressor</u>  110 cc ± 10 cc (3.7 oz. ± 0.3 oz.)  <u>Part Number</u> G 052 154 A2*	4.0 L (4.3 qt)  <u>Fluid PN</u> G 052 164*

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

\*\*Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

\*\*\* Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.

# TT-TTS-TTRS - 2013 FLUID CAPACITY CHART 27 August 2012

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drive	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
<b>TT RS - quattro</b>  (8J35R9) Coupe	<b>2.5L TFSI 360 hp (CEPB)</b> 6.5L (6.9 qt)  <b>Audi Oil Spec:</b> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	<b>6-Spd (0A6)</b> 2.3 L (2.4 qt.)  <b>Oil PN</b> G 052 171 A2*	N/A	<b>Front F/Drive</b> 0.9L (1.0 qt)  <b>Oil PN</b> G 052 145 S2*  <b>Rear F/Drive (OBR)</b> 0.95L (1.0 qt)  <b>Oil PN</b> G 052 145 S2*  <b>Haldex Clutch (4)</b> <b>New Fill:</b> 0.85 L (0.9 qt)  <b>Replacement:</b> 0.7 L (0.8 qt)  <b>Oil PN</b> G 055 175 A2*	9.0 L (9.5 qt)***	Electro-Mechanical	1.0 L (1.1 qt) (approximately)  <b>VW Brake Fluid Specification:</b>  Use new fluid only.  FMVSS 116 DOT 4 or SAE J 1703  <b>Fluid PN</b> B 000 750*	<b>Refrigerant</b> <b>Use only R134a</b> 500 ± 25 g (17.6 ± 0.9 oz.)  <b>Refrigerant Oil</b> Use a PAG oil with R134a  <b>Denso Compressor</b>  90 ± 10 cc (3.0 oz. ± 0.3 oz.)  <b>Part Number</b> G 052 300 A2  <b>Sanden Compressor</b>  110 cc ± 10 cc (3.7 oz. ± 0.3 oz.)  <b>Part Number</b> G 052 154 A2*	4.0 L (4.3 qt)  <b>Fluid PN</b> G 052 164*

**For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.**

**\* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.**

**\*\*Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.**

**\*\*\* Audi Coolant Additive Specification and Part Number: (color is purple) G 12 plus-plus PN- G 012 A8G.**