Executive Service

2014 A5 / S5 Coupe / Cab



Engine	Part	Part Number	Quantity
	Oil Filter	06J115403Q	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)
2.0L TFSI: CAED	Drain Plug Gasket	N 0138157	1
2.0L 11 31. CALD	Air Filter (Coupe) >> 04.11.2013	8R0133843K	1
	Air Filter (Coupe) 04.11.2013 >>	8K0133843M	1
	Air Filter (Cabriolet)	8R0133843D	1

Engine	Part	Part Number	Quantity		
	Oil Filter	06J115403Q	1		
2.0L TFSI: CPMB	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)		
	Drain Plug Gasket	N 0138157	1		
	Air Filter >> 04.11.2013	8R0133843K	1		
	Air Filter 04.11.2013 >>	8K0133843M	1		

Engine	Part	Part Number	Quantity	
	Oil Filter	06E115562A	1	
3.0L V6: CTUB	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)	
	Drain Plug Gasket	N 0138157	1	
	Air Filter Also use O-Ring:	8K0133843 N 90964301	1	

6-15-2015

Executive Service

2014 A5 / S5 Coupe / Cab



Miscellaneous	Part	Part Number	Quantity	
	Pollen Filter (20K Only) PR-9AK	8K0819439	1	
	Pollen Filter (20K Only) PR-9AQ	8K0819439B	1	
	Driver's Wiper Blade (Left)	8K1955425A	1	
Miscellaneous	Passenger's Wiper Blade (Right)	8K1955426A	1	
	Battery	000915105DHDSP	1	
	Battery	000915105DKDSP	1	
	Battery	000915105DLDSP	1	

Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select CAR function button > Service Interval display > Reset oil change interval or CAR function button > Car systems* control button > Servicing & Checks > Reset oil change interval.



Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service
 Reminder remains stored even when the vehicle battery is disconnected.

6-15-2015

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.





Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
A5 Coupe quattro (8T35G9) Manual A5 Cabriolet FWD (8F75GH) Auto	2.0L TFSI 220 hp (CAED) 4.6L (4.9 qt) Audi Oil Spec**	6-Spd (0B2) 4.5L (4.7qt) Oil PN G 052 911 A2*	N/A CVT (0AW) New Fill: 8.0 L (8.5 qt) Change: 5.5 - 6.0 L (5.8 - 6.3 qt) Oil PN G 052 516 A2*	Rear F/Drive (0BC) New Fill: 0.9L (1.0 qt) Oil PN G 052 145 S2* Front F/Drive New Fill: 1.1L (1.2 qt) Oil PN G 055 190 A2*	10.0 L (10.5 qt)***	1.0 L (1.1qt) (approximately) Audi Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750 *	Refrigerant Use only R134a 550 g ± 15 g (19.5 oz. ± 0.5 oz.) Refrigerant Oil Use a PAG oil with R134a Oil Capacity Denso 150 cc +/- 10 cc (5.0 ± 0.3 fl. oz.) Fluid PN	4.5L (4.8 qt) Fluid PN G 052 164*
A5 quattro (8F752A) Cabrio A5 Coupe quattro (8T352A)	2.0L TFSI 211 hp (CPMB) 4.6L (4.9 qt) Audi Oil Spec**	N/A	8-Spd Tiptronic (OBK/OBL) New Fill: 8.6 L (9.0 qt) Oil PN G 060 162 A2	Front F/Drive New Fill: 1.0L (1.1qt) Transfer Case New Fill: 1.1L (1.1qt) Oil PN G 055 145 A2 Rear F/Drive (0BD) New Fill: 1.0L (1.1 qt) Oil PN G 052 145 S2*			G 052 300 A2*	

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.





Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
S5 Coupe quattro (8T3549) Manual A5/S5 Coupe quattro (8T354Y) Cabriolet quattro (8F754Y) RS5 Coupe quattro (8T35XY) RS5 Cabriolet	3.0L V6 333 hp (TUB) 6.8L (7.2 qt) Audi Oil Spec** 4.2L V8 450 hp (CFSA) 9.7L (10.2 qt) Audi Oil Spec**	6-Spd (0B4) 3.8L (4.0 qt) Oil PN G 052 911 A2* N/A	7-Spd DSG (0B5) New Fill: 7.5L (7.9 qt) Change: 6.7L (7.0 qt) approx. Oil PN G 052 529 A2*	Front F/Drive New Fill: 1.0L (1.1qt) Oil PN G 052 145 S2* Transfer Case New Fill: 4.35L (4.5 qt) Oil PN G 052 513 A2* Rear F/Drive (0BC / 0BF) New Fill: 0.9L (1.0 qt) Oil PN G 052 145 S2*	11.1 L (11.7qt)*** 15.0 L (15.8qt)***	1.0 L (1.1qt) approximately Audi Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750 *	Refrigerant Use only R134a 550 g ± 15 g (19.5 oz. ± 0.5 oz.) Refrigerant-RS5 Use only R134a 570 g ± 20 g (20.1 oz. ± 0.7 oz.) Refrigerant Oil Use a PAG oil with R134a Oil Capacity Denso 150 cc +/- 10 cc (5.0 ± 0.3 fl. oz.) Fluid PN G 052 300 A2*	4.5L (4.8 qt) Fluid PN G 052 164*
quattro (8F75XY)								

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.