



Engine	Part	Part Number	Quantity
3.0L TFSI: CTUA	Oil Filter	06E115562A	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	4G0133843	1

Engine	Part	Part Number	Quantity
	Oil Filter	059198405	1
3.0L TDI: CPNB	VW 507 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.4L (6.8qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	4G0133843	1

Engine	Part	Part Number	Quantity
	Oil Filter	079198405D	1
4.0L FSI: CEUC	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	8.3L (8.8qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	4G0133843	1

Miscellaneous	Part	Quantity	
	Pollen Filter (20K Only)	4H0819439	1
	Driver's Wiper Blade (Left)	4G1955425A	1
	Passenger's Wiper Blade (Right)	8F1955426A	1
	Battery	000915105CCDSP	1
Miscellaneous	Battery	000915105CDDSP	1
Miscellaneous	Battery	000915105CEDSP	1
	Battery	000915105CFDSP	1
	Battery	000915105DHDSP	1
	Battery	000915105DKDSP	1
	Battery	000915105DLDSP	1

6-15-2015

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.

Executive Service

2014 A7 / S7



Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select CAR function button > Car systems* control button > Servicing & checks > Service Intervals > Reset oil change interval.



Note

If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



Tips

- Do not reset the display between oil changes, otherwise the display will be incorrect.
- The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

6-15-2015

A7 - 2014 FLUID CAPACITY CHART 01 Aug 2013



Vehicle	Engine Oil approx. qty. w/filter change	Manual Trans	Automatic Transmission	Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
A7 quattro (4GA51A)	3.0L TFSI 310 hp (CTUA) 6.8L (7.2 qt) Audi Oil Spec: VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	NA	8-Spd Tiptronic (OBKE) New Fill: 8.6L (9.0 qt) Refill: 3.6-4.0L (3.8-4.2 qt.) Oil PN G 060 162 A2 Transfer Case New Fill: 1.0L (1.0 qt.) Refill: 0.85L (0.9 qt.) Oil PN G 055 145 A2	Front F/Drive New Fill: 1.0L (1.0 qt.) Refill: 0.9L (1.0 qt.) Rear F/Drive (0BC/OBF) 0.9L (1.0 qt) Oil PN G 052 145 S2*	12.0 L (12.7 qt)***	1.0 L (1.1qt) (approximately) Fluid PN G 002 000* or G 004 000*	1.0 L (1.1qt) (approximately) VW Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750*	Refrigerant Use only R134a 570g ± 20g (20.11 ± 0.71 oz.) Refrigerant Oil Use a PAG oil with R134a Oil Capacity & PN For Denso 120 cc +/- 10 cc (4.06 ± 0.34 oz.) G 052 300 A2*	Windshield 3.5 L (3.7 qt) Windshield w/headlight 4.9L (5.2 qt.) Fluid PN G 052 164*

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J). Dilute with Distilled Water.

A7 - 2014 FLUID CAPACITY CHART 01 Aug 2013



Vehicle	Engine Oil approx. qty. w/filter change	Manual Trans	Automatic Transmission	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
A7 quattro (4GA5CA)	3.0L TDI 240 hp (CPNB) 6.4L (6.8 qt) Audi Oil Spec: VW 507 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	NA	8-Spd Tiptronic (OBKE) New Fill: 8.6L (9.0 qt) Refill: 3.6-4.0L (3.8-4.2 qt.) Oil PN G 060 162 A2 Transfer Case New Fill: 1.0L (1.0 qt.) Refill: 0.85L (0.9 qt.) Oil PN G 055 145 A2	Front F/Drive New Fill: 1.0L (1.0 qt.) Refill: 0.9L (1.0 qt.) Rear F/Drive (0BC/OBF) 0.9L (1.0 qt) Oil PN G 052 145 S2*	AdBlue® Tank 17.0L (4.5 gal)**** ISO Standard 22241-1 Only fill with filling device VAS6542 & holding device SET740.	1.0 L (1.1qt) (approximately) VW Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750*	Refrigerant Use only R134a 570g ± 20g (20.11 ± 0.71 oz.) Refrigerant Oil Use a PAG oil with R134a Oil Capacity & PN For Denso 120 cc +/- 10 cc (4.06 ± 0.34 oz.) G 052 300 A2*	Windshield 3.5 L (3.7 qt) Windshield w/headlight 4.9L (5.2 qt.) Fluid PN G 052 164*

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J). Dilute with Distilled Water.

^{****} Part Numbers for AdBlue® Reducing Agent: 0.5 gal (1.89 L) G 052 910 A2 for warranty repairs, 2.5 gal (10.0L) GUS 052 910 A3 for maintenance services.



Vehicle	Engine Oil approx. qty. w/filter change	Manual Trans	Automatic Transmission	Final Drives	Cooling System	Brake System	A/C System	Windshield Headlight Fluid
S7 Quattro (4GA53Y)	4.0L FSI 420 hp (CEUC) 8.3L (8.8 qt.) Audi Oil Spec: VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	NA	7-Spd S-tronic (0B5) Automatic portion New Fill: 7.0 - 7.5L (7.3 - 7.9 qt) Change: 5.5 - 6.0L (5.8 - 6.3 qt.) Oil PN G 052 529 A2 Transfer Case New Fill: 4.35L (4.5 qt.) Oil PN G 055 532 A2	Front F/Drive New Fill: 1.0L (1.0 qt.) Refill: 0.9L (1.0 qt.) Rear F/Drive (0BC/OBF) 0.9L (1.0 qt) Oil PN G 052 145 S2*	15.0 L (15.8 qt)***	1.0 L (1.1qt) (approximately) VW Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750*	Refrigerant Use only R134a 570g ± 20g (20.11 ± 0.71 oz.) Refrigerant Oil Use a PAG oil with R134a Oil Capacity & PN For Denso 120 cc +/- 10 cc (4.06 ± 0.34 oz.) G 052 300 A2*	Windshield 3.5 L (3.7 q Windshield w/headligh 4.9L (5.2 qt Fluid PN G 052 164

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J). Dilute with Distilled Water.

RS7 - 2014 FLUID CAPACITY CHART 01 Aug 2013



Vehicle	Engine Oil approx. qty. w/filter change	Manual Trans	Automatic Transmission	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
RS7 quattro (4GA5RA)	4.0L FSI 560 hp (CRDB) 8.3L (8.8 qt) Audi Oil Spec: VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-40 SAE 0W-40	NA	8-Spd Tiptronic (OBKD) New Fill: 8.6L (9.0 qt) Refill: 3.6-4.0L (3.8-4.2 qt.) Oil PN G 060 162 A2 Transfer Case New Fill: 1.0L (1.0 qt.) Refill: 0.85L (0.9 qt.) Oil PN G 055 145 A2	Front F/Drive New Fill: 1.0L (1.0 qt.) Refill: 0.9L (1.0 qt.) Rear F/Drive (0BC/OBF) 0.9L (1.0 qt) Oil PN G 052 145 S2*	15.0 L (15.8 qt)***	1.0 L (1.1qt) (approximately) VW Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750*	Refrigerant Use only R134a 530g ± 20g (18.6 ± 0.7 oz.) Refrigerant Oil Use a PAG oil with R134a Oil Capacity & PN For Denso 120 cc +/- 10 cc (4.06 ± 0.34 oz.) G 052 300 A2*	Windshield 3.5 L (3.7 qt) Windshield w/headlight 4.9L (5.2 qt.) Fluid PN G 052 164*

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW 774 J). Dilute with Distilled Water.