



Engine	Part	Part Number	Quantity
1.8L TFSI: CNSB	Oil Filter	06L115562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.9L (5.2qt)
	Drain Plug + Gasket	06L103801	1
	Air Filter	5Q0129620B	1

Engine	Part	Part Number	Quantity
2.0L TFSI: CNTC	Oil Filter	06L115562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	5.5L (5.8qt)
	Drain Plug + Gasket	06L103801	1
	Air Filter	5Q0129620B	1

Engine	Part	Part Number	Quantity
2.0L TDI: CRUA	Oil Filter	03N115562	1
	VW 507 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	5.5L (5.8qt)
	Drain Plug + Gasket	N 90813202	1
	Air Filter	5Q0129620C	1

Engine	Part	Part Number	Quantity
2.0L TFSI: CYFB	Oil Filter	06L115562	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	5.5L (5.8qt)
	Drain Plug + Gasket	06L103801	1
	Air Filter	5Q0129620B	1

6-15-2015



Miscellaneous	Part	Part Number	Quantity
<i>Miscellaneous</i>	Pollen Filter (20K Only) PR-KH6 >> 19.05.2014	5Q0819653	1
	Pollen Filter (20K Only) PR-KH6 19.05.2014 >>	5Q0819644A	1
	Pollen Filter (20K Only) PR-9AK	5Q0819653	1
	Wiper Blade Set (Left+Right)	8V1998002A	1
	Battery	000915105CCDSP	1
	Battery	000915105DEDSP	1
	Battery	000915105DGDSP	1

Resetting the indicator

Your authorized Audi dealer or authorized Audi Service Facility will reset the service interval display after performing service.

If you perform an oil change yourself to the Audi specifications, you must reset the service interval display.

To reset the display, select the **MENU** button > **Car** > **Systems*** control button > **Service & control** > **Service intervals** > **Reset oil change interval**.



Note

- Only reset the oil change indicator if the oil was changed.
- Following the service intervals is critical to maintaining the service life and value of your vehicle, especially the engine. Even if the mileage on the vehicle is low, do not exceed the time for the next service.
- Calculating the time to the next oil change is interrupted when the vehicle battery is disconnected. If the vehicle is not driven for a long period of time, check the maintenance schedule so that you can follow the maintenance intervals.

6-15-2015

A3 - 2015 FLUID CAPACITY CHART

UPDATE: Jul 31, 2014

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Auto Trans	Final Drive	Cooling System	Brake System	A/C System	Windshield Fluid
A3 FWD - Auto (8VS57X)	1.8L 170 hp (CNSB) 4.9L (5.2 qt.) <u>Audi Oil Spec:</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	6-Spd S tronic (0D9) <u>New Fill:</u> 6.9L (7.3) <u>Change:</u> 5.2L (5.4 qt.) <u>Mechatronic Only</u> 3-4L (3.1-4.2 qt) <u>Oil PN</u> G052 182 A2	Bevel Box <u>New Fill:</u> 0.9L (1.0qt) <u>Oil PN</u> G 052 145 S2*	10.0L (10.5 qt)***	1.0 L (1.1qt) (approximately) <u>Audi Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750 *	<u>Refrigerant</u> Use only R134a <u>Refrig. Capacity</u> 500 +/- 15 g (17.5 ± 0.5 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil PN & Capacity</u> 1) For Sanden use 75 cc +/- 10 cc (2.5 ± 0.3 fl. oz.) 2) For Delphi use 110 cc +/- 15 cc (3.7 ± 0.5 fl. oz.) 3) For Denso use 110 cc +/- 10 cc (3.7 ± 0.3 fl. oz.) G 052 300 A2* G 052 154 A2*	3.1L (3.2qt) <u>Fluid PN</u> G 052 164*
			Haldex Clutch <u>New Fill:</u> 0.85L (0.9qt) <u>Replacement:</u> 0.65L(0.7qt) <u>Oil PN</u> G 060 175 A2*				
A3 quattro (8VS58L)	2.0 TFSI 220 hp (CNTC) 5.5L (5.8 qt.) <u>Audi Oil Spec:</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40			10.0L (10.5 qt)***			

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) **G 13** (TL-VW 774 J). **Dilute with Distilled Water.**

A3 - 2015 FLUID CAPACITY CHART

UPDATE: Jul 31, 2014

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Auto Trans	Final Drive	Cooling System	Brake System	A/C System	Windshield Fluid
A3 TDI FWD (8VS5RX) (8VSPRX) (8VSXRX)	2.0L 150 hp (CRUA) 5.5L (5.8 qt.) <u>Audi Oil Spec:</u> VW 507 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	6-Spd S tronic (0D9) <u>New Fill:</u> 6.9L (7.3) <u>Change:</u> 5.2L (5.4 qt.) <u>Mechatronic Only</u> 3-4L (3.1-4.2 qt) <u>Oil PN</u> G052 182 A2	Bevel Box <u>New Fill:</u> 0.9L (1.0qt) <u>Oil PN</u> G 052 145 S2*	8.0L (8.4 qt)***	<u>Audi Brake Fluid</u> <u>Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750 *	<u>Refrigerant</u> Use only R134a <u>Refrig. Capacity</u> 500 +/- 15 g (17.5 ± 0.5 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil PN & Capacity</u> 1) For Sanden use 75 cc +/- 10 cc (2.5 ± 0.3 fl. oz.) 2) For Delphi use 110 cc +/- 15 cc (3.7 ± 0.5 fl. oz.) 3) For Denso use 110 cc +/- 10 cc (3.7 ± 0.3 fl. oz.) G 052 300 A2* G 052 154 A2*	3.1L (3.2qt) <u>Fluid PN</u> G 052 164*
			Haldex Clutch <u>New Fill:</u> 0.85L (0.9qt) <u>Replacement:</u> 0.65L(0.7qt) <u>Oil PN</u> G 060 175 A2* Rear Final Drive 0.95L (1.0 qt) <u>Oil PN</u> G 052 145 A1*				<u>AdBlue® Tank</u> <u>New Fill</u> 17.0L (17.9 qt.) <u>Refill</u> 15.0 L - (15.8 qt.)**** <u>ISO Standard</u> 22241-1

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

** Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) **G 13** (TL-VW 774 J). **Dilute with Distilled Water.**

**** Part Numbers for AdBlue® Reducing Agent: 0.5 gal (1.89 L) G 052 910 A2 for warranty repairs, 2.5 gal (10.0L) GUS 052 910 A3 for maintenance services.

S3 - 2015 FLUID CAPACITY CHART

February 2, 2015

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Auto Trans	Final Drive	Cooling System	Brake System	A/C System	Windshield Fluid
S3 quattro (8VS51L)	2.0 TFSI 292 hp (CYFB) 5.5L (5.8 qt.) <u>Audi Oil Spec:</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	6-Spd S tronic (0D9) <u>New Fill:</u> 6.9L (7.3) <u>Change:</u> 5.2L (5.4 qt.) <u>Mechatronic Only</u> 3-4L (3.1-4.2 qt) <u>Oil PN</u> G052 182 A2	Bevel Box <u>New Fill:</u> 0.9L (1.0qt) <u>Oil PN</u> G 052 145 S2* Haldex Clutch <u>New Fill:</u> 0.85L (0.9qt) <u>Replacement:</u> 0.65L(0.7qt) <u>Oil PN</u> G 060 175 A2* Rear Final Drive 0.95L (1.0 qt) <u>Oil PN</u> G 052 145 A1*	10.0L (10.5 qt)***	1.0 L (1.1qt) (approximately) <u>Audi Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750 *	<u>Refrigerant</u> Use only R134a <u>Refrig. Capacity</u> 500 +/- 15 g (17.5 ± 0.5 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil PN & Capacity</u> 1) For Sanden use 75 cc +/- 10 cc (2.5 ± 0.3 fl. oz.) 2) For Delphi use 110 cc +/- 15 cc (3.7 ± 0.5 fl. oz.) 3) For Denso use 110 cc +/- 10 cc (3.7 ± 0.3 fl. oz.) G 052 300 A2* G 052 154 A2*	3.1L (3.2qt) <u>Fluid PN</u> G 052 164*

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in Elsa.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) **G 13** (TL-VW 774 J). **Dilute with Distilled Water.**