Executive Service

2015 A5 / S5 Coupe / Cab



Engine	Part	Part Number	Quantity	
2.0L TFSI: CAED	Oil Filter	06J115403Q	1	
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)	
2.0E 11 31. CALD	Drain Plug Gasket	N 0138157	1	
	Air Filter (Coupe)	8K0133843M	1	
	Air Filter (Cabriolet)	8R0133843D	1	

Engine	Part	Part Number	Quantity
2.0L TFSI: CPMB	Oil Filter	06J115403Q	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	8K0133843M	1

Engine	Part	Part Number	Quantity	
	Oil Filter >> 25.11.2014	06E115562A	1	
	Oil Filter 25.11.2014 >>	06E115562C	1	
3.0L V6: CTUB	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)	
	Drain Plug Gasket	N 0138157	1	
	Air Filter Also use O-Ring:	8K0133843 N 90964301	1	

Miscellaneous	Part	Part Number	Quantity	
	Pollen Filter (20K Only) PR-9AK	8K0819439	1	
	Pollen Filter (20K Only) PR-9AQ	8K0819439B	1	
	Driver's Wiper Blade (Left)	8K1955425A	1	
Miscellaneous	Passenger's Wiper Blade (Right)	8K1955426A	1	
	Battery	000915105DHDSP	1	
	Battery	000915105DKDSP	1	
	Battery	000915105DLDSP	1	

6-15-2015

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.

Executive Service

2015 A5 / S5 Coupe / Cab



Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select CAR function button > Service Interval display > Reset oil change interval or CAR function button > Car systems* control button > Servicing & Checks > Reset oil change interval.



Note

- Only reset the oil change display when you have completed an oil change.
- If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



Tips

The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

6-15-2015

© 2015 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher. All parts and service references provided in this document are subject to change and/or removal. Always check with your Parts Department and service manuals for the latest information.



A5, A5 Cabriolet S5,RS5 2015 FLUID CAPACITY CHART 31July 2014 Final

	gabiloidt e	0 1 0 0 0 0 0 0 0 0 		<u> </u>	<u> </u>	Toury 2014 I Illai		
Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
A5	2.0L TFSI 220 hp	6-Spd	N/A	Rear F/Drive	10.0 L (10.5 qt)***	1.0 L (1.1qt)	Refrigerant	4.5L (4.8 qt)
Coupe	(CAED)	(0B2)		(0BC)	(**************************************	(approximately)	Use only R134a	(4.7
quattro	4.6L (4.9 qt)	(- /		New Fill:		(3)1	550 g ± 15 g	Fluid PN
'	(1,	4.5L (4.7qt)		0.9L (1.0 qt)		Audi Brake Fluid	(19.5 oz. ± 0.5 oz.)	G 052 164*
(8T35G9)	Audi Oil Spec**	(1,		(1,		Specification:		
`Manual ´	VW 502 00**	Oil PN		Oil PN			Refrigerant Oil	
	Use synthetic oil	G 055 532 A2*		G 052 145 S2*		Use new fluid only.	Use a PAG oil	
A5	SAE 5W-40,		CVT (0AW)	Front F/Drive		-	with R134a	
Cabriolet	SAE 5W-30 or SAE 0W-40		New Fill:	New Fill:		FMVSS 116 DOT 4		
FWD	SAE UW-40		8.0 L (8.5 qt)	1.1L (1.2 qt)		or SAE J 1703		
							Oil Capacity	
(8F75GH)			Change:	Oil PN			Denso	
Auto			5.5 – 6.0 L	G 055 190 A2*			150 cc +/- 10 cc	
			(5.8 – 6.3 qt)			Fluid PN	$(5.0 \pm 0.3 \text{ fl. oz.})$	
			Oil PN			B 000 750 *		
			G 052 516 A2*				Fluid PN	
A5	2.0L TFSI 211 hp		8-Spd	Front F/Drive			G 052 300 A2*	
quattro	(CPMB)		Tiptronic	New Fill:				
	4.6L (4.9 qt)		(OBK/OBL)	1.0L (1.1qt)				
			New Fill:	Transfer Case				
(8F752A)	Audi Oil Spec**	N/A	8.6 L (9.0 qt)	New Fill:				
Cabrio	VW 502 00**			1.1L (1.1qt)				
	Use synthetic oil SAE 5W-40,		Change:	Change:				
	SAE 5W-30 or		3.6 - 4.0L	0.8L (0.84 qt.)				
	SAE 0W-40		(3.8 - 4.2 qt.)	OH DN				
A5	1		OH DN	Oil PN				
Coupe			<u>Oil PN</u> G 060 162 A2	G 055 145 A2				
quattro			G 000 102 A2	Rear F/Drive (0BD)				
				New Fill:				
(8T352A)				1.0L (1.1 qt)				
				1.02 (1.1 qt)				
				Oil PN				
				G 052 145 S2*				

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

© 2014 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.

A5, A5 Cabriolet S5,RS5 2015 FLUID CAPACITY CHART 31 July 2014 Final



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Manual Trans	Auto Trans	Final Drives	Cooling System	Brake System	A/C System	Windshield & Headlight Fluid
S5	3.0L V6 333 hp	6-Spd	N/A	Front F/Drive	12.0 L (12.6 qt)***	1.0 L (1.1qt)	Refrigerant	4.5L (4.8 qt)
Coupe	(CTUB)	(0B4)		New Fill:		approximately	Use only R134a	
quattro	6.8L (7.2 qt)			1.0L (1.1qt)			550 g ± 15 g	Fluid PN
		3.8L (4.0 qt)				Audi Brake Fluid	$(19.5 \text{ oz.} \pm 0.5)$	G 052 164*
(8T3549)				<u>Oil PN</u>		Specification:	oz.)	
Manual	Audi Oil Spec**	Oil PN		G 052 145 S2*				
	VW 502 00**	G 052 911 A2*				Use new fluid	Refrigerant-RS5	
A5/S5	Use synthetic oil SAE 5W-40,		7-Spd DSG	Transfer Case		only.	Use only R134a	
Coupe	SAE 5W-30 or	N/A	(0B5)	New Fill:			570 g ± 20 g	
quattro	SAE 0W-40		New Fill:	4.35L (4.5 qt)		FMVSS 116 DOT	(20.1 oz. ± 0.7	
			7.0 - 7.5L			4	oz.)	
(8T354Y)			(7.3 - 7.9 qt)	<u>Oil PN</u> G 052 532 A2*		or SAE J 1703		
Cabriolet			Change:				Refrigerant Oil	
quattro			6.7L (7.0 qt)	Rear F/Drive			Use a PAG oil	
(8F754Y)			approx.	(0BC / 0BF)		Fluid PN	with R134a	
(/				New Fill:		B 000 750 *		
RS5	4.2L V8 450 hp	N/A	Oil PN	0.9L (1.0 qt)	15.0 L (15.8qt)***	-		
Coupe	(CFSA)		G 052 529 A2*	, , ,	(() () ()		Oil Capacity	
quattro	9.7L (10.2 qt)			Oil PN			Denso	
1	(1)			G 052 145 S2*			150 cc +/- 10 cc	
(8T35XY)							$(5.0 \pm 0.3 \text{ fl. oz.})$	
()	Audi Oil Spec**							
RS5	VW 502 00**						Fluid PN	
Cabriolet	Use synthetic oil						G 052 300 A2*	
quattro	SAE 5W-40, SAE 5W-30 or SAE 0W-40							
(8F75XY)								

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

© 2014 Audi of America, Inc. All rights reserved. Information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Audi of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.

^{*} Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

^{**}Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

^{***} Audi Coolant Additive Specification and Part Number: (color is pink) G 13 (TL-VW774J). Dilute with Distilled Water.