



Engine	Part	Part Number	Quantity
2.0L TFSI: CAED	Oil Filter	06J115403Q	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	4.6L (4.9qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	4G0133843K	1

Engine	Part	Part Number	Quantity
3.0L TFSI: CTUA	Oil Filter >> 25.11.2014	06E115562A	1
	Oil Filter 25.11.2014 >>	06E115562C	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.8L (7.2qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	4G0133843	1

Engine	Part	Part Number	Quantity
3.0L TDI: CPNB	Oil Filter	059198405	1
	VW 507 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	6.4L (6.8qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	4G0133843	1

Engine	Part	Part Number	Quantity
4.0L FSI: CEUC	Oil Filter	079198405D	1
	VW 502 00 Use synthetic oil SAE 5W-40, SAE-5W-30, or SAE-0W-40	N/A	8.3L (8.8qt)
	Drain Plug Gasket	N 0138157	1
	Air Filter	4G0133843	1

6-15-2015



Miscellaneous	Part	Part Number	Quantity
<i>Miscellaneous</i>	Pollen Filter (20K Only)	4H0819439	1
	Driver's Wiper Blade (Left)	4G1955425A	1
	Passenger's Wiper Blade (Right)	8F1955426A	1
	Battery	000915105CB	1
	Battery	000915105CDDSP	1
	Battery	000915105CEDSP	1
	Battery	000915105CFDSP	1
	Battery	000915105DHDSP	1
	Battery	000915105DKDSP	1
	Battery	000915105DLDSP	1
Battery	000915105EE	1	

Resetting the service interval display

Your authorized Audi dealer will reset the corresponding service schedule after performing the appropriate service on your vehicle. You also have the possibility to reset the oil change schedule after having performed an oil change according to Audi specifications.

Select the **CAR** function button > **Car systems*** control button > **Servicing & checks** > **Service Intervals** > **Reset oil change interval**.



Note

- Only reset the oil change display when you have completed an oil change.
- If you disconnect the battery terminals, no calculations can be made for the service interval display during this time and no service reminder will appear. Remember that observing the proper service intervals is vitally important to extending the life of your vehicle, particularly the engine, and maintaining its value. Even if the mileage driven is low, the maximum period of one year from one service to the next must not be exceeded.



Tips

The information in the Service Reminder remains stored even when the vehicle battery is disconnected.

A6 - 2015 FLUID CAPACITY CHART 31 July 2014 Final

Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Auto Trans	Front Final Drives	Rear Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
A6 FWD (4G25MH)	2.0L TFSI 220 hp (CAED) 4.6L (4.9qt) <u>Audi Oil Spec**</u> VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	CVT (0AW) <u>New Fill:</u> 8.0L (8.5qt) <u>Change:</u> 5.5 - 7.0L (5.8-7.3qt) <u>Oil PN</u> G 052 516 A2*	Front F/Drive New Fill: 1.1L (1.2qt) <u>Oil PN</u> G 055 190 A2*	NA	10.0L (10.5 qt)***	Electro-mechanical	1.0 L (1.1qt) (approximately) <u>VW Brake Fluid Specification:</u> Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 <u>Fluid PN</u> B 000 750*	<u>Refrigerant</u> Use only R134a 570 ± 20g (20.1 ± 0.7 oz.) <u>Refrigerant Oil</u> Use a PAG oil with R134a <u>Oil PN & Capacity</u> For Denso use: 120 cc ± 10 cc (4.0 ± 0.3 fl. oz.) G 052 300 A2*	w/o headlight wash 3.5L (3.7 qt.) with headlight wash 4.9L (5.2 qt.) <u>Fluid PN</u> G 052 164*
A6 quattro (4G25MA) Sedan		8-Spd Tiptronic (OBKD) <u>New Fill:</u> 8.6L (9.0 qt) <u>Refill:</u> 3.6-4.0L (3.8-4.2 qt.) <u>Oil PN</u> G 060 162A2*	Front F/Drive <u>New Fill:</u> 1.0L (1.0 qt.) <u>Refill:</u> 0.9L (1.0 qt.) <u>Oil PN</u> G 052 145 A2*	Transfer Case <u>New Fill:</u> 1.0L (1.0 qt.) <u>Refill:</u> 0.85L (0.9 qt.) <u>Oil PN</u> G 055 145 A2 Rear F/Drive (OBC/OBF) 0.9L (1.0 qt) <u>Oil PN</u> G 052 145 S2*	10.0L (10.5 qt)***				

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) G13 (TL-VW774J). Dilute with Distilled Water.

A6/S6 - 2015 FLUID CAPACITY CHART

31 July 2014 Final



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Auto Trans	Front Final Drives	Rear Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
A6 quattro (4G251A) Sedan	3.0L TFSI 310 hp (CTUA) 6.8L (7.2 qt.) Audi Oil Spec**: VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (0BKH) New Fill: 8.6L (9.0 qt) Refill: 3.6-4.0L (3.8-4.2 qt.) Oil PN G 060 162 A2*	Front F/Drive New Fill: 1.0L (1.0 qt.) Refill: 0.9L (1.0 qt.) Oil PN G 052 145 A2*	Transfer Case New Fill: 1.0L (1.0 qt.) Refill: 0.85L (0.9 qt.) Oil PN G 055 145 A2 Rear F/Drive (0BC/OBF) 0.9L (1.0 qt) Oil PN G 052 145 S2*	12.0L (12.7 qt)***	Electro- mechanical	1.0 L (1.1qt) (approximately) VW Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750*	Refrigerant Use only R134a 570 ± 20g (20.1 ± 0.7 oz.) Refrigerant-S6 Use only R134a 530 ± 20g (18.6 ± 0.7 oz.) Refrigerant Oil Use a PAG oil with R134a Oil PN & Capacity For Denso use: 120 cc ± 10 cc (4.0 ± 0.3 fl. oz.) G 052 300 A2*	w/o headlight wash 3.5L (3.7 qt.) with headlight wash 4.9L (5.2 qt.) Fluid PN G 052 164*
S6 quattro (4G253Y) Sedan	4.0L FSI 420 hp (CEUC) 8.3L (8.8 qt.) Audi Oil Spec: VW 502 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	7-Spd S-tronic (0B5) Automatic portion New Fill: 7.0 - 7.5L (7.3 - 7.9 qt) Change: 6.7L (7.0 qt.) Oil PN G 052 529 A2	Front F/Drive New Fill: 1.0L (1.0 qt.) Refill: 0.9L (1.0 qt.) Oil PN G 052 145 A2*	Transfer Case New Fill: 4.35L (4.5 qt.) Oil PN G 055 532 A2 Rear F/Drive (0BC/OBF) 0.9L (1.0 qt.) Oil PN G 052 145 S2*	15.0L (15.8 qt)***				

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 502 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) G13 (TL-VW774J). Dilute with Distilled Water.

A6/S6 - 2015 FLUID CAPACITY CHART

31 July 2014 Final



Vehicle (Sales Code)	Engine Oil approx. qty. w/filter change	Auto Trans	Front Final Drives	Rear Final Drives	Cooling System	Power Steering	Brake System	A/C System	Windshield & Headlight Fluid
A6 quattro (4G25CA) Sedan	3.0L TDI 240 hp (CPNB) 6.4L (6.8 qt.) Audi Oil Spec**: VW 507 00** Use synthetic oil SAE 5W-40, SAE 5W-30 or SAE 0W-40	8-Spd Tiptronic (OBK) New Fill: 8.6L (9.0 qt) Refill: 3.6 - 4.0L (3.8 - 4.2 qt.) Oil PN G 060 162A2*	Front F/Drive New Fill: 1.0L (1.0 qt.) Refill: 0.9L (1.0 qt.) Oil PN G 052 145 A2*	Transfer Case New Fill: 1.0L (1.0 qt.) Refill: 0.85L (0.9 qt.) Oil PN G 055 145 A2 Rear F/Drive (OBC/OBF) 0.9L (1.0 qt) Oil PN G 052 145 S2*	12.0L (12.7 qt)***	Electro- mechanical	1.0 L (1.1qt) (approximately) VW Brake Fluid Specification: Use new fluid only. FMVSS 116 DOT 4 or SAE J 1703 Fluid PN B 000 750*	Refrigerant Use only R134a 570 ± 20g (20.1 ± 0.7 oz.) Refrigerant-S6 Use only R134a 530 ± 20g (18.6 ± 0.7 oz.) Refrigerant Oil Use a PAG oil with R134a Oil PN & Capacity For Denso use: 120 cc ± 10 cc (4.0 ± 0.3 fl. oz.) G 052 300 A2*	w/o headlight wash 3.5L (3.7 qt.) with headlight wash 4.9L (5.2 qt.) Fluid PN G 052 164* AdBlue® Tank 17.0L (4.5 gal)**** ISO Standard 22241-1 Only fill with filling device VAS6542 & holding device SET740.

For proper fluid level and filling information, see the Repair Manual and/or Maintenance Manual in ElsaWeb.

* Oil and fluid part numbers are for reference only. Always check with your Parts Department for the latest part information.

**Audi Oil Specification: VW 507 00. Use synthetic oil SAE 5W-40, 5W-30 or 0W-40. Refer to Technical Bulletin 2010043 for engine oils that meet this Audi oil standard.

*** Audi Coolant Additive Specification and Part Number: (color is pink) G13 (TL-VW774J). Dilute with Distilled Water.

**** Part Numbers for AdBlue® Reducing Agent: 0.5 gal (1.89 L) G 052 910 A2 for warranty repairs, 2.5 gal (10.0L) GUS 052 910 A3 for maintenance services.